

## DisplayPort to DVI over Cat5/6 Active Extender Kit, Pigtail-Style Transmitter/Receiver for Video/Audio, 1080p @ 60 Hz

MODEL NUMBER: **B150-1A1-DVI**



### Description

The B150-1A1-DVI DisplayPort to DVI over Cat5/6 Active Extender Kit includes a transmitter unit and a receiver unit that work in tandem to convert a DisplayPort audio/video signal to DVI and then extend it to a projector, monitor or television up to 125 feet away. The kit is ideal for digital signs, trade shows, presentations, classrooms, churches, retail settings and other applications where the video source is located farther than convention cables allow.

One Cat5e/6 cable connects the transmitter and receiver (for best results, use 24 AWG solid-wire Cat5e/6 cable, such as Tripp Lite's N202-Series). A built-in DisplayPort plug connects the transmitter to the source, while a built-in DVI-D single-link plug connects the receiver to the display. Included USB Micro-B cables supply power to the units via USB ports on the source and display or USB wall chargers. No external power supplies are needed.

The B150-1A1-DVI can extend a high-definition 1920 x 1080 (60 Hz) signal up to 125 feet. In addition to crystal-clear video, including 24-bit True Color (8 bits per channel), the kit delivers full, rich stereo. LEDs on the RJ45 ports indicate when the units are receiving power and a DVI signal from the source. Built-in equalization control lets you fine-tune the image on the DVI display. Easy to set up with no software or drivers to install. Compatible with all operating systems. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

### Features

#### Converts DisplayPort Signal to DVI, Extends It Up to 125 Ft.

- Ideal for digital signs, trade shows, presentations, classrooms, churches and retail settings
- Extends a high-definition 1920 x 1080 (60 Hz) signal up to 125 ft.
- Transmitter and receiver connect with one Cat5e/6 cable (for best results, use 24 AWG solid-wire Cat5e/6 cable, such as Tripp Lite's N202-Series)
- Supports 24-bit True Color (8 bits per channel) and stereo audio
- Built-in equalization control lets you adjust the image on the display

### Highlights

- Supports high-definition video resolutions up to 1920 x 1080 (60 Hz)
- Supports 24-bit True Color (8 bits per channel) and stereo audio
- Included USB Micro-B cables supply power to both units
- Works with all operating systems
- Plug and play—no software or drivers to install

### System Requirements

- Computer with DisplayPort output port\*
- Display with DVI-D input port

\*DisplayPort source must be enabled to support audio in order for kit to extend audio signals

### Package Includes

- Transmitter unit
- Receiver unit
- Screwdriver for adjusting equalization
- (2) USB Micro-B cables, 3 ft.
- Owner's manual



#### Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers to download and install
- Works with all operating systems
- Built-in cables connect transmitter to DisplayPort source and receiver to DVI-D display
- Included USB Micro-B cables provide power to the units
- LEDs indicate when the units are receiving power and sharing a signal

#### TAA Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

INPUT	
Cable Length (ft.)	1
Cable Length (m)	0.3
PHYSICAL	
Color	Black
CONNECTIONS	
Connector A	DISPLAYPORT (MALE)
Connector B	DVI-D SINGLE LINK (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>