

# ActivBoard 387 PRO Mobile System

## Product Specifications

### INTERACTIVE WHITEBOARD SYSTEM

The ActivBoard Mobile System, featuring ActivBoard reliability and a state-of-the-art extreme short throw projector (EST), provides high performance all-in-one capabilities in a modular, movable package.

### ACTIVBOARD GENERAL SPECIFICATIONS

<b>Internal Resolution</b>	2730 points (lines) per inch
<b>Output Resolution</b>	200 points (lines) per inch
<b>Tracking Rate</b>	200 inches per second providing a fast response to pen commands
<b>Output Rate</b>	120 coordinate pairs per second
<b>User Input</b>	Cordless Battery-free pen incorporating tip switch and side switch for full mouse functionality (ActivPen)
<b>Digitizing Technology</b>	Passive Electromagnetic
<b>Power Requirement</b>	USB powered device
<b>Connection to Computer</b>	USB
<b>Screen Surface</b>	Low Glare Melamine
<b>Certifications</b>	UL, CE, FCC
<b>Dual User Functionality</b>	2 Teacher and 2 Student ActivPens included
<b>Integrated USB Sound</b>	Two integrated slim line speakers and amplifier (with controls, inputs and outputs)
<b>Upgrade Option</b>	Wireless connection to computer
<b>Packed Contents List</b>	ActivBoard, 2 ActivPens (Teacher), 2 ActivPens (Student), 1 Amp PSU, Installation Guide, Access to ActivInspire Professional Edition via download from Promethean Planet



### ACTIVBOARD SPECIFICATIONS

<b>Model</b>	<b>ActivBoard 387 Pro</b>
<b>ActivBoard Size</b>	87in
<b>Resolution</b>	14600 x 9200
<b>Screen Formats</b>	16:10
<b>Overall Dimensions</b>	2105mm x 1329mm (82.9in x 52.3in)
<b>Active Area Dimensions</b>	1865mm x 1175mm (73in x 46in)
<b>Active Area Diagonal</b>	2196mm (86.5in)
<b>Actual Image Diagonal</b>	2193mm (86.4in)
<b>Board Weight</b>	32kg (71lb)
<b>Packed Weight</b>	48kg (106lb)
<b>Packed Dimensions</b>	1500mm x 2270 x 110mm (59.1in x 89.4in x 4.3in)

### INTEGRATED USB SOUND SPECIFICATIONS

<b>Amplifier Power Output</b>	20W per channel RMS (<1% distortion)
<b>Controls</b>	Volume, Base, Treble, on/off
<b>Amplifier Frequency Response</b>	40Hz to 18kHz +/-3dB (at 1W)
<b>USB Sound</b>	USB Sound supported for Minimum System Requirements stated
<b>Connectivity – Inputs (4)</b>	Stereo PC, Stereo CD/DVD, Mono Auxiliary, Microphone to PC via PC
<b>Connectivity – Outputs (2)</b>	2 Stereo
<b>Power Requirement</b>	18V 3.3 Amp

### MINIMUM COMPUTER REQUIREMENTS

<b>Operating Systems</b>	Windows XP SP2 and above (XP/Vista/7); Mac OSX 10.4.11 – 10.6.1 (Tiger/Leopard/Snow Leopard); Linux Ubuntu 9.04, 9.10; Debian
<b>PC</b>	Pentium 4 – 1 GHz processor (800MHz for Vista), 512 MB of RAM, 1024x768 resolution, 1.5 GB of Free Disk space
<b>Mac</b>	Macintosh Intel Processors (Universal Binary), 512 MB of RAM, 1024x768 resolution, 3.0 GB of Free Disk Space

### INSTALLATION

#### ActivBoard Mobile System

Requires installation by a certified Promethean installer. Components supplied and minimum specifications stated have been tested and are required for optimal performance. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance and affect warranty. Contact your Promethean partner or visit [www.prometheankb.com](http://www.prometheankb.com) for more information. After installation, Promethean recommends that the ActivBoard Mobile System is moved by 2 people.

### MOBILE STAND SPECIFICATIONS

<b>Board Size</b>	Accommodates ActivBoard 387 Pro
<b>Height Settings</b>	Height-adjustable mount, with 600mm (23.6in) of adjustment from 350mm (13.8in) to 950mm (37.4in) ± 50mm (1.9"). Top and bottom limit stops are fitted if the full range of movement is not required/appropriate. Height adjustment is powered by an electrical motor and is operated using a switch on the side of the stand.
<b>Actuator Specification</b>	<p>Input Voltage: 24VDC                      Max Load: 750N                      Static Load: more than 750N                      Speed: 30mm/s (no load), 20mm/s (750N)                      Stroke Length: 600 ± 2mm                      Retracted Length: 795 ± 2mm                      End Mounting Dimension: H Type, ø10.1 hole, 6.3mm Slot                      Limit Switch: Built-in                      Duty Cycle: S2-10min                      Temperature: -26°- 65°C                      IP Degree: IP54                      AC-DC Adaptor:                      Input Voltage: 100 ~ 240VAC                      Output Voltage: 29VDC                      Current: 2Amp (4Amp protected)                      Cable and Plug: 1.5m, IEC Plug</p>
<b>Projector Boom</b>	Aluminium boom arm, extends 740mm (29.1in) from the back of the System. Projector Boom adjusts with the height of the ActivBoard reducing the need for specific re-calibration following height adjustment.
<b>Mobile Base Dimensions</b>	1400mm x 740mm (55.1in x 29.1in)
<b>Room Height Requirements</b>	Minimum 2562mm (100.87in) for full range operation
<b>Door Size Requirements</b>	Minimum door height clearance of 1962mm (77.24in) and door width clearance of 775mm (30.5in). Consideration should also be given to the size of corridors and layout of the school.
<b>Minimum Turning Circle Requirement</b>	See technical drawings
<b>Power</b>	Integrated 'power management' system for ActivBoard, Mobile Stand and Projector. There will be one lead from the Mobile System to plug in to a wall socket.
<b>Weight</b>	Frame only (approx.): 100kg (220.5lb); excludes board, projector, cabling and accessories Complete System Weight (approx.): 140kg (308.5lb) (when ActivBoard 387 Pro is fitted)

CONTINUED ON NEXT PAGE

### MOBILE STAND SPECIFICATIONS (CONTINUED)

<b>Connectivity Panel</b>	Connectivity panel with inputs for 2 x fully wired VGA (to support VESA DDC) plus 3.5mm stereo jack audio inputs, USB-B input (for ActivBoard), S-video, composite video plus auxillary audio jack inputs, Cat 5e ethernet input. Connectivity panel is mounted to the left hand-side of the Support Frame (when facing the system).
<b>Cables</b>	Cable assembly includes: 2 x 3.6m (11.8ft) VGA panel mount (fully wired to support VESA DDC), 3.6m (11.8ft) S-video panel mount, 3.6m (11.8ft) composite video panel mount, 3.6m (11.8ft) Ethernet panel mount 2.5m (8.2ft) USB patch cable (to connect computer to face plate). 2.3m (7.5ft) right angle stereo jack to panel mount jack socket, 2.3m (7.5ft) right angle stereo jack to panel mount phono pair, for PC audio input (to connect computer to face plate). 2m (6ft) VGA cable provided in the projector box (to connect the computer to the face plate).
<b>Pack Weights &amp; Dimensions</b>	<p><b>Box 1 of 4:</b> 13kg (28.7lb) Dimensions: 217mm x 1427mm x 467mm (8.54in x 56.18in x 18.39in) Contents: Projector Boom</p> <p><b>Box 2 of 4:</b> 28kg (61.7lb) Dimensions: 182mm x 1652mm x 442mm (7.2in x 65in x 17.4in) Contents: Spine</p> <p><b>Box 3 of 4:</b> 22kg (48.5lb) Dimensions: 128mm x 1782mm x 822mm (5.04in x 70.16in x 32.36in) Contents: Frame</p> <p><b>Box 4 of 4:</b> 42kg (92.6lb) Dimensions: 202mm x 1442mm x 782mm (7.95in x 56.77in x 30.79in) Contents: Mobile Base</p>

### PROJECTOR SPECIFICATIONS

<b>Model</b>	EST-P1 (DLP)
<b>Native Resolution</b>	WXGA (1280 x 800)
<b>Compressed Resolution</b>	up to 1080i
<b>Typical Colours</b>	16.77 million colours
<b>Brightness (ANSI lumens)</b>	2200 ANSI (normal), 2500 ANSI (high)
<b>Contrast Ratio</b>	2000:1
<b>Noise Level</b>	28dB (normal) 32dB (high brightness mode)
<b>Dimensions (w x d x h)</b>	354mm x 319mm x 157mm (13.9in x 12.6in x 6.1in) not including lens 354mm x 411mm x 219mm (13.9in x 16.1in x 8.6in) including lens
<b>Weight</b>	9kg (19.8lb)
<b>Aspect Ratio</b>	16:10 (native), 4:3, 16:9
<b>Power Consumption</b>	290W (<1W standby)
<b>Device Type</b>	DLP Technology
<b>Focus</b>	Manual Focus

CONTINUED ON NEXT PAGE

### PROJECTOR SPECIFICATIONS (CONTINUED)

<b>Zoom</b>	N/A
<b>Focal Length</b>	F=2.4
<b>Projection Distance</b>	0.39m ~ 0.56m (15in ~ 22in)
<b>Projection Screen Size</b>	1.98m ~2.79m (78in ~ 110in)
<b>Lamp Type</b>	220W lamp
<b>Lamp Life</b>	6000hrs (normal) 4000hrs (high)
<b>Keystone Correction</b>	Vertical: max $\pm 15^\circ$
<b>Operating Temperature</b>	5°C ~ 35°C (41°F ~ 95°F)
<b>Power Supply Voltage</b>	100 - 240V AC, 50/60Hz
<b>Horizontal Scan Rate</b>	15Hz ~ 90kHz
<b>Vertical Scan Rate</b>	43Hz ~ 85Hz
<b>Computer Compatibility</b>	IBM PC and Compatibles; Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1035i), EDTV (480p, 575i), SDTV (480i, 576i)
<b>Inputs</b>	D-sub 15-pin (RGB) x2 HDMI V1.3 x1 RCA x 1, S-Video x 1 LAN (RJ45) x1 RS-232C (D-sub 9-pin) x1 USB x1
<b>Colour</b>	Silver
<b>Security</b>	Padlock and security cable hole, Kensington lock hole, pin code security
<b>On-screen Menu</b>	Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish
<b>Advanced Features</b>	3D Ready Crestron RoomView Quick Start Instant Off Source Search Freeze Quick Access Lamp Close Caption
<b>Packed Contents List</b>	Power cord, computer cable (Dsub15-Dsub15), wireless remote, owner's manual (CD-ROM & Quick Start Guide)

### UPGRADE AND ACCESSORY OPTIONS

<b>Wireless Upgrade Pack 300 Pro</b>	Allows the ActivBoard 300 Pro to connect to the computer wirelessly; includes an ActivHub (2.4 GHz) and Quick Start Guide
<b>ActivWand 50</b>	Wireless, battery free and extended reach input device for the ActivBoard – 540mm (21.2in) in length; “left click”, cursor and hover, just like a mouse
<b>Mobile Stand Drawer</b>	Optional drawer in the base of the System (includes lock and key), and can be used to store sets of ActivExpressions, or ActiVotes, ActivSlate or the EST-P1 remote control. (Available July 2010)
<b>Mobile Stand Dry Erase Whiteboard</b>	Optional dry erase whiteboard, can use 1 or 2 dry erase whiteboards per system (Available July 2010)
<b>Mobile Stand Laptop Shelf</b>	Storage for 1 laptop, with a maximum size of 17in, includes a lock and key (Available July 2010)

### WARRANTY AND SUPPORT<sup>†</sup>

<b>ActivBoard, Mobile Stand</b>	Three-Year Warranty with Three-Year Email and Telephone Support. Additional Two-Year Warranty and Two-Year Email Support upon registration. Warranty is return to base for repair coverage.
<b>EST-P1</b>	Three-Year Warranty and Three-Year/3000hr Lamp Warranty with Three-Year Email and Telephone Support. Warranty is return for repair coverage.
<b>ActivPen</b>	One-Year Warranty and 90-Day Telephone Support
<b>Support</b>	Online support for all Promethean Products available from: <a href="http://www.prometheankb.com">www.prometheankb.com</a>

### TECHNICAL DRAWING SPECIFICATIONS

