

24" Medical Grade All in One PC



Display	<ul style="list-style-type: none"> • 23.6-inch medical grade 16:9 LED (1920x1080) 	I/O Ports	<ul style="list-style-type: none"> • 2 x USB 3.0 ports • 4 x USB 2.0 ports • 1 x RS232 upto 3 COM ports • DVI monitor out port • 1 x HDMI output (1080p) • Mic, Line-in, Line-out
CPU Support	<ul style="list-style-type: none"> • 2nd and 3rd generation Intel Core i3, i5 & i7 processors 	Power Supply	<ul style="list-style-type: none"> • Medical Grade 135W 100 ~ 240V AC, 50-60Hz. Supports Output range: DC 18V-19V, 7.5A
Chipset	<ul style="list-style-type: none"> • Intel® H61 	Touch Screen	<ul style="list-style-type: none"> • Projected Capacitive Multi-Touch
Memory	<ul style="list-style-type: none"> • 2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB Max. Supports PC3-10600 1333MHz SO-DIMM 	Wireless	<ul style="list-style-type: none"> • Intel Centrino 802.11 a/b/g/n + Bluetooth 4.0
HDD Support	<ul style="list-style-type: none"> • Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports 	Webcam	<ul style="list-style-type: none"> • 3 megapixel camera
Video & Graphics	<ul style="list-style-type: none"> • Nvidia GT630 M Dedicated 1GB DDR3 	Wall Mount	<ul style="list-style-type: none"> • Supports both 75mm & 100mm VESA mounting holes
Networking	<ul style="list-style-type: none"> • 2 x Gigabit (GbE) Fast Ethernet (Realtek RTL 8111E) 	Expansion Slots	<ul style="list-style-type: none"> • Two Mini PCI-e (1xFull-size and 1xHalf-size)
Audio	<ul style="list-style-type: none"> • Realtek ALC892 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and "jack re-tasking" 	Bios	<ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection
Swivel base	<ul style="list-style-type: none"> • Optional desktop stand with Antimicrobial Germ protection with rotation function Left/Right plus Tilt function up/down 		

Weight	• Unit: 22.9lbs with base, 17lbs without base, Power Adapter: 2.2lbs	O/S	• Windows 8, Windows 7, Linux
Environment	• Ambient Temperature: 0°C ~ 40°C (operating)	Dimensions	• 23.5" long, 14.8" tall, 2.08" deep (not including base)
Relative Humidity	• 10% ~ 90% (non-condensing)	Colors	• White with Antimicrobial Germ Protection
		Certifications	• EN60601-1 medically certified, UL60950 electrical safety, FCC class B, CE, Energy Star 5.2, RoHs, WEEE



Corporate Headquarters
Cybernet Manufacturing
5 Holland,
Irvine, CA 92618
Toll free: 888-834-4577
Local: 949-600-8000
Fax: 949-600-8013
www.cybernetman.com
sales@cybernetman.com
support@cybernetman.com

Cybernet Europe
Network House, Hawkins Road
Colchester, Essex CO2 8LA
United Kingdom
UK Phone: 0845-539-1200
UK Fax: 0845-539-1201
www.cyberneteuropa.com
sales@cyberneteuropa.com
support@cyberneteuropa.com

Cybernet Taiwan Company, LTD.
4F., No.25, Lane 140, Xingai Rd
Neihu District, Taipei City 11494
Taiwan (R.O.C.)
Phone: (02) 2790-4776
Fax: (02) 2793-3172
www.cybernet.com.tw
sales@cybernet.com.tw
support@cybernet.com.tw