



## The workhorse that's also a sprinter

**This Tank-Tough® printer offers flexible forms handling and lightning-fast throughput.**

### Highlights:

- Fast results ideal for high-volume printing
- Multiple paper paths for added flexibility
- Letter-quality 24-pin printer
- Zero-tear capability (through any paper path) with auto-advance
- Up to 610 characters-per-second print speed
- Crisp, clear printing—even on 5-part forms
- Rated at up to 8,000-hour MTBF
- Co-resident Epson®, IBM® and MICROLINE® emulations
- Eight resident scalable barcodes and four text fonts
- 1-Year limited Depot warranty, including parts, labor and printhead<sup>1</sup>
- Live, toll-free technical support<sup>1</sup>

The OKI® MICROLINE® printer delivers trouble-free reliability—with swift printing speeds, high-volume output, and flexible paper handling.

Each of its four print speeds is among the fastest in its class:

- At 610 cps, the High-Speed Draft mode blasts through spreadsheet reports in no time;
- The 485-cps Utility and 245-cps Near Letter Quality modes kick out drafts and memos at a rapid clip; and
- The 165-cps Letter Quality mode delivers crisp, clear correspondence and proposals in short order.

The ML395 is built Tank-Tough: it comes with a printhead rated for 200 million characters, and has an MTBF of 8,000 hours.

### Multiple paper paths for added flexibility.

Use the optional bottom push tractor and the bottom feed's straight-through paper path for those hard-to-handle labels, card stock, and forms with up to 5 parts. Add the top feed for single sheets and envelopes, the rear push feed for fanfold paper.

A time-saving "paper park" function lets you switch forms at the push of a button.

The printer even saves paper: its zero-tear function advances a printed page to the perforation and lets you tear sheets off cleanly and precisely. Then it positions the next page for printing—automatically.

### Getting the job done — with style.

Make a lasting, professional-looking impression with the four letter-quality resident fonts and eight resident barcode fonts.

### Rugged. Dependable. Virtually unstoppable.

The ML395 is all that and more. Ask for the fast, flexible 24-pin workhorse that's sure to be a winner in your busy office.



<sup>1</sup> Available in the U.S. and Canada only.

# MICROLINE® 395

## Specifications

### Technology, Speed and Print Characteristics

- **Printhead:** 24-pin, (0.20 mm diameter)
- **Graphics Resolution:** 60 x 60 dpi (min.); 360 x 360 dpi (max.)
- **Feed Rate:** 10 ips
- **Print Speed and Character Matrix:**

Mode	LQ	NLQ	Utility	HS Draft
Speed (in cps)	165	245	485	610

### Emulation, Interface and Memory

- **Emulation:** Epson® LQ 2550, IBM® XL24E AGM and IBM ProPrinter® co-resident
- **Interface:** Standard: Parallel and RS232-C Serial
- **Memory:** 64K RAM
- **Interface Buffer:** Max. 23K

### Compatibility

- **Operating Systems:** Windows®10, Windows 8.1, Windows 8, Windows 7, Server 2019, Server 2016, Server 2012/R2, Server 2008/R2

### Paper Handling

- **Paper Input:** Multi-Part Form, Continuous Form (non-overlap type), Cut Sheet, Card Stock, Envelopes (single feed)
- **Number of Copies:** Original plus 3
- **Single Sheet Thickness:** 0.002" to .0049" (0.05mm to 0.12mm)
- **Multipart Thickness:** Rear Feed: .014" (0.36mm); Bottom Feed: .02" (0.5mm)
- **Paper Weight:** Single Part – 12 to 24 lb.; Card Stock – 100 lb. or less

- **Paper Feeding:** Bottom, Top and Rear
- **Standard:** Built-in Push Tractor (Rear Feed), Friction Feed (Top)
- **Options:** Pull Tractor, Bottom Feed Push Tractor

### Warranty and Reliability

- **Warranty:** 1-Year limited Carry-In Depot; parts, labor and printhead<sup>1</sup>
- **MBTF:** 8,000 hours (25% duty/35% page density)
- **Monthly Workload:** 17,000 pages at 25% duty cycle/-35% density
- **Printhead Life:** 200 Million characters avg. at 25% duty cycle
- **Ribbon Life:** 5 million-character life

### Environmental

- **Size (WxDxH):** 22.4" x 16.4" x 7.1" (57 cm x 41.7 cm x 18.0 cm)
- **Net Weight:** 37 lb. (17 kg); UPS shippable
- **Power Consumption:** 180 VA (max.) operating; 60 VA idle
- **Electrical:** 120V
- **Frequency:** 50/60 Hz (±2%)
- **Operating Temperature:** 41° F to 104° F (5° C to 40° C) @ 20% to 80% relative humidity
- **Acoustic Noise:** 58dBA LQ mode; 56dBA Quiet mode

## Ordering Information

Description	Part Number
MICROLINE 395 – 120V	62410501
<b>Accessories</b>	
Pull Tractor Kit (with acoustic cover)	70011701
Bottom Feed Push Tractor Kit	70021601
<b>Ribbon:</b>	
Black Cartridge	52103601
<b>OKIcare® Warranty Enhancement Programs</b>	
<b>OKI Depot™OKI On-Site™</b>	
2-Year Extension	58251311 58252311
3-Year Extension	58251411 58252411

Note: All Warranty Enhancement Program options extend the total warranty coverage period from the date of purchase to the number of years listed for each order number above.

<sup>1</sup> Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2019 Oki Data Americas, Inc. OKI, MICROLINE, OKiLAN, OKIcare Reg. T.M., Oki Data Americas, Inc. Epson Reg. T.M., Seiko Epson Corp. IBM, ProPrinter Reg. T.M., International Business Machines Corp. Windows Vista, Reg. T.M., Microsoft Corp.

## Okidata Americas, Inc.

### USA

8505 Freeport Pkwy., Suite 600  
Irving, TX 75063  
Tel: 800.OKI.DATA (800.654.3282)  
Fax: 856.222.5320

[www.oki.com/us](http://www.oki.com/us)

### Canada

5800 Hurontario St., Suite 1020  
Mississauga, Ontario L5R 4B9  
Tel: 905.755.5800  
Fax: 905.755.5840

[www.oki.com/ca](http://www.oki.com/ca)

# OKI®