Technical Specifications

HP Z43 42.5-inch 4K UHD Display




Front

1. Power LED

Technical Specifications

HP Z43 42.5-inch 4K UHD Display



- **1.** Power Button
- 2. OSD Button (Viewing Modes)
- 3. OSD Button (Next Active Input)
- **4.** OSD Button (Information)
- **5.** OSD Button (Menu)
- **6.** Power Switch

- **7.** Power Connector Port
- 8. Audio Line Out
- 9. HDMI 2.0
- **10.** Mini DisplayPort™ 1.2
- **11.** DisplayPort™ 1.2
- **12.** USB-C[™] 3.1

- 13. USB 3.0 Type-A Ports
- 14. Security Lock Slot
- 15. USB 3.0 Type-A
- **16.** USB-C[™] 3.1

Technical Specifications

Models: 1AA85A4

Panel Specifications* Display Size (Diagonal) 42.5-in

Display Panel Type IPS

Native Resolution/Timing 3840×2160 @ 60 Hz

NOTE: DisplayPort 1.2 or HDMI 2.0 required to drive panel at its native resolution

Panel Bit Depth True 10-bit **Aspect Ratio** 16:9 **Brightness - Typical** 350 cd/m² Static Contrast Ratio - Typical 1000:1 **Static Contrast Ratio - Minimum** 700:1 **Dynamic Contrast Ratio (DCR)** 5.000.000:1

Pixel Pitch 0.2451 x 0.2451 mm

Pixels Per Inch (PPI) 104

Backlight Lamp Life (to half brightness -30k minimum in hours)

Anti-Glare Panel Yes

5ms ("gray to gray") Response Time - Typical

NOTE: Product default is 8ms response time and can be adjusted to as low as 5ms in the display menu.

Horizontal Viewing Angle

178° (typical CR>10) Vertical Viewing Angle (typical CR>10) 178°

Panel Active Area (w x h) 941.184 x 529.416 mm (37.05 x 20.84 in)

Preset Graphic Modes/Supported 640 x 480@60Hz Resolutions 720 x 400@70Hz 800 x 600@60Hz

720 x 480@60HZ 1280 x 720@60HZ 1280 x 800@60HZ 1280 x 1024@60HZ 1600 x 900@60HZ 1600 x 1200 @60HZ 1680 x 1050@60HZ 1920 x 1080@60HZ 1920 x 1200@60HZ 2560 x 1440@60HZ

3840 x 2160@30HZ

Maximum Resolution 3840×2160 @ 60 Hz **Recommended Resolution** 3840×2160 @ 60 Hz

Vertical Scan Range 47-63Hz **Horizontal Scan Range** 121.8-140 kHz

Maximum Pixel Clock Speed 78MHz

Default Color Temperature Standard (10000K)

*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage NTSC 72%

> **sRGB** 96%

Factory Color Calibrated Color Management Yes

> **Factory Color Presets** Calibrated (D93). Neutral (D65)

Default Color Temperature D93 **Low Blue Light Modes** Yes



Technical Specifications

Monitor Specifications Exterior Color of Monitor Bezel and

Black Pearl Stand

Pluq & Play Yes

Tilt Yes. -5° to +10° Yes, 20°(+/-10°) **Swivel**

Pivot No **Height Adjustment Range** No

VESA Mounting Yes, both 200 mm and 100 mm with included bracket

Security Lock Ready

Detachable Base Yes, ships detached

Warrantv 3/3/0 **Zero Bright Dot Warranty** Yes

On Screen Display

(OSD)

Luminance **Color Control**

Input Control Image Control

PIP Control On Screen Display User Controls Power Control

Menu Control Management Language Information

User Programmable Modes Yes. 20

Menu, Information, Next Active Input, viewing modes, **Monitor Control Buttons or Switches**

Power

User-Assignable Function Buttons Yes, 3 (9 options)

10 (English, Spanish, German, French, Italian, Netherlands, Languages

(1) DisplayPort™ 1.2

Portuguese, Japanese, T-Chinese and S-Chinese)

Connector Types

DisplayPort™ Mini-DisplayPort™

(1) Mini DisplayPort™ 1.2 (1) HDMI 2.0 HDMI USB Type-C™ (1) USB 3.1, Gen1

HDCP support Yes HDCP 2.2, (DisplayPort and HDMI)

Audio Output (1) Analog

USB Port Specifications **USB Version** 3.0 **USB Hub** Yes **Downstream Ports** 4 Ports **Upstream Ports** 1 Port **Fast Charging USB Ports** 3 Ports

7.5W 4.5W 7.5W

Power Output Maximum

15W

USB-Type C™ Port **Specifications**

USB-Type C™ Version USB 3.1 Gen1 / 5G bps Yes

USB-Type C™ Hub **Upstream** Rear: 1 Port

Downstream Side: 1 Port **Video Support** Rear: USB-C™ Alt mode – DisplayPort™ 1.2

5V/3A **Power Output** 9V/3A

Technical Specifications

10V/5A 12V/5A 15V/4.33A 20V/3.25A Rear: 65W Max

Power Output Maximum Side: 15W Max

Special Features Picture-in-Picture, Picture-by-Picture Yes

Power & Operating Power Supply Internal

Specs **Power Source** 90~265 Vac. 45~63 Hz

> **Power Consumption - Maximum** 205W **Energy Saving/Standby Mode** 0.5W **Power Consumption - Typical** 95W Power cable length 1.9 m

ENERGY STAR® Data Operational Mode at 230 VAC 41.4W

EU Energy Efficiency Class (EC1062)

On-mode Power Consumption (EC

71W 1062/2010)

Annual Power Consumption (EC 104 kWh 1062/2010)

Energy Efficiency Class (EC 1062/2010)

Visible Screen Size 42.5 in / 108 cm diagonal

Operating Conditions Operating Temperature - Celsius $(5^{\circ} - 35^{\circ}C)$

Operating Temperature - Fahrenheit $(41^{\circ} - 95^{\circ}F)$ Non-operating Temperature - Celsius -20° - 60°C Non-operating Temperature -29° - 140°F **Fahrenheit**

Operating Humidity 20 – 80% Relative Humidity (non-condensing)

Non-operating Humidity 5 - 95%

Operating Altitude 0 – 5,000 m (16,400 ft.) Non-operating Altitude 0 - 12.192 m (40,000 ft.)

Environmental Features and Certifications

Mercury-free LED display backlights Yes **Arsenic-Free Display Glass** Yes Low Halogen Yes

NOTE: External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts

obtained after purchase may not be Low Halogen.

CE,CB,KC/KCC/PSB/ICE/TUV-S/ISO 9241-307/

Agency Approvals and Certifications EAC/UL/PSB/ISC/CCC/CEL/CECP/SEPA/Edge/ISC/VCCI/FCC/B

SMI/WEEE

Yes

Microsoft WHQL Certification Win 10, Win 8, Win 8.1, Win 7

China Energy Label **CEL Grade 1** SmartWay Transport Partnership - NA Yes (NA SKU)

only

Contains Recycled Back Cover Plastic

Base/Stand Yes Other Parts Yes **Recyclable Plastics** Yes

Recyclable Packaging (Box, packing

Yes, except EPS materials)

Technical Specifications

		Metric	Imperial
Unit Product/Package Specifications	Unpacked with stand (highest setting) Product Dimensions (W x D x H)	97,21 x 24 x 61,9 cm	38.27 x 9.44 x 24.37 in
•	Head Only Product Dimensions (W x D x H)	97,21 x 12,28 x 56,59 cm	38.27 x 4.83 x 22.28 in
	Base Area Footprint Product Dimensions (W x D x H)	399,99 x 239,99 mm	9.33 x 0.43 x 8.07 in
	Packaged Packaged Dimensions (W x D x H)	112 x 70 x 36 cm	44.09 x 27.56 x 14.17 in
	Plastic Bezel Measurements Product Weight, Packed Product Weight, Unpacked Product Weight, Head Only	Top 14,42 mm Side 14,43 mm Bottom 20,02 mm 23,47 kg 16,95 kg 12,45 kg	Top 0.567 in Side 0.567 in Bottom 0.788 in 51.7 lb 37.38 lb 27.45 lb
Pallet Information	Pallet Dimensions (L x W x H mm) Pallet Dimensions (L x W x H inch) Pallet Total Weight (including units) kg Pallet Total Weight (including units) lbs Pallet Layers Pallet Product per Layer Total Products per Pallet Container Load, 20-Foot Container Load, 40-Foot Container Load, 40-Foot	735 x 1150 x 120 mm 28.93 x 45.27 x 4.72 in 156,32 kg 344.32 lbs 3 2 6 96 units 192 units	
What's in the box?	Monitor Software included	HP Z43 42.5-inch 4K UHD Display HP Display Assistant USB-C-to-C cable (1.8m)	
	VESA Mounting Bracket	Yes	
Accessories Included	AC Power Cord DisplayPort™ 1.2 Cable USB-C™ to USB Type-A Cable	Metric 1,9 m 1,8 m 1,8 m	Imperial 6.2 ft 5.9 ft 5.9 ft
Other	User Guide Languages Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish. English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.	

Service and Warranty

Protected by HP, including a 3-year standard limited warranty. Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties. 1

Technical Specifications

Copyright © 2018 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

USB Type-C[™] and USB-C[™] are trademarks of USB Implementers Forum.

ENERGY STAR® is a registered trademark owned by the U.S. Environmental Protection Agency.

1. Care Packs are optional. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See http://www.hp.com/go/cpc for details.



Technical Specifications

Change Log	
V1 to V2	"Integrated Mount" removed from Monitor specifications and VESA mounting Bracket added to What's in the box section
V2 to V3 October 12, 2018	Added USB-C-to-C cable (1.8m)

