

Overview

HP ProBook 440 G6 Notebook PC



Left

- | | |
|-----------------------------|---|
| 1. Internal Microphones (2) | 6. SD Card Reader |
| 2. Webcam | 7. Thermal Vent |
| 3. Webcam LED | 8. USB 2.0 Port |
| 4. Clickpad | 9. Standard Security Lock Slot (Lock sold separately) |
| 5. Hard Drive LED | 10. Power Button |

Overview



Right

- | | |
|-----------------------------------|--|
| 1. Power Connector | 5. USB 3.1 Gen 1 Port |
| 2. USB Type-C™ 3.1 Gen 1 Port | 6. USB 3.1 Gen 1 Port |
| 3. Ethernet Port (RJ-45) | 7. Headphone/Microphone Combo Jack |
| 4. HDMI Port (Cable not included) | 8. HP Fingerprint Sensor (select models) |

Overview

At a Glance

- Preinstall with Windows 10 versions or FreeDOS 3.0
- Choice of 8th Generation Intel® Core™ i7, i5, i3 processors
- Display include your choice of 35.56 cm (14.0") diagonal HD, Ultra Wide Viewing Angle FHD, Touch or Non-Touch
- Optional Nvidia GeForce MX250 and MX130 with 2 GB GDDR5 dedicated video memory or integrated Intel® HD Graphics 610 or Intel® UHD 620
- Enhanced security features including TPM2.0, HP BIOSphere, Hardware enforced Firmware Protection, HP Fingerprint Sensor³ (select models) and optional IR camera
- Passed 19 items of MIL-STD 810G testing plus an additional 120,000 hours of reliability testing through HP's Total Test Process¹
- Weight starting at 3.53 lbs (1.6kgs)
- HP Long-Life Rechargeable battery, with HP Fast Charge Technology recharges 50% in 30 minutes²
- Supports wireless LAN and wireless WWAN options for connectivity on the go
- Up to 512 GB Solid State Drives and 1 TB Hard Drive
- Up to 32 GB total system memory
- 720p HD webcam, IR camera for face authentication with Windows Hello
- Spill-resistant and optional backlit Keyboard with numeric keypad, and Clickpad with multi-touch gestures enabled, taps enabled as default
- Enjoy the rich conferencing experience of the Skype for Business™ Certified HP ProBook 440

1. MIL STD 810G testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Damage under the MIL STD test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.
2. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.
3. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Technical Specifications

PRODUCT NAMES

HP ProBook 440 G6 Notebook PC

OPERATING SYSTEMS

Preinstalled	Windows 10 Pro 64 ¹ Windows 10 Pro 64 (National Academic only) ² Windows 10 Home 64 ¹ Windows 10 Home Single Language 64 ¹ Windows 10 China Government Edition FreeDOS 3.0
---------------------	---

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

PROCESSORS

Intel® Core™ i7-8665U processor with Intel® UHD Graphics 620 (1.9 GHz base frequency, up to 4.8 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores) supports Intel® vPro™ Technology^{3,4,5,6,7}

Intel® Core™ i7-8565U with Intel® UHD Graphics 620 (1.8 GHz base frequency, up to 4.6 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{3,4,5,6}

Intel® Core™ i5-8265U with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)^{3,4,5,6}

Intel® Core™ i5-8365U vPro™ processor with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 4.1 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)^{3,4,5,6}

Intel® Core™ i3-8145U with Intel® UHD Graphics 620 (2.1 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 4 MB L3 cache, 2 cores)^{3,4,5,6}

Intel® Core™ i7+ 8565U processor (Core™ i7 and 16 GB Intel® Optane™ memory) with Intel® UHD Graphics 620 (1.8 GHz base frequency, up to 4.6 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{3,4,5,6,7}

Intel® Core™ i7-8665U vPro™ with Intel® UHD graphics 620 (1.9 GHz base frequency, up to 4.8 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{3,4,5,7}

Intel® Core™ i5+ 8265U processor (Core™ i5 and 16 GB Intel® Optane™ memory) with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)^{3,4,5,6,7}

Intel® Celeron® 4205U processor with Intel® HD Graphics 610 (1.8 GHz base frequency, 2 MB L3 cache, 2 cores)^{3,4,5,6}

Intel® Pentium® 5405U processor with Intel® HD Graphics 610 (2.3 GHz base frequency, 2 MB L3 cache, 2 cores)^{3,4,5,6}

Processors Family

8th Generation Intel® Core™ i7 processor (i7-8565U, i7-8665U)⁶

8th Generation Intel® Core™ i5 processor (i5-8265U, 8365U)⁶

7th Generation Intel® Core™ i3 processor (i3-8145U)⁶

Intel® Pentium® processor (5405U)⁶

Intel® Celeron® processor (4205U)⁶



Technical Specifications

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
 4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
 5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.
 6. NOTE: In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.
 7. Intel® Optane™ memory system acceleration does not replace or increase the DRAM in your system and requires configuration with an optional Intel® Core™ i(5 or 7)+ processor.
-

CHIPSET

Integrated with processor

GRAPHICS

Integrated

Intel® UHD graphics 620⁸

Discrete

NVIDIA® GeForce® MX130 (2 GB DDR5 dedicated)⁹

NVIDIA® GeForce® MX250 (2 GB DDR5 dedicated)⁹

Supports

Support HD decode, DX12, HDMI 1.4b up to 4K 30Hz

Support CUDA, Optimus, PhysX, GPU Boost 2.0

8. HD content required to view HD images.
 9. Integrated graphics depends on processor. NVIDIA® Optimus™ technology requires an Intel processor, plus an NVIDIA® GeForce® discrete graphics configuration and is available on Windows 10 Pro OS. With NVIDIA® Optimus™ technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).
-

DISPLAYS

Non-Touch

35.56 cm (14") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m², 67% sRGB two WLAN antennas (1366 x 768)^{8,11}

35.56 cm (14") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m², 67% sRGB for HD camera, one WLAN antenna (1366 x 768)^{8,11}

35.56 cm (14") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m², 67% sRGB for HD camera and two WLAN antennas (1366 x 768)^{8,11}

35.56 cm (14") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m², 67% sRGB for HD + IR camera and two WLAN antennas (1366 x 768)^{8,11}

35.56 cm (14") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m², 67% sRGB for HD camera, WWAN and two WLAN antennas (1366 x 768)^{8,11}



Technical Specifications

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB and two WLAN antennas (1920 x 1080)^{8,11}

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB for HD camera and one WLAN antenna (1920 x 1080)^{8,11}

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB for HD camera and two WLAN antennas (1920 x 1080)^{8,11}

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB for HD + IR camera and two WLAN antennas (1920 x 1080)^{8,11}

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB for HD camera, WWAN and two WLAN antennas (1920 x 1080)^{8,11}

Touch

35.56 cm (14") diagonal HD SVA eDP LED-backlit slim touch screen, 220 cd/m², 67% sRGB for HD camera and two WLAN antennas (1366 x 768)^{8,10,11}

35.56 cm (14") diagonal HD SVA eDP LED-backlit slim touch screen, 220 cd/m², 67% sRGB for HD camera, WWAN and two WLAN antennas (1366 x 768)^{8,10,11}

HDMI

Supports resolutions up to 4K 30Hz

8. HD content required to view HD images.

10. Sold separately or as an optional feature.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

Docking station model	Total number of supported displays (incl. the notebook display)	Max. resolutions supported	Dock Connectors	Technical limitations
HP Thunderbolt Dock 120W G2	3	Dual 4k @60Hz	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP USB-C Dock G4	3	Dual 2K @ 60Hz Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP USB-C Universal Dock	3	Dual 4K @ 60Hz Single 5K @ 60Hz	2xDP	
HP USB-C Travel Dock	2	Single 2K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 4K @ 30Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time

STORAGE AND DRIVES

Primary Storage



Technical Specifications

500 GB 7200 rpm SATA¹²
1 TB 5400 rpm SATA¹²
1 TB 7200 rpm SATA¹²

Primary M.2 Storage

128 GB M.2 SATA TLC Solid State Drive¹²
256 GB M.2 SATA TLC Solid State Drive¹²
256 GB PCIe® NVMe™ M.2 Value Solid State Drive¹²
512 GB PCIe® NVMe™ M.2 TLC Solid State Drive¹²
512 GB PCIe® NVMe™ M.2 Value Solid State Drive¹²

12. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

Note: PCIe SSD not available for Celeron

MEMORY

Maximum Memory

32 GB DDR4-2400 SDRAM¹³

Memory

32 GB DDR4-2400 SDRAM (2 X 16 GB)¹³
16 GB DDR4- 2400 SDRAM (1 X 16 GB)
16 GB DDR4- 2400 SDRAM (2 X 8 GB)¹³
12 GB DDR4- 2400 SDRAM (4 GB and 8 GB (1 x 8 GB))¹³
8 GB DDR4- 2400 SDRAM (1 x 8 GB)
8 GB DDR4- 2400 SDRAM (2 x 4 GB)¹³
4 GB DDR4- 2400 SDRAM (1 x 4 GB)

Memory Slots

2 SODIMM
Both slots are customer accessible / upgradeable
DDR4 PC4 SODIMMS, system runs at 2400
Supports Dual Channel Memory

13. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 5.0 Combo, non-vPro™¹⁴
Realtek RTL8821CE 802.11a/b/g/n/ac (1x1) WLAN + Bluetooth® 4.2 Combo¹⁴
Realtek RTL8822BE 802.11a/b/g/n/ac (2x2) WLAN + Bluetooth® 4.2 Combo¹⁴

WWAN

Intel® XMM™ 7262 LTE-Advanced (Cat6)¹⁵
Intel® XMM™ 7360 LTE-Advanced (Cat9)¹⁵

Ethernet



Technical Specifications

Realtek RTL8111HSH-CG 10/100/1000 GbE NIC¹⁶

14. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.
15. WWAN module requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.
16. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Audio

Integrated microphone (Mono or Dual Array)
2 Integrated stereo speakers

Speaker Power

2W/4ohm Per speaker

Camera

720p HD camera⁸
720p HD camera+IR Camera^{8,17}

8. HD content required to view HD images.
17. Sold separately or as an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Keyboard, spill resistant with optional backlit function

Pointing Device

Clickpad with multi-touch gesture support

Function Keys

F1 - Display Switching
F2 - Blank
F3 - Brightness Down
F4 - Brightness Up
F5 - Audio Mute
F6 - Volume Down
F7 - Volume Up
F8 - Mic Mute
F9 - Blank or Backlit Toggle
F10 - numlk
F11 - Wireless
F12 - Sleep

Hidden Functions



Technical Specifications

Fn+R - Break
Fn+S - Sys Rq
Fn+C - Scroll Lock

SOFTWARE AND SECURITY

BIOS

HP BIOSphere Gen4¹⁸
HP DriveLock & Automatic DriveLock
BIOS Update via Network
Secure Erase¹⁹
Absolute Persistence Module²⁰
Pre-boot Authentication
HP Wireless Wakeup

Software

HP Native Miracast²¹
HP LAN-Wireless Protection
HP Connection Optimizer
HP 3D DriveGuard
HP Hotkey Support - CMIT
HP Jumpstart
HP Support Assistant²²
HP Noise Cancellation Software
HP Host Based MAC Address Manager
Buy Office (sold separately)

Manageability Features

HP Driver Packs²³
HP System Software Manager (SSM)
HP BIOS Config Utility (BCU)
HP Client Catalog
HP Manageability Integration Kit Gen2²⁴
Ivanti Management Suite²⁵
HP Cloud Recovery²⁶

Client Security Software

HP Client Security Suite Gen4²⁷ including:
HP Security Manager²⁸ (including Credential Manager, HP Password Manager, HP Spare Key)
HP Device Access Manager²⁹
HP Power On Authentication
HP Fingerprint Sensor (select models)³⁴



Technical Specifications

Windows Defender³⁰

Security Management

Secure Erase¹⁹

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)³¹

SATA 0,1 port disablement (viaBIOS)

RAID configurations³²

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

Integrated hood sensor

HP Sure Click³³

18. HP BIOSphere Gen4 requires Intel(R) or AMD 8th Gen processors. Features may vary depending on the platform and configurations.
19. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method.
20. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
21. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming
22. HP Support Assistant requires Windows and Internet access.
23. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
24. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.
25. Ivanti Management Suite subscription required.
26. HP Cloud Recovery is available for HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, wired network connection. Note: You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/document/c05115630>
27. HP Client Security Suite Gen 4 requires Windows and Intel® or AMD 8th generation processors.
28. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.
29. HP Device Access Manager requires HP Client Security Suite Gen4.
30. Windows Defender Opt in and internet connection required for updates.
31. Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).
32. RAID configuration is optional and does require a second hard drive.
33. HP Sure Click is available on most HP PCs and supports Microsoft® Internet Explorer and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode, when Microsoft Office or Adobe Acrobat are installed.
34. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.



Technical Specifications

POWER

Power Supply

HP Smart 65 W External AC power adapter³⁵
HP Smart 65 W EM External AC power adapter³⁵
HP Smart 65 W USB Type-C™ adapter³⁵
HP Smart 45 W External AC power adapter³⁵
HP Smart 45 W USB Type-C™ adapter³⁵

Primary Battery

HP Long Life 3-cell, 45 Wh Polymer³⁶

Battery Life

Up to 13 hours and 15 minutes³⁷

Power Cord

3-wire plug - 1.8m³⁵
3-wire plug - 1.0m³⁵
2-wire plug - 1.0m³⁵
Duckhead power cord - 1.0m³⁵
Duckhead power cord - 1.8m³⁵

Battery Weight

0.49 lb
0.22 kg

35. Availability may vary by country.

36. Battery is internal and not replaceable by customer. Serviceable by warranty.

37. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Weight

Starting at 3.53 lbs³⁸
Starting at 1.6 kg³⁸

Dimensions (w x d x h)

12.76 x 9.36 x 0.71 in
32.42 x 23.77 x 1.8 cm

38. Weight will vary by configuration.

PORTS/SLOTS

1 USB 3.1 Type-C™ Gen 1 (Power delivery, DisplayPort™ 1.2)
1 USB 2.0 (Powered port)
2 USB 3.1
1 HDMI 1.4b³⁹
1 RJ-45
1 AC power
1 Headphone/microphone combo jack



Technical Specifications

Expansion Slots

1 SD

Supports SD, SDHC, SDXC

39. HDMI cable sold separately.

SERVICE AND SUPPORT

HP Services offers 3-year and 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life Batteries which will have same 1-year or 3-year limited warranty as the platform. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.⁴⁰

40. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	Win 10
Integrated graphics	5.71W
Discrete Graphics	6.78W
Max Operating Power	Discrete < 65W UMA < 45W

Temperature

Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

Random Vibration

Operating	0.75 grms
Non-operating	1.50 grms

Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry Standard Certifications

UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR®	Selected models ⁴¹
EPEAT® 2019	Yes, Silver in U.S. ⁴²
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes



Technical Specifications

SABS	Yes
UKRSERTCOMPUTER	Yes

41. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

42. Configurations of the HP ProBook 440 G6 is ENERGY STAR® certified are identified as HP ProBook 440 G6 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Panel LCD 14 inch diagonal FHD (1920 x 1080) Anti- Glare WLED UWVA 45% NTSC 250 nits eDP slim	Outline Dimensions (W x H x D)	316.17 x 197.98 (max)
	Active Area	309.37 x 174.02 (typ.)
	Weight	285 g (max)
	Diagonal Size	14.0 inch
	Thickness	3.0 mm (max)
	Interface	eDP 1.2 (2 lane)
	Surface Treatment	Anti-glare
	Touch Enabled	No
	Contrast Ratio	600:1 (typ)
	Refresh Rate	60 Hz
	Brightness	250 nits
	Pixel Resolution	1920 x 1080 (FHD)
	Format of LCD Pixel Arrangement	RGB
	Backlight	LED
Color Gamut Coverage	45% of NTSC	
Color Depth	6 bits	
Viewing Angle	UWVA 85/85/85/85	

Panel LCD 14 inch diagonal FHD (1920 x 1080) Anti- Glare WLED UWVA 45% NTSC 220nits eDP slim NB non-touch	Outline Dimensions (W x H x D)	316.112 x 197.98 max.
	Active Area	309.312 x 173.988
	Weight	<280 g max.
	Diagonal Size	14.0"
	Thickness	3.0 mm max.
	Interface	eDP 1.2
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	600:1 (typical)
	Refresh Rate	60 Hz

Technical Specifications

Brightness	220 nits typical (Panel Only)
Pixel Resolution	1920 x 1080 (FHD)
Format of LCD Pixel Arrangement	RGB
Backlight	LED
Color Gamut Coverage	45% of NTSC
Color Depth	6 bits + Hi FRC
Viewing Angle	UWVA 85/85/85/85

Panel LCD 14 inch diagonal HD (1366 x 768) Anti-Glare WLED SVA 45% NTSC 220nits eDP 1.2 w/o PSR slim NB non-touch	Outline Dimensions (W x H x D)	316.2 x 198.04 (max.)
	Active Area	309.4 x 173.95
	Weight	<280 g max.
	Diagonal Size	14.0 (inch)
	Thickness	3.0 mm max
	Interface	eDP 1.2 (1 lane)
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	300:1 (typ)
	Refresh Rate	60 Hz
	Brightness	220 nits typical (Panel Only)
	Pixel Resolution	1366 x 768 (HD)
	Format of LCD Pixel Arrangement	RGB
	Backlight	LED
	Color Gamut Coverage	45% of NTSC
	Color Depth	6 bits + Hi FRC
Viewing Angle	SVA 40/40/15/30	

Panel LCD 14 inch diagonal HD (1366 x 768) WLED SVA 45% NTSC 220nits eDP 1.2 w/o PSR slim NB touch	Outline Dimensions (W x H x D)	316.2 x 198.04 (max.)
	Active Area	309.4 x 173.95
	Weight	<413 g max.
	Diagonal Size	14.0 (inch)
	Thickness	3.2 mm max
	Interface	eDP 1.2 (1 lane)
	Surface Treatment	BrightView Glass
	Touch Enabled	Yes
	Contrast Ratio	300:1 (typ)
	Refresh Rate	60 Hz
	Brightness	220 nits typical (Panel Only)
	Pixel Resolution	1366 x 768 (HD)
	Format of LCD Pixel Arrangement	RGB



Technical Specifications

Backlight	LED
Color Gamut Coverage	45% of NTSC
Color Depth	6 bits + Hi FRC
Viewing Angle	SVA 40/40/15/30

STORAGE AND DRIVES

Hard Drives

500 GB 7200 rpm SATA Hard Drive	Drive Weight	0.20 lbs (92 g) ~ 0.21 lbs (95 g)
	Rotation speed	7200 rpm
	Cache Buffer	Up to 32 MB
	Height	0.28 in (7 mm)
	Width	2.75 in (69.85 mm)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	600 MB/s
	Seek Time	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 13 ms; Maximum: 18 ~ 22 ms
	Logical Blocks	976,773,168
	Operating Temperature	32° to 140° F (0° to 60° C) [top cover temp]
	Security Features	ATA Security
	Features	S.M.A.R.T., NCQ, Ultra DMA
1 TB 5400 rpm SATA Hard Drive	Drive Weight	0.21 lbs (94 g)
	Rotation speed	5400 rpm
	Cache Buffer	Up to 32 MB
	Height	0.28 in (7.2 mm)
	Width	2.75 in (69.85 mm)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	600 MB/s
	Seek Time	Single Track 2 ms Average 12 ~ 13 ms Maximum 18 ~ 22 ms
	Logical Blocks	1,953,525,168
	Operating Temperature	32° to 140° F (0° to 60° C) [top cover temp]
	Security Features	ATA Security
	Features	S.M.A.R.T., NCQ, Ultra DMA
1 TB 7200 rpm SATA Hard Drive	Drive Weight	0.20 lbs (90 g)
	Rotation speed	7200 rpm
	Cache Buffer	128 MB
	Height	0.28 in (7.2 mm)



Technical Specifications

Width	2.75 in (69.85 mm)
Interface	ATA-8, SATA 3.0
Transfer Rate	600 MB/s
Seek Time	Single Track: 1.5 ms Average: 13 ms Maximum: 32 ms
Logical Blocks	1,953,525,168
Operating Temperature	32° to 140° F (0° to 60° C) [top cover temp]
Security Features	ATA Security
Features	S.M.A.R.T., NCQ, Ultra DMA

SSD 128 GB 2280 M2 SATA-3 TLC	Form Factor	M.2 2280
	Capacity	128GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (10 g)
	Interface	ATA-8, SATA 3.0
	Maximum Sequential Read	Up To 520 MB/s
	Maximum Sequential Write	Up To 450 MB/s
	Logical Blocks	250,069,680
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	DIPM; TRIM; DEVSLP	

256 GB 2280 PCIe NVMe Value Solid State Drive	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3
	Maximum Sequential Read	Up To 1700 MB/s
	Maximum Sequential Write	Up To 1300 MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	TRIM; L1.2

512 GB 2280 M2 PCIe NVMe TLC Solid State Drive	Form Factor	M.2 2280
	Capacity	512 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)



Technical Specifications

Width	0.87 in (22 mm)
Interface	PCIe NVMe Gen3X4
Maximum Sequential Read	Up To 2600 MB/s
Maximum Sequential Write	Up To 1400 MB/s
Logical Blocks	1,000,215,216
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	TRIM; L1.2

16 GB 2280 PCIe-3x2 NVMe 3D Xpoint Solid State Drive

Form Factor	M.2 2280
Capacity	16 GB
NAND Type	Xpoint
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Interface	PCIe NVMe Gen3X2
Maximum Sequential Read	1400
Maximum Sequential Write	300
Logical Blocks	28,181,188
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	L1.2

SSD 256 GB 2280 M2 SATA-3 TLC

Form Factor	M.2 2280
Capacity	256 GB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Interface	ATA-8, SATA 3.0
Maximum Sequential Read	Up To 560 MB/s
Maximum Sequential Write	Up To 530 MB/s
Logical Blocks	500,118,192
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	DIPM; TRIM; DEVSLP

512 GB 2280 PCIe NVMe Value Solid State Drive

Form Factor	M.2 2280
Capacity	512 GB
NAND Type	Value
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Interface	0.02 lb (10 g)
Maximum Sequential Read	Up To 1500 ~ 1700 MB/s
Maximum Sequential Write	Up To 860 ~ 1500MB/s
Logical Blocks	1,000,215,216



Technical Specifications

Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	"ATA Security, TRIM; L1.2

NETWORKING/COMMUNICATIONS

WWAN

Intel® XMM™ 7360 LTE-Advanced CAT9¹	Technology/Operating bands	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 1400 (Band 11), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1400 (Band 21), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 1700/2100 (Band 66). TDD LTE: 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41). HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz
	Wireless protocol standards	3GPP Release 11 LTE Specification CAT.9, DL 60MHz BW throughput up to 450Mbps; UL 20MHz throughput up to 50Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	GPS	Standalone, A-GPS (MS-A, MS-B)
	GPS bands	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	Maximum data rates	LTE: 450 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	Maximum output power	LTE: 23 dBm HSPA+: 23.5 dBm
	Maximum power consumption	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
	Form Factor	M.2, 3042-S3 Key B
	Weight	5.8 g
	Dimensions (Length x Width x Thickness)	42 x 30 x 2.3 mm



Technical Specifications

1. WWAN module is optional, must be configured at the factory and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

Intel® XMM™ 7262 LTE-Advanced DL CAT6¹	Technology/Operating bands	FDD LTE: 2100 (Band 1), 1800 (Band 3), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 800 (Band 20), 700 (Band 28), HSPA+: 2100 (Band 1), 850 (Band 5), 900 (Band 8)
	Wireless protocol standards	3GPP Release 11 LTE Specification CAT.6, DL 40MHz BW throughput up to 300Mbps; UL 20MHz throughput up to 50Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	GPS	Standalone, A-GPS (MS-A, MS-B and XTRA)
	GPS bands	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz
	Maximum data rates	LTE: 300 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	Maximum output power	LTE: 23 dBm HSPA+: 23.5 dBm
	Maximum power consumption	LTE: 1,200 mA (peak); 830 mA (average) HSPA+: 1,100 mA (peak); 680 mA (average)
	Form Factor	M.2, 3042-S3 Key B
	Weight	6 g
	Dimensions (Length x Width x Thickness)	42 x 30 x 2.3 mm

1. WWAN module is optional, must be configured at the factory and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

WLAN

Intel® 9560 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 5.0 Combo¹ non-vPro	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi® certified
	Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan)

Technical Specifications

	<ul style="list-style-type: none"> • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> • IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum
Power Consumption	Transmit mode: 2.0 W Receive mode: 1.6 W Idle mode (PSP)180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby: 10mW Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display

Technical Specifications

	enclosure
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard with CNVi Interface
Dimensions	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230: 2.8g 2. Type 126: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (–10° to 70° C) Non-operating –40° to 176° F (–40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON
	1. Check latest software/driver release for updates on supported security features.
	2. Maximum output power may vary by country according to local regulations.
	3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

Bluetooth® Specification	4.0/4.1/4.2/5.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ BLE: 1 Mbps signaling data rate ¹ 1. Actual throughput may vary.
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping



Technical Specifications

LE Dual Mode
 LE Link Layer
 LE Low Duty Cycle Directed Advertising
 LE L2CAP Connection Oriented Channels
 Train Nudging & Interlaced Scan
 BT4.2 ESR08 Compliance
 LE Secure Connection- Basic/Full
 LE Privacy 1.2 –Link Layer Privacy
 LE Privacy 1.2 –Extended Scanner Filter Policies
 LE Data Packet Length Extension
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)2
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)

Realtek 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 4.2 Combo¹	Wireless LAN Standards Interoperability Frequency Band Data Rates Modulation Security³ Network Architecture Models	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac Wi-Fi® certified 802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, , 80MHz & 160MHz) Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM <ul style="list-style-type: none"> • IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
---	--	---



Technical Specifications

Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +14dBm minimum • 802.11g: +12dBm minimum • 802.11a: +12dBm minimum • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	Transmit mode 2.0 W Receive mode 1.6 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10 mW Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm
Weight	Type 2230: 2.8g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.2 Wireless Technology

Bluetooth Specification	4.0/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available	Legacy: 0~79 (1 MHz/CH)

Not all configuration components are available in all regions/countries.
c06142920 — DA 16311 - Worldwide — Version 19 — April 22, 2020



Technical Specifications

Channels	BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ BLE: 1 Mbps signaling data rate ¹ 1. Actual throughput may vary.
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Electrical Interface	USB 2.0 compliant
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826
Bluetooth Profiles Supported	Low Voltage Directive IEC950UL, CSA, and CE Mark
	BT4.1-ESR 5/6/7 Compliance
	LE Link Layer Ping
	LE Dual Mode
	LE Link Layer
	LE Low Duty Cycle Directed Advertising
	LE L2CAP Connection Oriented Channels
	Train Nudging & Interlaced Scan
	BT4.2 ESR08 Compliance
	LE Secure Connection- Basic/Full
	LE Privacy 1.2 –Link Layer Privacy
	LE Privacy 1.2 –Extended Scanner Filter Policies
	LE Data Packet Length Extension
	FAX Profile (FAX)
	Basic Imaging Profile (BIP) ²
	Headset Profile (HSP)
	Hands Free Profile (HFP)
	Advanced Audio Distribution Profile (A2DP)

**Realtek
802.11a/b/g/n/ac (1x1)
WLAN and Bluetooth® 4.2
Combo¹**

Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
Interoperability	Wi-Fi certified
Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz
	802.11a/n • 4.9 – 4.95 GHz (Japan)

Technical Specifications

	<ul style="list-style-type: none"> • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> • IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +14dBm minimum • 802.11g: +12dBm minimum • 802.11a: +12dBm minimum • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	Transmit mode 2.0 W Receive mode 1.6 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10 mW Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to



Technical Specifications

	support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm
Weight	Type 2230: 2.8g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (–10° to 70° C) Non-operating –40° to 176° F (–40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps data signaling rate up to 2.17 Mbps BLE: 1 Mbps data signaling rate up to 0.2 Mbps 1. Actual throughput may vary.

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Electrical Interface	USB 2.0 compliant
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode



Technical Specifications

LE Link Layer
 LE Low Duty Cycle Directed Advertising
 LE L2CAP Connection Oriented Channels
 Train Nudging & Interlaced Scan
 BT4.2 ESR08 Compliance
 LE Secure Connection- Basic/Full
 LE Privacy 1.2 –Link Layer Privacy
 LE Privacy 1.2 –Extended Scanner Filter Policies
 LE Data Packet Length Extension
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)2
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)

POWER

HP 45W Smart AC adapter	Dimensions (H x W x D)	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)		
	Weight	0.386 lb (175g) max		
	Input	90 to 265 VAC		
	Output	Input Efficiency	87.74% at 115Vac and 88.4% at 230Vac	
		Input frequency range	47 to 63 Hz	
		Input AC current	1.4 A at 90 VAC	
		Output power	45W	
		DC output	19.5V	
	Connector	Hold-up time	5 msec at 115 VAC input	
		Output current limit	<8.0A	
		4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords		
Environmental Design	Operating temperature	32° F to 95° F (0° to 35° C)		
	Non-operating (storage) temperature	-4° F to 185oF (-20o to 85° C)		
	Altitude	0 to 16,400 ft (0 to 5,000 m)		
	Humidity	20% to 95%		
	Storage Humidity	10% to 95%		
EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.			

HP 65W Smart AC adapter Dimensions 90x51x28.5mm



Technical Specifications

Weight	unit: 220g +/- 10g
Input	Input Efficiency 88% min at 115 VAC and 89% min at 230 VAC
	Input frequency range 47 to 63 Hz
	Input AC current 1.7 A at 90 VAC
	Output
Output	Output power 65W
	DC output 19.5V
	Hold-up time 5 msec at 115 VAC input
	Output current limit <11.0A
Connector	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
Environmental Design	Operating temperature 32° F to 95° F (0° to 35° C)
	Non-operating (storage) temperature -4° F to 185° F (-20° to 85° C)
	Altitude 0 to 16,400 ft (0 to 5000m)
	Humidity 20% to 95%
	Storage Humidity 10% to 95%
	EMI and Safety Certifications

HP 65W EM Smart AC adapter

Dimensions	102x55x30mm	
Weight	270g +/- 10g	
Input	Input Efficiency 87% min at 115V/230V	
	Input frequency range 47 to 63 Hz	
	Input AC current 1.7 A at 90 VAC and maximum load	
	DC output 65W(19.5V/3.33A)	
	Hold-up time 5 msec at 115 VAC input	
	Output current limit <11A, Over voltage protection- 29V max automatic shutdown	
	Connector	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	Environmental Design	Operating temperature 0° to 35° C
Non-operating (storage) temperature -20° to 85° C		
Altitude 0 to 5,000 m		
Humidity 0% to 95%		
Storage Humidity 0% to 95%		
EMI and Safety Certifications		*CE Mark - full compliance with LVD and EMC directives



Technical Specifications

EMI and Safety Certifications

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt nPFC USB type C

Dimensions

74x74x28.5mm

Weight

unit: 245g +/- 10g

Input

Input Efficiency

81.5% min at 115 Vac/ 230Vac @ 5V/3A
86.7% min at 115 Vac/ 230Vac @ 9V/3A
88% min at 115 Vac/ 230Vac @ 10V/5A
88% min at 115 Vac/ 230Vac @ 12V/5A
89% min at 115 Vac/ 230Vac @ 15V/4.33A
89% min at 115 Vac/ 230Vac @ 20V/3.25A

Input frequency range

47 to 63 Hz

Input AC current

1.7 A at 90 VAC and maximum load

Output power

65W

DC output

5V/9V/10V/12V/15V/20V

Hold-up time

5ms at 115 Vac input

Output current limit

<8.0A

Connector

Type C

Environmental Design

Operating temperature

0° to 35° C

Non-operating (storage) temperature

-20° to 85° C

Altitude

0 to 5,000 m

Humidity

0% to 95%

Storage Humidity

0% to 95%

EMI and Safety Certifications

*CE Mark - full compliance with LVD and EMC directives

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 45 Watt nPFC USB type C

Dimensions

62.0x62.0x28.5mm

Weight

unit: 220g +/- 10g

Input

Input Efficiency

Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:5V: 81.5%9V : 86.7%10V : 87.5%12V : 87.8%15V: 87.8%20V : 87.8%

Input frequency range

47 to 63 Hz

Input AC current

Max. 1.4 A at 90 Vac

Output power

5V/15W
9V/27W



Technical Specifications

		10V/37.5W
		12V/45W
		15V/45W
		20V/45W
	DC output	5V/9V/10V/12V/15V/20V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<5.0A
Connector		Type C
Environmental Design	Operating temperature	0° to 35° C
	Non-operating (storage) temperature	-20° to 85° C
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
EMI and Safety Certifications		*CE Mark - full compliance with LVD and EMC directives
		* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.
		* MTBF - over 200,000 hours at 25°C ambient condition.

3 Cell WHr 45 Long Life - Polymer HP Fast Charge Technology¹	Dimensions	3.900Ah
	Weight	45Wh
	Connector	Type C
	Energy	32° to 113° F (0° to 45° C)
	Voltage	14° to 122° F (-10° to 60° C)

1. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part Number
Cases	HP Essential Top Load Case	H2W17AA
	HP Essential Backpack	H1D24AA
	HP Essential Messenger Case	H1D25AA
Dockings	HP USB-C Mini Dock	1PM64AA
	HP USB-C Universal Dock	1MK33AA
	HP USB-C Dock G4	3FF69AA
Input/Output	HP USB Essential Keyboard and Mouse	H6L29AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP HDMI to DVI Adapter	F5A28AA
Memory	4GB 2666MHz DDR4	4VN05AA
	8GB 2666MHz DDR4	4VN06AA
	16GB 2666 MHz DDR4	4VN07AA
Power	HP 45W Smart AC Adapter 4.5mm	H6Y88AA
	HP 65W Slim AC Adapter	H6Y82AA
	HP 65W USB-C Power Adapter	3PN48AA
	HP 45W USB-C Power Adapter	1HE17AA
	HP 65W USB-C Power Adapter	1HE08AA
	HP Power Bank	N9F71AA
	HP USB-C Power Bank	2NA10AA
	HP 45W LC USB-C Power Adapter	1MZ01AA#ABA
Storage	HP External USB Optical Drive	F2B56AA
	HP 500GB 7200rpm HDD	F3B97AA
Security	HP Combination Lock	T0Y15AA
	HP Essential Keyed Cable lock 12.3mm	T0Y14AA
	HP Keyed Cable Lock 10mm	T1A62AA
	HP UltraSlim Keyed Cable Lock	T1A62AA
UCC	HP Conferencing Keyboard	K8P74AA
	HP Speaker Phone	K7V16AA
	HP Wired Headset	K7V17AA
Displays	HP ProDisplay P223 21.5-inch Monitor	X7R61AA
	HP ProDisplay P232 23-inch Monitor	K7X31AA
	HP ProDisplay P240va 23.8-inch Monitor	X3B48AA
	HP EliteDisplay E243 23.8-inch Monitor	1FH47AA
	HP EliteDisplay E243m 23.8-inch Collaboration Monitor	1FH48AA
	HP EliteDisplay E273 27-inch Monitor	1FH50AA



Summary of Changes

Date of change:	Version History:		Description of change:
December 10, 2018	V1 to V2	Removed	Dock UltraSlim
December 12, 2018	V2 to V3	Removed	Phonewise Software
December 21, 2018	V3 to V4	Added	Skype in at a glance section
January 30, 2019	V4 to V5	Added	Storage Section
March 7, 2019	V5 to V6	Updated	Passed MIL-STD
March 15, 2019	V6 to V7	Added	Processors
March 27, 2019	V7 to V8	Updated	Storage and drives and Graphic section
April 17, 2019	V8 to V9	Updated	MIL-STD
May 7, 2019	V9 to V10	Updated	At a glance section
June 11, 2019	V10 to V11	Added	HP Cloud Recovery
July 23, 2019	V11 to V12	Added	Speaker to Audio section
September 20, 2019	V12 to V13	Added	Lock Slot, 250nits Panel
October 11, 2019	V13 to V14	Added	DisplayPort™ 1.2 and i5-8365U Processor
November 21, 2019	V14 to V15	Updated	Longevity and Upgrading section
January 8, 2020	V15 to V16	Added	Processor i7-8665U
January 13, 2020	V16 to V17	Updated	Primary Battery and added 8665U processor
February 27, 2020	V17 to V18	Updated	Copyright and footnote for fingerprint sensor.
April 22, 2020	V18 to V19	Updated	Networking / Communications section

Copyright © 2020 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Bluetooth is a trademark of its proprietor and used by HP Inc. under license. Intel, Core, Celeron and Intel vPro are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. NVIDIA, the NVIDIA logo, and GeForce are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

