

IN119HDxa Projector

InFocus

Value-packed HD Projector

Part #: IN119HDxa

Confidently project your most important content with the high brightness, high-quality, incredibly affordable IN119HDxa. Built to perform with HDMI input, high brightness, high contrast, and BrilliantColor technology, the IN119HDxa features a compact, light weight design so it's easy to move and easy to install.



Key Features:

- Full 1920 x 1080 HD resolution for exceptional image quality
- 3,600 lumens and high 28,000:1 contrast ratio make details pop
- Vivid and accurate color with BrilliantColor technology
- Display 3D content from Blu-ray, game consoles, and more
- Lamp life up to an amazing 15,000 hours, plus no filters to replace



Full native HD resolution

Achieve quality images and true-to-life colors with DLP technology with InFocus BrilliantColor implementation. 3,600 lumens mean bright, clear images even with the lights on, while the 28,000:1 contrast ratio adds sharpness with darker blacks and whiter whites. Preset modes ensure quality images on a beige wall, whiteboard, blackboard, or any surface that suits your presentation.



Advanced 3D Support



Powered by the latest DLP technology, the IN119HDxa displays stunning 3D content from PCs, Blu-Ray, Xbox, PlayStation, and many other sources. Just add 144Hz DLP Link 3D glasses (sold separately) to seamlessly synchronize for an awesome 3D experience.

HDMI CEC Compatible

The IN119HDxa is an HDMI Consumer Electronics Control (CEC) compatible device, so you can control it, and up to 14 other HDMI CEC compatible devices, with one remote.

Specifications*

	IN119HDxa
Display Technology	Texas Instruments DLP® 0.65" DMD with DarkChip3™ 1080p Technology
Resolution	Full HD (1920 x 1080) 1080p
Brightness (Normal/Eco)	3,600 / 2,800 lumens
Contrast Ratio	28,000:1
Lamp Life (Normal/Eco/Dynamic)	5,000 / 7,000 / 15,000 hours
Throw Ratio	1.124~1.47(D/W) @ 60"
Throw Distance (focus range)	1.2m to 7.5m
Zoom Type	1.3:1
I/O Connectors	HDMI x2 (1.4a 3D support) + MHL v2.1, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service
Speaker (Watts)	10
Keystone Correction	± 40° Vertical
Weight	5.5 lbs / 2.5 kg
Dimensions (W x D x H)	4 x 12.4 x 8.8 in / 101.6 x 315 x 223.5 mm
Aspect Ratio	16:9 Native, 16:10/4:3 Compatible
Offset	116% ±5%
Projection Screen Size	1.06 - 7.75m (41.8" - 305") Diagonal 16:9
Projection Distance	1.5 - 10 m
Projection Lens (f-stop)	2.43 (Wide.)~ 2.78 (Tele)
Focus (manual/power)	Manual
Image Width	36.95" ~ 301.4" optimized @ 60"
Lens Shift H	N/A
Lens Shift V/Offset	16%
Uniformity	80%
Maximum Resolution	1080p
Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, PC, Mac
Video Compatibility	PAL, NTSC, SECAM, 480i/p, 576i/p, 720p, 1080i, 1080p
3D Compatibility	1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Horizontal Scan Rate	15.375~91.146 KHz
Horizontal Scan Rate	24 ~ 85Hz (120Hz for 3D)
Displayable Colors	1073.4 Million
Noise Level (Eco mode)	24dB
Power Supply	100-240V, 50-60Hz
Lamp Type (Normal, Eco, Dynamic)	195 / 160 / 83W
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Security	Security bar, Kensington lock, password protection
On Screen Display	27 Languages: English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Danish, Norwegian, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Vietnamese, Farsi, Romanian, Indonesian
Standard Accessories	Power cord, remote control, documentation
Projection method	Front, rear, ceiling mount, table top

*Product specifications, terms, and offerings are preliminary and subject to change at any time without notice.

Optional Accessories

Replacement Lamp (SP-LAMP-097)
 Universal Ceiling Mount (PRJ-MNT-UNIV)
 LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
 LiteShow Mount (PRJ-MNT-LS3)
 Soft Carry Case (CA-SOFTVAL-2)
 DLP Link 3D Glasses (X103-EDUX3-R1)
 Extended Warranties (EPW-PJV1, EPW-PJV2)

