


Overview

HPE Cloudline CL2600 Gen10 Server

Need an open system known for its design, reliability, and global support? The HPE Cloudline CL2600 Gen10 Server is the standard of open systems in a 1U Hewlett Packard Enterprise flagship design. From quality controls and rigor in the manufacturing and design, to security controls in the supply chain, this server represents peace of mind. It is ideal for service providers, hyperscalers, and a segment of traditional enterprise customers seeking commonality in the server options and management across vendors. Deploy globally and confidently with HPE's global service and support.


The HPE Cloudline CL2600 Gen10 server supports the first and second generation Intel® Xeon® Scalable processors, six memory channels per CPU, an AMI BIOS for open systems management, and industry standard options all in a 1U standard-depth chassis with options for power supplies to support AC and DC power. In addition, the server supports up to eight SFF SAS/SATA HDD/SSD + two SFF NVMe, or up to ten SFF NVMe SSDs.



8SFF Front View- Standard 8SFF shown

Item	Description	Item	Description
1.	Drive Support Label	6.	NIC Status LED
2.	Serial number label pull tab	7.	USB 3.0 port
3.	Optional: +2 SFF NVMe Option	8.	UID LED
4.	Power On/Standby and system power LED	9.	Up to 8 SFF SAS/SATA HDD/SSD drive bays
5.	Health LED		


Overview



Premium 10SFF NVMe Front View

Item	Description	Item	Description
1.	Drive Support Label	6.	NIC Status LED
2.	Serial number label pull tab	7.	USB 3.0 port
3.	2 SFF NVMe drive bays	8.	UID LED
4.	Power On/Standby and system power LED	9.	8 SFF SAS/SATA/NVME HDD/SSD drive bays
5.	Health LED		

Overview

**Standard for all CL2600 Gen10 - Internal View**


- | | |
|--|---|
| 1. Standard single rotor hot plug fans ¹ | 9. Up to 2 Power Supplies for redundant power |
| 2. DDR4 DIMM slots (Fully populated 24 DIMMs shown) | 10. Slot 1 from Primary Riser |
| 3. Up to 2 processors (shown with standard heat sinks) | 11. Slot 2 from Primary Riser (expansion card shown); |
| 4. Dual internal USB 3.0 connector | 12. Primary (CPU1) PCIe 3.0 riser ³ |
| 5. Hard Drive backplane power connector | 13. x4 SATA port 1&2 |
| 6. System Battery | 14. Reserved |
| 7. Optional: TPM 2.0 | 15. Front Power USB 3.0 connector |
| 8. Secondary (CPU2) PCIe 3.0 riser ² | |

NOTE 1: 1 CPU – 5 standard fans, 2 CPUs – 7 standard fans. 7 High-Performance Fans (P10544-B21) optional for 8SFF chassis, required upon selecting 2NVMe Backplane kit with 8SFF chassis, and standard for Premium 10SFF chassis

NOTE 2: Not available on Premium 10SFF chassis due to dedicated 10 x4 NVMe direct attach PCIe riser; Optional 1x16 Low Profile Riser for 8SFF Chassis corresponding to Slot 3 in the rear; requires 2 processors for functionality

NOTE 3: Standard: x16/x8. Optional: x16/x16 + Dual M.2 SATA on riser (P10572-B21). OR x16/x8 + Dual x4 NVMe (P09679-B21)

Overview



Standard for all CL2600 Gen10 - Rear View

- | | | | |
|----|---|-----|---|
| 1. | Slot 1 from Primary PCIe 3.0 riser (x16) | 6. | Embedded 4x 1GbE Adapter (if equipped) ³ |
| 2. | Slot 2 from Primary PCIe 3.0 riser ¹ | 7. | BMC Management Port (1Gb) |
| 3. | Slot 3 from Secondary PCIe 3.0 riser ² | 8. | Optional serial port (with serial cable) |
| 4. | Power Supply (PS1&PS2) | 9. | 2x USB 3.0 Ports |
| 5. | VGA port | 10. | Rear UID LED |

NOTE 1: 1x8 standard or 1x16 with optional M.2 riser

NOTE 2: Not available on Premium 10SFF chassis due to dedicated 10 x4 NVMe direct attach PCIe riser; Optional 1x16 Low Profile Riser for 8SFF Chassis corresponding; requires 2 processors for functionality

Note 3: Network Choice (NC) models do not include embedded LOM.

What's New

- Network Choice (NC) CTO models featuring no embedded LOM
- 2nd generation Intel® Xeon® Scalable Processor Family
- 16/32/64GB 2933 MT/s DIMMs
- Intel® VROC Software License
- 480/960GB & 2.4TB Secure Encrypted Drives (SED)
- 375GB Write Intensive SFF SSD
- HPE CL LSI CVM02 CacheVault Module Kit
- HPE CL SAS MegaRAID SafeStore Software License and Physical Key FIO Kit

Overview

Platform Information

Form Factor

1U rack

Chassis Types

8 SFF chassis supporting SAS/SATA HDD/SSD with optional 2 NVMe or dual (2x) M.2 2280 SATA cartridges

10 SFF Premium chassis supporting 2 NVME and up to 8 SFF SAS/SATA/NVME with optional dual (2x) M.2 2280 SATA cartridges

System Fans

Single rotor hot plug fans will be included

NOTE: The CL2600 Gen10 will support up to 7 fans with fan redundancy built in. One fan rotor failure will place server in degraded mode but fully functional. Two fan rotor failures could provide warning and imminent server shutdown.

For 8 SFF chassis:

1 CPU – Includes 5 standard fans

2 CPUs – Includes 7 standard fans

NOTE: Optional High-Performance Fan Kit (P10544-B21) available (includes 7 fans).

For 10 NVMe Premium chassis:

2 CPUs – Includes 7 high performance fans as standard

Standard Features

Standard Features

Processors – Up to 2 of the following depending on model.

NOTE: The 2nd digit of the processor model number “x1xx” and “x2xx” is used to denote the processor generation (i.e. 1=1st generation and 2=2nd generation)

NOTE: Maximum memory per socket is dependent on processor selection. 2nd generation processors supporting 2 TB per CPU are indicated by the “M” in the processor model names (i.e. 8260M).

NOTE: This table covers the public Intel offering only.

NOTE: For more information regarding Intel Xeon processors, please see the following <http://www.intel.com/xeon>

2 nd Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Platinum 8280M Processor	2.7 GHz	28	38.50 MB	205W	3 @ 10.4 GT/s	2933 MT/s	2TB
Platinum 8276M Processor	2.2 GHz	28	38.50 MB	165W	3 @ 10.4 GT/s	2933 MT/s	2TB
Platinum 8276 Processor	2.2 GHz	28	38.50 MB	165W	3 @ 10.4 GT/s	2933 MT/s	1TB
Platinum 8270 Processor	2.7 GHz	26	35.75 MB	205W	3 @ 10.4 GT/s	2933 MT/s	1TB
Platinum 8268 Processor	2.9 GHz	24	35.75 MB	205W	3 @ 10.4 GT/s	2933 MT/s	1TB
Platinum 8260M Processor	2.4 GHz	24	35.75 MB	165W	3 @ 10.4 GT/s	2933 MT/s	2TB
Platinum 8260 Processor	2.4 GHz	24	35.75 MB	165W	3 @ 10.4 GT/s	2933 MT/s	1TB

NOTE: Platinum Processors:

2nd Generation:

6-Channel DDR4 @ 2933 MT/s.

Support for: Vector Neural Network Instructions (VNNI) for inference acceleration.

2 and 4 socket capable, 2S - 2UPI, 2S - 3UPI, 4S - 3UPI @ 10.4 GT/s.

Intel Turbo Boost Technology, Intel Hyper-Threading Technology Intel AVX-512 (2x 512-bit FMA).

48 lanes PCIe 3.0, advanced RAS

2 nd Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Gold 6254 Processor	3.1 GHz	18	24.75 MB	200W	3 @ 10.4 GT/s	2933 MT/s	1TB
Gold 6248 Processor	2.5 GHz	20	27.5 MB	150W	3 @ 10.4 GT/s	2933 MT/s	1TB
Gold 6242 Processor	2.8 GHz	16	22 MB	150W	3 @ 10.4 GT/s	2933 MT/s	1TB
Gold 6240 Processor	2.6 GHz	18	24.75 MB	150W	3 @ 10.4 GT/s	2933 MT/s	1TB
Gold 6230 Processor	2.1 GHz	20	27.5 MB	125W	3 @ 10.4 GT/s	2933 MT/s	1TB
Gold 5220 Processor	2.2 GHz	18	24.75 MB	125W	2 @ 10.4 GT/s	2666 MT/s	1TB
Gold 5218 Processor	2.3 GHz	16	22 MB	125W	2 @ 10.4 GT/s	2666 MT/s	1TB
Gold 5217 Processor	3.0 GHz	8	11 MB	115W	2 @ 10.4 GT/s	2666 MT/s	1TB
Gold 5215M Processor	2.5 GHz	10	13.75 MB	85W	2 @ 10.4 GT/s	2666 MT/s	2TB
Gold 5215 Processor	2.5 GHz	10	13.75 MB	85W	2 @ 10.4 GT/s	2666 MT/s	1TB

Standard Features

1 st Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Gold 6152 Processor	2.1 GHz	22	30.25 MB	140W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6148 Processor	2.4 GHz	20	27.50 MB	150W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6144 Processor	3.5 GHz	8	24.75 MB	150W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6142 Processor	2.6 GHz	16	22.00 MB	150W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6140 Processor	2.3 GHz	18	24.75 MB	140W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6138 Processor	2.0 GHz	20	27.50 MB	125W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6136 Processor	3.0 GHz	12	24.75 MB	150W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6134 Processor	3.2 GHz	8	24.75 MB	130W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6130 Processor	2.1 GHz	16	22.00 MB	125W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6128 Processor	3.4 GHz	6	19.25 MB	115W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 6126 Processor	2.6 GHz	12	19.25 MB	125W	3 @ 10.4 GT/s	2666 MT/s	768GB
Gold 5122 Processor	3.6 GHz	4	16.50 MB	105W	2 @ 10.4 GT/s	2666 MT/s	768GB
Gold 5120 Processor	2.2 GHz	14	19.25 MB	105W	2 @ 10.4 GT/s	2400 MT/s	768GB
Gold 5118 Processor	2.3 GHz	12	16.50 MB	105W	2 @ 10.4 GT/s	2400 MT/s	768GB
Gold 5115 Processor	2.4 GHz	10	13.75 MB	85W	2 @ 10.4 GT/s	2400 MT/s	768GB

NOTE: Gold Processors:

2nd Generation:

6-Channel DDR4 @ 2933 MT/s (Gold 6200 skus only), 2666 MT/s on all Gold 5200 skus

Support for: Vector Neural Network Instructions (VNNI) for inference acceleration.

2 and 4 socket capable, 2S - 2UPI, 2S - 3UPI, 4S - 3UPI @ 10.4 GT/s.

Intel Turbo Boost Technology, Intel Hyper-Threading Technology Intel AVX-512 (2x 512-bit FMA).

48 lanes PCIe 3.0, advanced RAS

1st Generation:

6-Channel 1DPC DDR4 @ 2400 MT/s (SKU 5122 - supports 2666 MT/s).

768 GB max memory capacity (1.5 TB on select skus).

2 and 4 socket capable, 2S - 2UPI, 4S - 3UPI @ 10.4 GT/s.

Intel Turbo Boost Technology, Intel Hyper-Threading Technology, Intel AVX-512 (1x 512-bit FMA) (SKU 5122 - supports 2x512 bit FMA).

48 lanes PCIe 3.0, advanced RAS.

Standard Features

2 nd Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Silver 4216 Processor	2.1 GHz	16	22 MB	100W	2 @ 9.6 GT/s	2400 MT/s	1TB
Silver 4215 Processor	2.5 GHz	8	11 MB	85W	2 @ 9.6 GT/s	2400 MT/s	1TB
Silver 4214 Processor	2.2 GHz	12	16.5 MB	85W	2 @ 9.6 GT/s	2400 MT/s	1TB
Silver 4210 Processor	2.2 GHz	10	13.75 MB	85W	2 @ 9.6 GT/s	2400 MT/s	1TB
Silver 4208 Processor	2.1 GHz	8	11 MB	85W	2 @ 9.6 GT/s	2400 MT/s	1TB
1 st Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Silver 4116 Processor	2.1 GHz	12	16.50 MB	85W	2 @ 9.6 GT/s	2400 MT/s	768GB
Silver 4114 Processor	2.2 GHz	10	13.75 MB	85W	2 @ 9.6 GT/s	2400 MT/s	768GB
Silver 4112 Processor	2.6 GHz	4	8.25 MB	85W	2 @ 9.6 GT/s	2400 MT/s	768GB
Silver 4110 Processor	2.1 GHz	8	11.00 MB	85W	2 @ 9.6 GT/s	2400 MT/s	768GB
Silver 4108 Processor	1.8 GHz	8	11.00 MB	85W	2 @ 9.6 GT/s	2400 MT/s	768GB

NOTE: Silver Processors:

2nd Generation:

6-Channel DDR4 @ 2400 MT/s.

2TB max RAM

Support for: Intel® Vector Neural Network Instructions (VNNI) for inference acceleration.

2 and 4 socket capable, 2S - 2UPI, 2S - 3UPI, 4S - 3UPI @ 9.6 GT/s.

Intel Turbo Boost Technology, Intel Hyper-Threading Technology Intel AVX-512 (2x 512-bit FMA).

48 lanes PCIe 3.0, standard RAS

1st Generation:

6-Channel DDR4 @ 2400 MT/s, 768 GB max memory capacity.

2 socket capable, 2S - 2UPI @ 9.6 GT/s.

Intel Turbo Boost Technology, Intel Hyper-Threading Technology, Intel AVX-512 (1x 512-bit FMA).

48 lanes PCIe 3.0, standard RAS.

1 st Generation Intel® Xeon® Scalable Processor Family							
Intel Xeon Models	CPU Frequency	Cores	L3 Cache	Power	UPI	DDR4	Memory per socket
Bronze 3106 Processor	1.7 GHz	8	11.00 MB	85W	2 @ 9.6 GT/s	2133 MT/s	768GB
Bronze 3104 Processor	1.7 GHz	6	8.25 MB	85W	2 @ 9.6 GT/s	2133 MT/s	768GB

NOTE: Bronze Processors:

1st Generation:

6-Channel DDR4 @ 2133 MT/s, 768 GB max memory capacity.

2 socket capable, 2S - 2UPI @ 9.6 GT/s.

Intel AVX-512 (1x 512-bit FMA).

48 lanes PCIe 3.0, standard RAS.

Standard Features

Chipset

Intel C621 Chipset

NOTE: For more information regarding Intel® chipsets, please see the following

URL: <https://www.intel.com/content/www/us/en/products/chipsets/server-chipsets.html>

On System Management Chipset

HPE BMC – remote server management processor embedded on the system board of the server

Memory

Type	DDR4	Industry Standard DDR4 Registered (RDIMM), Load Reduced (LRDIMM) Memory
DIMM Slots Available	24	12 DIMM slots per processor, 6 channels per processor, 2 DIMMs per channel
Maximum capacity (LRDIMM)	1.5 TB	24 x 64 GB LRDIMM @ 2933 MT/s
Maximum capacity (RDIMM)	1.5 TB	24 x 64 GB RDIMM @ 2933 MT/s

NOTE: Maximum memory per socket is dependent on processor selection. 2nd generation processors supporting 2 TB per CPU are indicated by the “M” in the processor model names (i.e. 8260M).

NOTE: Mixing of RDIMM and LRDIMM memory is not supported.

Memory Protection

Advanced ECC	Advanced ECC uses single device data correction to detect and correct single and all multibit error that occurs within a single DRAM chip.
Online Spare	Memory online spare mode detects a rank that is degrading and switches operation to the spare rank.

Expansion Slots

Primary Riser	Expansion Slots #	Technology	Bus Width	Connector Width	Processor	Slot Form Factor
	1	PCIe 3.0	x16	x16	CPU1	Full-height, 3/4 length (up to 9.5in)
	2	PCIe 3.0	x8	x8	CPU1	Low Profile
Primary SATA M.2 Riser	Expansion Slots #	Technology	Bus Width	Connector Width	Processor	Slot Form Factor
	1	PCIe 3.0	x16	x16	CPU 1	Full-height; 3/4 length (up to 9.5in)
	2	PCIe 3.0	x16	x16	CPU 1	Low Profile
Primary NVMe Riser	Expansion Slots #	Technology	Bus Width	Connector Width	Processor	Slot Form Factor
	1	PCIe 3.0	x16	x16	CPU 1	Full-height; 3/4 length (up to 9.5")
	2	PCIe 3.0	x8	x8	CPU 1	Low Profile
Secondary Riser*	Expansion Slots #	Technology	Bus Width	Connector Width	Processor	Slot Form Factor
	3	PCIe 3.0	x16	x16	CPU 2	Low Profile

Standard Features

Operating Systems and Virtualization Software

2nd Generation Intel® Xeon® Scalable Processor Family

- Microsoft Windows Server 2012 R2
- Microsoft Windows Server 2016
- SLES 12 SP3 & 15 (64 bit) w/ Xen and KVM
- Red Hat Enterprise Linux 7.6 (64 bit) (includes KVM)
- VMware vSphere 6.5 U3, 6.7 U1
- CentOS 7.6
- Ubuntu LTS 18.04

1st Generation Intel® Xeon® Scalable Processor Family

- Microsoft Windows Server 2012 R2
- Microsoft Windows Server 2016
- Red Hat Enterprise Linux (64 bit) w/KVM 6.9, 6.10, 7.4, 7.5
- SLES 12 SP3 (64 bit) w/ Xen and KVM
- VMware vSphere 6.5 U1
- CentOS 7.5
- Ubuntu LTS 18.04

NOTE: For more information visit <http://www.hpe.com/info/ossupport>

Industry Standard Compliance

- AMI Aptio 5.12
 - UEFI 2.5 Support
 - UEFI Shell 2.1 Support
 - UEFI PI 1.4 Support
 - ACPI 6.1 Compliant
 - PCIe 3.0 Compliant
 - SMBIOS 3.0
 - PXE Support
 - WOL Support
 - USB 3.0 Compliant
 - USB 2.0 Compliant
 - Redfish version 1.0
 - IPMI 2.0
 - DCMI (Data Center Management Interface), version 1.5
 - SPS 3.0
 - SMBUS 2.0
-

Graphics

Integrated video standard

- Video modes up to 1920 x 1200 @ 60 Hz (32 bpp)
-

Standard Features

AMI UEFI BIOS

Unified Extensible Firmware Interface (UEFI) is an industry standard for better manageability and secured configuration than the legacy ROM at boot time. HPE Cloudline Gen10 servers have a UEFI Class 2 implementation and support both UEFI Mode (default) and Legacy BIOS Mode. Please reference the CL2600 User & Maintenance Guide.

- UEFI enables numerous new capabilities specific to HPE servers such as:
- Secure Boot and Secure Start enable for enhanced security
- Operating system specific functionality
- Support for > 2.2 TB (using GPT) boot drives
- USB 3.0 Stack
- Embedded UEFI Shell
- PXE boot support for IPv6 networks
- UEFI Boot Mode only
- TPM 2.0 Support
- NVMe Boot Support
- iSCSI Software Initiator Support.
- HTTP Boot support
- Boot support for option cards that only support a UEFI option ROM

NOTE:For UEFI Boot Mode, boot environment and OS image installations should be configured properly to support UEFI.

NOTE:Legacy FIO Setting (P11219-B22) can be selected to configure the system in Legacy mode in the factory for your HPE Cloudline Gen10 Server.

Embedded Management

Open Systems BMC

Industry standard baseboard management controller (BMC®) for effective remote management with IPMI / Redfish®, and DCMI/PXE boot standard interfaces allowing simple/scripted integration into an application infrastructure. A user can access the BMC firmware (FW), via a web browser, or scripting for server status configurations, user(s) privilege setup, FW updates, power control, event logging, BMC Network, serial port management, and SOL configuration.

Redfish API

Redfish API conformance and offers simplified server management automation such as configuration and maintenance tasks based on modern industry standards.

Security

- UEFI Secure Boot and Secure Start Support
- SECURE FLASH
- SSL (HTTPS) for secured sessions
- TPM (Trusted Platform Module) 2.0 option

NOTE: TPM 2.0 only works when UEFI is set to default

- Bezel Locking Kit
-

Standard Features

Warranty

Hardware support is available for 3 years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Hard drives have either a one year or three-year warranty; refer to the HPE Cloudline Servers and Options Global Limited Warranty and Technical Support for details.

NOTE: Server Warranty includes 3 Years Parts with five (5) days response time, 0 Years Labor, and 0 Years Onsite Support. Additional information regarding worldwide limited warranty and technical support is available at:

http://www.hpe.com/support/cloudline_warranty_en

Response time

Response times are based on local standard business days and working hours. Unless otherwise stated, all responses are measured from the time the customer calls until Hewlett Packard Enterprise has either established a mutually acceptable time for support to be performed, or Hewlett Packard Enterprise has begun to provide support or remote diagnostics. Response time is based on commercially reasonable effort. In some countries and under certain supplier constraints, response time may vary. If your location is outside the customary service zone, response time may be longer or there may be an additional charge. Contact your local Hewlett Packard Enterprise service organization for response time availability in your area.

Optional Features

Rack and Power Infrastructure

The story may end with servers, but it starts with the foundation that makes compute go – and business grow. We have reinvented our entire portfolio of rack and power products to make IT infrastructure more secure, more practical, and more efficient. In other words, we've created a stronger, smarter, and simpler infrastructure to help you get the most out of your IT equipment. As an industry leader, Hewlett Packard Enterprise is uniquely positioned to address the key concerns of power, cooling, cable management and system access.

HPE G2 Advanced and Enterprise Racks are perfect for the server room or today's modern data center with enhanced airflow and thermal management, flexible cable management, and a 10 year Warranty to support higher density computing.

HPE G2 PDUs offer reliable power in flexible form factors that operate at temperatures up to 60°, include color-coded outlets and load segments and a low-profile design for optimal access to the rack and support for dense rack environments.

HPE Uninterruptible Power Systems are cost-effective power protection for any type workload. Some UPSs include options for remote management and extended runtime modules so your critical dense data center is covered in power outages.

HPE KVM Solutions include a console and switches designed to work with your server and IT equipment reliably. We have got a cost-effective KVM switch for your first rack and multiple connection IP switches with remote management and security capabilities to keep your data center rack up and running.

Learn more about HPE Racks, KVM, PDUs and UPSs at [HPE Rack and Power Infrastructure](#).

Service and Support

Protect your business beyond warranty with Foundation Care NBD and Cloudline Support Services

HPE Foundation Care Next Business Day and Cloudline Support Services provide remote diagnosis and support, scheduled onsite hardware repair/troubleshooting, and coverage for replacement components. Also available with defective media retention (DMR) or comprehensive defective media retention (CDMR) services.

Extended support duration for up to 5 years is available on Foundation Care NBD services.

- HPE Cloudline 3 Years Parts + Remote Technical Support + Defective Media Retention
- HPE Cloudline 3 Years Parts + Remote Technical Support + Comprehensive Defective Media Retention
- HPE Foundation Care Next Business Day (3, 4, and 5 years options)
- HPE Foundation Care Next Business Day + Defective Media Retention (3, 4, and 5 years options)
- HPE Foundation Care Next Business Day + Comprehensive Defective Media Retention (3, 4, and 5 years options)

More information on Foundation Care NBD available at: <https://h20195.www2.hpe.com/v2/getpdf.aspx/4aa4-8876enw.pdf>

More information on Cloudline Support Services available at:

<https://h20195.www2.hpe.com/v2/GetPDF.aspx/4AA5-9207ENN.pdf>

Standard Support Recommendation

Connect to Hewlett Packard Enterprise for faster problem resolution. Cloudline Carepack Services provides hardware onsite response. Simplify your support experience and make Hewlett Packard Enterprise your first call for hardware or software questions.

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

Datacenter Care for Hyperscale

DC for Hyperscale is available for Service Providers and HPC customers who use a scale out approach to computing with a high volume homogenous infrastructure and resilient architecture. Customers can take advantage of this environment support tailored to their operating model. More information at <https://h20195.www2.hpe.com/v2/GetPDF.aspx/4AA6-3460ENW.pdf>.

Spares Management Service

Provides customers with spare parts inventory for onsite stocking, and access to the HPE Spares Management Tool – an automated inventory management tool that helps enable real-time inventory management. More information at

<https://h20195.www2.hpe.com/v2/GetPDF.aspx/4AA1-3116ENW.pdf>.

Advisory & Professional Services

Design, strategy, road map, and other services to help enable the digital transformation journey, tuned to IT and business needs. Advisory Services helps customers on their journey to Hybrid IT, Big Data, and the Intelligent Edge. More information at

<https://www.hpe.com/us/en/services/consulting.html>.

Operational offerings to improve performance and securely handle retirement of customers' IT environments.

Operate & Improve performance, minimize risk of downtime, and reduce security risks.

Retire & Sanitize to safely and securely dispose of retired IT, and ensuring customer data cannot be compromised.

Integrate the new solution with project management, installation and startup, relocation services, and more. We help mitigate risk to the business so there is no interruption when new technology is being integrated in the existing IT environment. More information at

<https://www.hpe.com/us/en/services/professional.html>.

Core Options

This section lists some of the steps required to configure a Factory Integrated Model.

To ensure valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

1. Factory Integrated Models must start with a CTO Server.
2. FIO indicates that this option is only available as a factory installable option.
3. All Factory Integrated Models (FIO) will include the hard drive carriers
4. Some options may not be integrated at the factory. Contact your local sales representative for additional information

Step 1: Base Configuration (choose one of the following configurable models)

Network Choice (NC) Models

Network Choice models do not include embedded LOM. To enable networking capability an HPE Ethernet 1Gb 4-port 366FLR Adapter will be auto-populated for primary NIC with customer choice of additional NICs (stand-up cards).

CTO Server	HPE CL2600 Gen10 8SFF NC CTO Svr	HPE CL2600 Gen10 Prem 10SFF NC CTO Svr
SKU Number	P20550-B21	P20551-B21
Processor	Not included as standard- Supports both 1 st and 2 nd Generation Intel Xeon processors	
DIMM Slots	24-DIMM slots (12 per CPU)	
Storage Controller	Choice of Intel C621 embedded SW RAID with 8 SATA ports, Intel VROC, or optional PCIe plug-in RAID/HBA controller	
PCIe	2 PCIe slots (1 x16 FH / 1 x8 LP) Optional: 1 x16 FH or LP	2 PCIe slots (1 x16 FH / 1 x8 LP)
Drive Cage - included	8 SFF - SAS/SATA Optional: up to 2 NVMe or 1 Dual (2x) 2280 M.2 cartridges	10 NVMe – 8 SAS/SATA/NVME + 2 NVME Optional: 1 Dual (2x) 2280 M.2 cartridges
Network Controller	HPE Ethernet 1Gb 4-port 366FLR Adapter (sideband supported) plus optional PCIe stand up card(s)	
Fans	1 CPU – 5 Standard Fans 2 CPU – 7 Standard Fans Optional: High Performance Fans	2 CPU – 7 High Performance Fans
Management	HPE BMC & AMI Firmware	
USB	Front: 1 USB 3.0 Rear: 2 USB 3.0 Internal: 2 USB 3.0	

Core Options

CTO Models with embedded LOM

CTO Server	HPE CL2600 Gen10 8SFF CTO Svr	HPE CL2600 Gen10 Prem 10SFF CTO Svr
SKU Number	P04359-B21	P09678-B21
Processor	Not included as standard- Supports <u>only 1st Generation</u> Intel Xeon processors	
DIMM Slots	24-DIMM slots (12 per CPU)	
Storage Controller	Choice of Intel C621 embedded SW RAID with 8 SATA ports, Intel VROC, or optional PCIe plug-in RAID/HBA controller	
PCIe	2 PCIe slots (1 x16 FH / 1 x8 LP) Optional: 1 x16 FH or LP	2 PCIe slots (1 x16 FH / 1 x8 LP)
Drive Cage - included	8 SFF - SAS/SATA Optional: up to 2 NVMe or 1 Dual (2x) 2280 M.2 cartridges	10 NVMe – 8 SAS/SATA/NVME + 2 NVME Optional: 1 Dual (2x) 2280 M.2 cartridges
Network Controller	Embedded 1Gb Ethernet 4-Port (sideband supported) plus optional PCIe stand up card(s)	
Fans	1 CPU – 5 Standard Fans 2 CPU – 7 Standard Fans Optional: High Performance Fans	2 CPU – 7 High Performance Fans
Management	HPE BMC & AMI Firmware	
USB	Front: 1 USB 3.0 Rear: 2 USB 3.0 Internal: 2 USB 3.0	

Step 2a: Choose Processor Options

Please select a minimum of one or maximum of two –L21 processors below. The Premium 10SFF base server requires two –L21 processors be selected.

NOTE: Mixing of 2 different processor models is not supported.

NOTE: For first processor selection on the 8SFF chassis, will include 5 fans; For second processor selection (if applicable), will add 2 additional fans. For the 8SFF chassis, the high performance fan kit (P10544-B21) is an optional upgrade, but required when selecting the 2NVMe backplane FIO kit (P09679-B21). For the Premium 10SFF chassis, 7 high performance fans come standard.

NOTE: Processors with 130W or higher will ship with a high-performance heatsink plus SKUs 6128, 5122 as noted below. All other processors will ship with the Standard heat sink.

NOTE: When 2nd Generation Intel Xeon Scalable Processor is selected, then only DDR4-2933 Memory Kit can be selected; When 1st Generation Intel Xeon Scalable Processor is selected, then only DDR4-2666 Memory Kit can be selected

Note: Only 1st Generation Intel Xeon Scalable Processors can be selected with: P04359-B21 and P09678-B21 (CTO chassis with embedded LOM)

Core Options

Processor Option Kits	Required Processor
2nd Generation Intel Xeon-Platinum	
HPE CL2600 Gen10 Intel Xeon-Platinum 8280M (2.7GHz/28-core/205W) FIO Processor Kit	P12097-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8276M (2.2GHz/28-core/165W) FIO Processor Kit	P12094-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8276 (2.2GHz/28-core/165W) FIO Processor Kit	P12093-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8270 (2.7GHz/26-core/205W) FIO Processor Kit	P12092-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8268 (2.9GHz/24-core/205W) FIO Processor Kit	P12091-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8260M (2.4GHz/24-core/165W) FIO Processor Kit	P12089-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Platinum 8260 (2.4GHz/24-core/165W) FIO Processor Kit	P12087-L21
NOTE: Ships with High Performance Heatsink.	
2nd Generation Intel Xeon-Gold	
HPE CL2600 Gen10 Intel Xeon-Gold 6254 (3.1GHz/18-core/200W) FIO Processor Kit	P12086-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Gold 6248 (2.5GHz/20-core/150W) FIO Processor Kit	P12084-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Gold 6242 (2.8GHz/16-core/150W) FIO Processor Kit	P12082-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Gold 6240 (2.6GHz/18-core/150W) FIO Processor Kit	P12080-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL2600 Gen10 Intel Xeon-Gold 6230 (2.1GHz/20-core/125W) FIO Processor Kit	P12078-L21
HPE CL2600 Gen10 Intel Xeon-Gold 5220 (2.2GHz/18-core/125W) FIO Processor Kit	P12077-L21
HPE CL2600 Gen10 Intel Xeon-Gold 5218 (2.3GHz/16-core/125W) FIO Processor Kit	P12075-L21
HPE CL2600 Gen10 Intel Xeon-Gold 5217 (3.0GHz/8-core/115W) FIO Processor Kit	P12073-L21
HPE CL2600 Gen10 Intel Xeon-Gold 5215M (2.5GHz/10-core/85W) FIO Processor Kit	P12072-L21
HPE CL2600 Gen10 Intel Xeon-Gold 5215 (2.5GHz/10-core/85W) FIO Processor Kit	P12071-L21
1st Generation Intel Xeon-Gold	
HPE CL Intel Xeon-Gold 6152 (2.1GHz/22-core/140W) FIO Processor Kit	P01905-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6148 (2.4GHz/20-core/150W) FIO Processor Kit	P01747-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6144 (3.5GHz/8-core/150W) FIO Processor Kit	P01743-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6142 (2.6GHz/16-core/150W) FIO Processor Kit	P01746-L21
NOTE: Ships with High Performance Heatsink.	

Core Options

HPE CL Intel Xeon-Gold 6140 (2.3GHz/18-core/140W) FIO Processor Kit	P01904-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6138 (2.0GHz/20-core/125W) FIO Processor Kit	P01903-L21
HPE CL Intel Xeon-Gold 6136 (3.0GHz/12-core/150W) FIO Processor Kit	P01745-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6134 (3.2GHz/8-core/130W) FIO Processor Kit	P01906-L21
NOTE: Ships with High Performance Heatsink.	
HPE CL Intel Xeon-Gold 6130 (2.1GHz/16-core/125W) FIO Processor Kit	P01902-L21
HPE CL Intel Xeon-Gold 6128 (3.4GHz/6-core/115W) FIO Processor Kit	P01742-L21
NOTE: Ships with High Performance Heatsink	
HPE CL Intel Xeon-Gold 6126 (2.6GHz/12-core/125W) FIO Processor Kit	P01744-L21
HPE CL Intel Xeon-Gold 5122 (3.6GHz/4-core/105W) FIO Processor Kit	P01741-L21
NOTE: Ships with High Performance Heatsink	
HPE CL Intel Xeon-Gold 5120 (2.2GHz/14-core/105W) FIO Processor Kit	P01901-L21
HPE CL Intel Xeon-Gold 5118 (2.3GHz/12-core/105W) FIO Processor Kit	P01900-L21
HPE CL Intel Xeon-Gold 5115 (2.4GHz/10-core/105W) FIO Processor Kit	P01795-L21
2nd Generation Intel Xeon-Silver	
HPE CL2600 Gen10 Intel Xeon-Silver 4216 (2.1GHz/16-core/100W) FIO Processor Kit	P12070-L21
HPE CL2600 Gen10 Intel Xeon-Silver 4215 (2.5GHz/8-core/85W) FIO Processor Kit	P12069-L21
HPE CL2600 Gen10 Intel Xeon-Silver 4214 (2.2GHz/12-core/85W) FIO Processor Kit	P12067-L21
HPE CL2600 Gen10 Intel Xeon-Silver 4210 (2.2GHz/10-core/85W) FIO Processor Kit	P12066-L21
HPE CL2600 Gen10 Intel Xeon-Silver 4208 (2.1GHz/8-core/85W) FIO Processor Kit	P12064-L21
1st Generation Intel Xeon-Silver	
HPE CL Intel Xeon-Silver 4114 (2.2GHz/10-core/85W) FIO Processor Kit	P01898-L21
HPE CL Intel Xeon-Silver 4112 (2.6GHz/4-core/85W) FIO Processor Kit	P01794-L21
HPE CL Intel Xeon-Silver 4110 (2.1GHz/8-core/85W) FIO Processor Kit	P01897-L21
HPE CL Intel Xeon-Silver 4108 (1.8GHz/8-core/85W) FIO Processor Kit	P01896-L21
HPE CL Intel Xeon-Silver 4116 (2.1GHz/12-core/85W) FIO Processor Kit	P01899-L21
1st Generation Intel Xeon-Bronze	
HPE CL Intel Xeon-Bronze 3106 (1.7GHz/8-core/85W) FIO Processor Kit	P01895-L21
HPE CL Intel Xeon-Bronze 3104 (1.7GHz/6-core/85W) FIO Processor Kit	P01894-L21

Step 2b: Choose Memory Options

Please select one or more memory from below.

NOTE: Maximum memory capacity and speed per processor is dependent on processor model selection or limitation.

NOTE: DDR4-2933 Memory Kits are only supported with 2nd Generation Intel Xeon Scalable Series Processors and DDR4-2666 Memory Kits are only supported with 1st Generation Intel Xeon Scalable Series Processors.

Registered DIMMs (RDIMMs) for 2nd Generation Intel Xeon Scalable Series

HPE CL 64GB (1x64GB) Dual Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	P14492-B21
HPE CL 32GB (1x32GB) Dual Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	P10660-B21
HPE CL 16GB (1x16GB) Dual Rank x8 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	P14119-B21
HPE CL 16GB (1x16GB) Single Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	P14117-B21

Core Options

Registered DIMMs (RDIMMs) for 1st Generation Intel Xeon Scalable Series

HPE CL 32GB (1x32GB) Dual Rank x4 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit	880841-B21
HPE CL 16GB (1x16GB) Dual Rank x8 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit	P07029-B21
HPE CL 16GB (1x16GB) Single Rank x8 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit	881067-B21

Load Reduced DIMMs (LRDIMMs) for 2nd Generation Intel Xeon Scalable Series

HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2933 CAS-21-21-21 Load Reduced Memory FIO Kit	P14121-B21
--	------------

Load Reduced DIMMs (LRDIMMs) for 1st Generation Intel Xeon Scalable Series

HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2666 CAS-19-19-19 Load Reduced Memory FIO Kit	880842-B21
--	------------

Step 2c: Choose Power Supplies

Please select one or two power supplies from below.

NOTE: Mixing of 2 different power supplies is not supported

HPE Flex Slot Power Supplies

HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	865408-B21
HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit	865438-B21
HPE 800W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	865414-B21
HPE 800W Flex Slot -48VDC Hot Plug Low Halogen Power Supply Kit	865434-B21
HPE 1600W Flex Slot Platinum Hot Plug Low Halogen Power Supply Kit	830272-B21

NOTE: 1600W Power supplies only support high line voltage (200 VAC to 240 VAC).

HPE 800W Flex Slot Universal Hot Plug Low Halogen Power Supply Kit	865428-B21
--	------------

Step 3: Choose Additional (FIO) Factory Integrated Options

Each of the following may be selected if desired at time of factory integration

HPE Trusted Platform Module 2.0 Gen10 Option	864279-B21
--	------------

NOTE: HPE Trusted Platform Module 2.0 option works with Gen10 servers with UEFI Mode, not Legacy Mode.

NOTE: HPE server systems can have a TPM module installed only once. It cannot be replaced with any other TPM module.

Step 4: Choose Additional Options for Factory Integration from Core and Additional Option sections below

Core Options

HPE Unique Options

Risers

HPE CL2600 Gen10 Low Profile FIO Riser Kit P05476-B21

HPE CL2600 Gen10 SATA M.2 2280 FIO Riser Kit P10572-B21

Riser Information*

Part number	Description	Riser position		Slot Bus width (Gen3 lanes)			NVMe Direct Connect		SATA m.2 2280
		Primary	Secondary	#1	#2	#3	Connectors	Max SSDs	Max drives
n/a	HPE CL2600 Gen10 x16/x8 Primary Riser	D	N	x16	x8	O			
P10572-B21	HPE CL2600 Gen10 x16/x16 SATA M.2 2280 Riser Kit	O	N	x16	x16	O			2
P05476-B21	HPE CL2600 Gen10 x16 Low-Profile Riser Kit	N	O	O	O	x16			
n/a	HPE CL2600 Gen10 x16/x8 1-port 2SFF NVMe Riser ¹	O	N	x16	x8	O	1	2	
n/a	HPE CL2600 Gen10 5-port 10SFF NVMe Riser Kit ²	N	D ²	O	O	O	5	10	

NOTE: D = Default on chassis; O = Optional; N = not supported or slot/connector not present

¹Included on 2SFF NVMe FIO Backplane Kit P09679-B21; only supported on 8SFF chassis P04359-B21

²Standard on Premium 10SFF chassis P09678-B21

Performance Cooling Options

HPE CL2600 Gen10 High Performance FIO Fan Kit P10544-B21

Universal Media Bay Options

HPE CL2600 Gen10 2NVMe FIO Backplane Kit P09679-B21

NOTE: Only supported on 8SFF chassis P04359-B21

Security

HPE Trusted Platform Module 2.0 Gen10 Option 864279-B21

HPE 1U Gen10 Bezel Kit 867998-B21

HPE Bezel Lock Kit 875519-B21

NOTE: HPE Bezel Lock Kit (875519-B21) requires selecting HPE 1U Gen10 Bezel Kit (867998-B21)

Cable Kits

HPE CL2600/2800Gen10 Rear Serial Cbl FIO P07013-B21

Core Options

Hard Disk Drive (HDD) Selection

Enterprise - 12G SAS - SFF – Hard Disk Drives

HPE CL 300GB 12G SAS 15K rpm SFF (2.5in) Seagate Hard Drive	P01660-B21
HPE CL 600GB 12G SAS 10K rpm SFF (2.5in) Enterprise Hard Drive	848513-B21
HPE CL 1.2TB 12G SAS 10K rpm SFF (2.5in) Enterprise Hard Drive	848505-B21
HPE CL 2.4TB 12G SAS 10K rpm SFF (2.5in) Seagate Enterprise Hard Drive	880853-B21

Hard Disk Drive (HDD) Selection- Secure Encrypted Drives (SED)

HPE CL 2.4TB SAS 12G Enterprise 10K SFF (2.5in) Seagate SED FIO HDD	P10335-B21
---	------------

Solid State Drive (SSD) Selection

Mixed Use - 6G SATA - SFF - Solid State Drives

HPE CL 240GB SATA 6G Mixed Use SFF (2.5in) Micron 5200 FIO SSD	P08787-B21
HPE CL 960GB SATA 6G Mixed Use SFF (2.5in) Intel S4610 FIO SSD	P08811-B21
HPE CL 1.92TB SATA 6G Mixed Use SFF (2.5in) Intel S4610 FIO SSD	P08814-B21
HPE CL 3.84TB SATA 6G Mixed Use SFF (2.5in) Intel S4610 FIO SSD	P04597-B21

Read Intensive - 6G SATA - SFF - Solid State Drives

HPE CL 240GB SATA 6G Read Intensive SFF (2.5in) Intel S4510 FIO SSD	P08796-B21
HPE CL 480GB SATA 6G Read Intensive SFF (2.5in) Intel S4510 FIO SSD	P08799-B21
HPE CL 960GB SATA 6G Read Intensive SFF (2.5in) Intel S4510 FIO SSD	P08802-B21
HPE CL 1.92TB SATA 6G Read Intensive SFF (2.5in) Intel S4510 FIO SSD	P08805-B21
HPE CL 1.92TB SATA 6G Read Intensive SFF (2.5in) Samsung PM883 FIO SSD	P01680-B21
HPE CL 3.84TB SATA 6G Read Intensive SFF (2.5in) Samsung PM883 FIO SSD	879720-B21
HPE CL 3.84TB SATA 6G Read Intensive SFF (2.5in) Intel S4510 FIO SSD	P08808-B21
HPE CL 7.68TB SATA 6G Read Intensive SFF (2.5in) Samsung PM883 FIO SSD	P01684-B21

Read Intensive – PCIe/NVMe - SFF - Solid State Drives

HPE CL 960GB NVMe x4 Lanes Read Intensive SFF (2.5in) Samsung PM983 FIO SSD	P10536-B21
HPE CL 1.92TB NVMe x4 Lanes Read Intensive SFF (2.5in) Samsung PM983 FIO SSD	P06710-B21
HPE CL 2TB NVMe x4 Lanes Read Intensive SFF (2.5in) Intel P4510 FIO SSD	P04600-B21
HPE CL 2TB NVMe Read Intensive SFF (2.5in) x 7mm Intel P4511 Solid State Drive FIO Kit	P04602-B21
HPE CL 3.2TB NVMe x4 Lanes Mixed Use SFF (2.5in) Intel P4610 FIO SSD	P06660-B21
HPE CL 3.84TB NVMe x4 Lanes Read Intensive SFF (2.5in) Samsung PM983 FIO SSD	P06713-B21
HPE CL 4TB NVMe x4 Lanes Read Intensive SFF (2.5in) Intel P4510 FIO SSD	P06663-B21
HPE CL 8TB NVMe x4 Lanes Read Intensive SFF (2.5in) Intel P4510 FIO SSD	P04599-B21

Mixed Use – PCIe/NVMe - SFF - Solid State Drives

HPE CL 3.2TB NVMe x4 Lanes Mixed Use SFF (2.5in) Intel P4610 FIO SSD	P06660-B21
HPE CL 3.2TB NVMe x4 Lanes Mixed Use SFF (2.5in) Samsung PM1725b FIO SSD	P06726-B21

Write Intensive- PCIe/NVMe - SFF - Solid State Drives

HPE CL 375GB NVMe x4 Lanes Write Intensive SFF (2.5in) Intel P4800X FIO SSD	P10984-B21
---	------------

Mixed Use – PCIe/NVMe – Add-in-card - Solid State Drives

HPE CL 1.6TB NVMe x4 Lanes Mixed Use HHHHL Samsung PM1725b FIO SSD	P01676-B21
--	------------

Mixed Use - 6G SATA - M.2 - Solid State Drives

HPE CL 240GB SATA 6G Mixed Use M.2 - UFF to SFF Micron 5100 FIO SSD	P08784-B21
---	------------

Core Options

Solid State Drive (SSD) Selection- Secure Encrypted Drives (SED)

Mixed Use - 6G SATA - SFF - Solid State Drives

HPE CL 960GB SATA 6G Mixed Use SFF (2.5in) Micron 5200 MAX FIO SSD P11734-B21

Read Intensive - 6G SATA - SFF - Solid State Drives

HPE CL 480GB SATA 6G Read Intensive SFF (2.5in) Micron 5200 ECO FIO SSD P11737-B21

HPE Networking

100 Gigabit Ethernet adapters

HPE CL Ethernet 100Gb 1-port QSFP28 Mellanox ConnectX-5 EN PCIe3 FIO Card 880150-B21

NOTE Mellanox ethernet adapters require Legacy BIOS Mode Setting (P11219-B22)

50 Gigabit Ethernet adapters

HPE CL Ethernet 50Gb 2-port SFP28 Mellanox ConnectX-5 Single Host PCIe 3.0 Card P01671-B21

NOTE: Mellanox ethernet adapters require Legacy BIOS Mode Setting (P11219-B22)

25 Gigabit Ethernet adapters

HPE CL Ethernet 25Gb 1-port SFP28 Intel XXV710 PCIe 3.0 Card P01667-B21

HPE CL Ethernet 25Gb 2-port SFP28 Q41212 PCIe 3.0 Card P01669-B21

HPE CL Ethernet 25Gb 2-port SFP+ Mellanox ConnectX-4 PCIe 3.0 Card P01670-B21

NOTE: Mellanox ethernet adapters require Legacy BIOS Mode Setting (P11219-B22)

10 Gigabit Ethernet adapters

HPE CL Ethernet 10Gb 4-port Intel X710-T4 PCIe3 FIO Adapter P10662-B21

HPE CL Ethernet 10Gb 4-port Intel X710-DA4 PCIe3 FIO Adapter P10664-B21

HPE CL Ethernet 10GBASE-T 2-port Q41112 PCIe FIO Adapter P08550-B21

HPE CL Ethernet 10GBASE-T 2-port Intel X550 PCIe 3.0 Card P01665-B21

HPE CL Ethernet 10Gb 2-port SFP+ Intel X710 PCIe 3.0 Card P01666-B21

HPE CL Ethernet 10Gb 2-port SFP+ QLogic Q41132 PCIe 3.0 Card P01668-B21

Additional Options

HPE Storage Controllers

Software RAID

HPE CL2600/2800 Gen10 Intel VROC FIO Enablement Kit P12568-B22

RAID Array Controllers

HPE CL Broadcom 9460-8i 2G with CVPM05 Tri-Mode RAID Controller P01726-B21

NOTE: This option does not support HW RAID with SFF NVME SSD

HPE CL 9361-8i SAS3108 1GB 8-port SAS Broadcom FIO MegaRAID Adapter 859912-B21

NOTE: A supercapacitor/battery clip comes standard with the 8SFF Chassis and the Premium 10SFF chassis to avoid blocking PCIe expansion slots

HBA Controllers

HPE CL 9300-8i SAS3008 8-port SAS Broadcom FIO Host Bus Adapter 859916-B21

Cache Module/SafeStore Options

HPE CL LSI CVM02 CacheVault Module for 9300 RAID Adapter 860048-B21

HPE CL SAS MegaRAID SafeStore Software License and Physical Key FIO Kit P10017-B21

HPE Rack Options

Rail Kits

HPE 1U Gen10 SFF Easy Install Rail Kit 874543-B21

HPE 1U Gen10 SFF Ball Bearing Rail Kit 872252-B21

NOTE: HPE rail kits contain telescoping rails which allow for in-rack serviceability.

NOTE: Hewlett Packard Enterprise recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.

HPE 1U Cable Management Arm for Rail Kit 734811-B21

NOTE: Supports both the Easy Install and Ball Bearing Rail Kits.

HPE Racks

Please see the [HPE Advanced Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

Please see the [HPE Enterprise Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

Please see the [HPE Standard Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

HPE Power Distribution Units (PDUs)

Please see the [HPE Basic Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.

Please see the [HPE Metered Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.

Please see the [HPE Intelligent Power Distribution Unit \(PDU\) QuickSpecs](#) for information on these products and their specifications.

Please see the [HPE Metered and Switched Power Distribution Units \(PDU\) QuickSpecs](#) for information on these products and their specifications.

HPE Uninterruptible Power Systems (UPS)

To learn more, please visit the [HPE Uninterruptible Power Systems \(UPS\) web page](#).

Please see the [HPE DirectFlow Three Phase Uninterruptible Power System QuickSpecs](#) for information on these products and their specifications.

Please see the [HPE Line Interactive Single Phase UPS QuickSpecs](#) for information on these products and their specifications.

Additional Options

HPE Cloudline Support Services

HPE 3 year Cloudline Parts plus Remote Technical with DMR CL2600 Gen10 Supp HF8N4E

HPE 3 year Cloudline Parts plus Remote Technical with CDMR CL2600 Gen10 Supp HF8N5E

HPE Foundation Care 3 Years Next Business Day Services

HPE 3 Year Foundation Care Next Business Day Cloudline 2600 Gen10 Service HF8N6E

HPE 3 Year Foundation Care Next Business Day with DMR Cloudline 2600 Gen10 Service HF8N7E

HPE 3 Year Foundation Care Next Business Day with CDMR Cloudline 2600 Gen10 Service HF8N8E

HPE Foundation Care 4 Years Next Business Day Services

HPE 4 Year Foundation Care Next Business Day Cloudline 2600 Gen10 Service HF8N9E

HPE 4 Year Foundation Care Next Business Day with DMR Cloudline 2600 Gen10 Service HF8P0E

HPE 4 Year Foundation Care Next Business Day with CDMR Cloudline 2600 Gen10 Service HF8P1E

HPE Foundation Care 5 Years Next Business Day Services

HPE 5 Year Foundation Care Next Business Day Cloudline 2600 Gen10 Service HF8P2E


HPE 5 Year Foundation Care Next Business Day with DMR Cloudline 2600 Gen10 Service HF8P3E

HPE 5 Year Foundation Care Next Business Day with CDMR Cloudline 2600 Gen10 Service HF8P4E

NOTE: For a full listing of support services available for this server, please visit <https://ssc.hpe.com/>

Memory

Memory Population guidelines



2 Slots per Channel

1 DIMM							8					
2 DIMMs							8		10			
3 DIMMs							8		10		12	
4 DIMMs			3		5		8		10			
5 DIMMs			3		5		8		10		12	
6 DIMMs	1		3		5		8		10		12	
7 DIMMs	1		3		5		7	8	10		12	
8 DIMMs			3	4	5	6	7	8	9	10		
9 DIMMs	1		3		5		7	8	9	10	11	12
10 DIMMs	1		3	4	5	6	7	8	9	10		12
11 DIMMs	1		3	4	5	6	7	8	9	10	11	12
12 DIMMs	1	2	3	4	5	6	7	8	9	10	11	12

DIMM Population Order

General Memory Population Rules and Guidelines:

- Install DIMMs only if the corresponding processor is installed.
- If only one processor is installed in a two-processor system, only half of the DIMM slots are available.
- To maximize performance, it is recommended to balance the total memory capacity between all installed processors.
- When two processors are installed, balance the DIMMs across the two processors.
- White DIMM slots denote the first slot to be populated in a channel.
- Mixing of DIMM types (RDIMM, and LRDIMM) is not supported.
- The maximum memory speed is a function of the memory type, memory configuration, and processor model.
- The maximum memory capacity is a function of the number of DIMM slots on the platform, the largest DIMM capacity qualified on the platform, the number and model of installed processors qualified on the platform.

Memory

2nd Generation Memory				
DIMM Type	Register DIMM (RDIMM)			
HPE SKU P/N	P14117-B21	P14119-B21	P10660-B21	P14492-B21
SKU Description	HPE CL 16GB (1x16GB) Single Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	HPE CL 16GB (1x16GB) Dual Rank x8 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	HPE CL 32GB (1x32GB) Dual Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit	HPE CL 64GB (1x64GB) Dual Rank x4 DDR4-2933 CAS-21-21-21 Registered Memory FIO Kit
DIMM Rank	Single Rank (1R)	Dual Rank (2R)	Dual Rank (2R)	Dual Rank (2R)
DIMM Capacity	16GB	16GB	32GB	64GB
DRAM Width [bit]	x4	x8	x4	X4
CAS Latency	21-21-21	21-21-21	21-21-21	21-21-21
DIMM Native Speed (MT/s)	2933 MT/s	2933 MT/s	2933 MT/s	2933 MT/s
Intel Xeon®Platinum/Gold 82xx/62xx Processors Officially Supported Memory Speed (MT/s)				
1 DIMM Per Channel	2933 MT/s	2933 MT/s	2933 MT/s	2933 MT/s
2 DIMM Per Channel	2666 MT/s	2666 MT/s	2666 MT/s	2666 MT/s
Intel Xeon®Gold 52xx Processors Officially Supported Memory Speed (MT/s)				
1 DIMM Per Channel	2666 MT/s	2666 MT/s	2666 MT/s	2666 MT/s
2 DIMM Per Channel	2666 MT/s	2666 MT/s	2666 MT/s	2666 MT/s
Intel Xeon®Silver 42xx Processors Officially Supported Memory Speed (MT/s)				
1 DIMM Per Channel	2400 MT/s	2400 MT/s	2400 MT/s	2400 MT/s
2 DIMM Per Channel	2400 MT/s	2400 MT/s	2400 MT/s	2400 MT/s
Intel Xeon®Bronze 32xx Processors Officially Supported Memory Speed (MT/s)				
1 DIMM Per Channel	2133 MT/s	2133 MT/s	2133 MT/s	2133 MT/s
2 DIMM Per Channel	2133 MT/s	2133 MT/s	2133 MT/s	2133 MT/s
NOTE: The maximum memory speed is a function of the memory type, memory configuration, and processor model.				

1st Generation Memory			
DIMM Type	Register DIMM (RDIMM)		
HPE SKU P/N	881067-B21	P07029-B21	880841-B21
SKU Description	HPE CL 16GB (1x16GB) Single Rank x8 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit	HPE CL 16GB (1x16GB) Dual Rank x8 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit	HPE CL 32GB (1x32GB) Dual Rank x4 DDR4-2666 CAS-19-19-19 Registered Memory FIO Kit
DIMM Rank	Single Rank (1R)	Dual Rank (2R)	Dual Rank (2R)
DIMM Capacity	16GB	16GB	32GB
DRAM Width [bit]	x4	x8	x4
CAS Latency	19-19-19	19-19-19	19-19-19
DIMM Native Speed (MT/s)	2666 MT/s	2666 MT/s	2666 MT/s
Intel Xeon®Platinum/Gold 81xx/61xx Processors Officially Supported Memory Speed (MT/s)			
1 DIMM Per Channel	2666 MT/s	2666 MT/s	2666 MT/s
2 DIMM Per Channel	2666 MT/s	2666 MT/s	2666 MT/s
Intel Xeon®Gold/Silver 51xx/41xx Processors Officially Supported Memory Speed (MT/s)			
1 DIMM Per Channel	2400 MT/s	2400 MT/s	2400 MT/s
2 DIMM Per Channel	2400 MT/s	2400 MT/s	2400 MT/s
Intel Xeon®Bronze 31xx Processors Officially Supported Memory Speed (MT/s)			
1 DIMM Per Channel	2133 MT/s	2133 MT/s	2133 MT/s
2 DIMM Per Channel	2133 MT/s	2133 MT/s	2133 MT/s
NOTE: The maximum memory speed is a function of the memory type, memory configuration, and processor model.			

Memory

2nd Generation Memory	
DIMM Type	Load Reduced (LRDIMM)
HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2933 CAS-21-21-21 Load Reduced Memory FIO Kit SKU Description	P14121-B21 HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2933 CAS-21-21-21 Load Reduced Memory FIO Kit
DIMM Rank	Quad Rank (4R)
DIMM Capacity	64GB
DRAM Width [bit]	x4
CAS Latency	21-21-21
DIMM Native Speed (MT/s)	2933 MT/s
Intel Xeon® Platinum/Gold 82xx/62xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2933 MT/s
2 DIMM Per Channel	2666 MT/s
Intel Xeon® Gold/Silver 52xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2666 MT/s
2 DIMM Per Channel	2666 MT/s
Intel Xeon® Gold/Silver 42xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2400 MT/s
2 DIMM Per Channel	2400 MT/s
Intel Xeon® Bronze 32xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2133 MT/s
2 DIMM Per Channel	2133 MT/s

NOTE: The maximum memory speed is a function of the memory type, memory configuration, and processor model.

DDR4 memory options part number decoder

NOTE: Capacity references are rounded to the common gigabyte (GB) values.

- 16GB = 16,384 MB
- 32GB = 32,768 MB
- 64GB = 65,536 MB

Memory

1st Generation Memory	
DIMM Type	Load Reduced (LRDIMM)
HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2666 CAS-19-19-19 Load Reduced Memory FIO Kit	880842-B21
SKU Description	HPE CL 64GB (1x64GB) Quad Rank x4 DDR4-2666 CAS-19-19-19 Load Reduced Memory FIO Kit
DIMM Rank	Quad Rank (4R)
DIMM Capacity	64GB
DRAM Width [bit]	x4
CAS Latency	19-19-19
DIMM Native Speed (MT/s)	2666 MT/s
Intel Xeon® Platinum/Gold 81xx/61xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2666 MT/s
2 DIMM Per Channel	2666 MT/s
Intel Xeon® Gold/Silver 51xx/41xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2400 MT/s
2 DIMM Per Channel	2400 MT/s
Intel Xeon® Bronze 31xx Processors Officially Supported Memory Speed (MT/s)	
1 DIMM Per Channel	2133 MT/s
2 DIMM Per Channel	2133 MT/s

NOTE: The maximum memory speed is a function of the memory type, memory configuration, and processor model.

DDR4 memory options part number decoder

NOTE: Capacity references are rounded to the common gigabyte (GB) values.

- 16GB = 16,384 MB
- 32GB = 32,768 MB
- 64GB = 65,536 MB

Storage



8SFF Chassis Drive Bay Numbering



8 SFF Chassis + optional 2 NVMe Drive Bay Numbering

NOTE: Bays 0 and 1 (highlighted) ONLY support NVMe Drives. The other bays support a mix of SATA and SAS drives.



Premium 10 SFF Chassis Drive Bay Numbering

NOTE: Bays 8 and 9 ONLY support NVMe Drives. The other bays support a mix of NVMe, SATA, and SAS drives.

Technical Specifications

System Unit

Dimensions (Height x Width x Depth)	4.29 x 43.46 x 70.7 cm 1.69 x 17.11 x 27.83 in	SFF Drives
Weight (approximate)	13.04 kg 28.74 lb 16.27 kg 35.86 lb	SFF minimum: One drive, one processor, one power supply, two heatsinks, one storage controller, and five fans. SFF maximum: 10 drives, two processors, two power supplies, two heatsinks, one storage controller and seven fans.
Input Requirements (per power supply)	Rated Line Voltage	100 to 120 VAC 200 to 240 VAC
BTU Rating	Maximum	For 800W Power Supply: 3207 BTU/hr (at 100 VAC), 3071 BTU/hr (at 200 VAC), 3112 BTU/hr (at 240 VDC) for China Only For 500W Power Supply: 1979 BTU/hr (at 100 VAC), 1911 BTU/hr (at 200 VAC), 1965 BTU/hr (at 240 VDC) for China Only
Power Supply Output (per power supply)	Rated Steady-State Power	For 1600W Power Supply: 1600W (at 240 VAC), 1600W (at 240 VDC) for China only For 800W Power Supply: 800W (at 100 VAC), 800W (at 240 VAC), 800W (at 240 VDC) input for China only For 500W Power Supply: 500W (at 100 VAC), 500W (at 240 VAC), 500W (at 240 VDC) input for China only
	Maximum Peak Power	For 1600W Power Supply: 1600W (at 200 to 240 1VAC), 1600W (at 240 VDC) input for China only
System Inlet Temperature	Standard Operating Support	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 20°C/hr (36°F/hr). The upper limit and rate of change may be limited by the type and number of options installed. System performance during standard operating support may be reduced if operating with a fan fault or above 30°C (86°F). For approved hardware configurations, the supported system inlet range is extended to be: 5° to 10°C (41° to 50°F) and 35° to 40°C (95° to 104°F) at sea level with an altitude derating of 1.0°C per every 175 m (1.8°F per every 574 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hpe.com/servers/ashrae
	Extended Ambient Operating Support	For approved hardware configurations, the supported system inlet range is extended to be: 40° to 45°C (104° to 113°F) at sea level with an altitude derating of 1.0°C per every 125 m (1.8°F per every 410 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hpe.com/servers/ashrae
		System performance may be reduced if operating in the extended ambient operating range or with a fan fault.
Relative Humidity (non-condensing)	Operating	8% to 90% - Relative humidity (Rh), 28°C maximum wet bulb temperature, non-condensing.
	Non-operating	5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.

Technical Specifications

Altitude	Operating	3050 m (10,000 ft). This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
	Non-operating	9144 m (30,000 ft). Maximum allowable altitude change rate is 457 m/min (1500 ft/min).

Acoustic Noise Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109). The listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels. Please have your HPE representative provide information from the HPE EMESC website for further technical details regarding the configurations listed below.

Example Configuration	8SFF Entry-Level Configuration	Premium 10SFF Performance Configuration
Idle		
LWAd	5.1 B	5.2 B
LpAm	35 dBA	36 dBA
Operating		
LWAd	5.3 B	5.9 B
LpAm	36 dBA	45 dBA

NOTE: Acoustics levels presented here are generated by a test configuration only. Acoustics levels will vary depending on system configuration. Values are subject to change without notification and are for reference only.

Emissions Classification (EMC)

To view the regulatory information for your product, view the Safety and Compliance Information for Server, Storage, Power, Networking, and Rack Products, available at the Hewlett Packard Enterprise Support Center:

<http://www.hpe.com/support/Safety-Compliance-EnterpriseProducts>

Environment-friendly Products and Approach - End-of-life Management and Recycling

Hewlett Packard Enterprise offers **end-of-life product return, trade-in, and recycling programs**, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the **Hewlett Packard Enterprise web site**. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
03-Sep-2019	Version 6	Changed	Overview, Standards Features, Core Options and Additional Options sections were updated
01-Jul-2019	Version 5	Changed	Overview, Standard Features, Configuration Information and Memory sections were updated
02-Apr-2019	Version 4	Changed	Addition of network card and removed OBS SKUs
04-Mar-2019	Version 3	Changed	Obsolete SKUs were removed
04-Feb-2019	Version 2	Changed	Addition of NVMe-related content. Overview, Standard Features, Configuration Information, Core Options, Storage and Technical Specification sections were updated
03-Dec-2018	Version 1	New	New QuickSpecs.



Sign up for updates

© Copyright 2019 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

a00056109enw - 16324 - Worldwide - V6 - 03-September-2019

