

Planar PT1945P

19" Touch Screen Monitor

For image-conscious retail, hospitality or healthcare establishments, the Planar® PT1945P 19" monitor is optimized with multi-touch interactivity. With its ultrathin profile enclosure to its sleek, edge-to-edge glass surface, the Planar PT1945P provides the ultimate end-user experience.



SPECIFICATION	DETAIL
Product Name	PT1945P
Planar Part Number	997-7415-00
Viewable Size	19" diagonal (14.81" horizontal x 11.85" vertical)
Touchscreen Type	Projected Capacitive
Number of Touch Points	10
Touchscreen Interface	USB
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	170° horizontal, 160° vertical
Response Time (typ)	5 ms
Brightness (w/touchscreen)	225 cd/m ²
Brightness (w/o touchscreen)	250 cd/m ²
Display Type	Edge-Lit LED LCD
Display Resolution	1280 x 1024
Aspect Ratio	5:4
Tilt Range	-5° to +90°
Palette	16.7 million colors
Pixel Pitch	0.294 mm
Refresh Rate	56 to 75 Hz

Dimensions (W x H x D)	17.0" x 15.4" x 8.6" (431.8 mm x 390.9 mm x219.0 mm)
Display Weight	13.4 lbs (6.1 kg)
Shipping weight	19.4 lbs (8.8 kg)
Video Inputs	Analog
Audio Output	2 speakers, 1W/channel
Compatibility	Windows® 8, 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Apple® Mac OS, Linux, HID Compliant - no drivers needed for basic touchscreen operation
External Connections	D-sub 15-pin, Type B socket USB, audio-in, AC power-in
Power Supply	Internal
Power Requirements	100-240 VAC, 50/60Hz
Power Consumption (max)	17.6W (1.4W standby, 0.8W off)
Operating Temperature	0° to +40° C
VESA Compatible/Location	Built-in 100mm VESA, monitor back
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Multi-language On screen display (OSD), Kensington® Security Slot
Product Approvals	UL/c-UL, FCC-Class B, CE, RoHS II
CI-Black-PN	997-7415-00
In the Box	PT1945P 19" Touchscreen LCD Monitor, Power Cord, VGA Cable, USB Cable (A to B), Audio-in Cable, User's Guide, Quick Start Guide
UPC	8 10689 00024 2