

## 1330 82-Column Flatbed Dot Matrix Printer



Tally Dascom's 1330 flatbed serial dot matrix printer, is a 24-pin, 82-column printer with USB interface as standard. The 1330 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

The 1330 is equipped with a linear encoder sensor to position the print head with high accuracy and intellectually detect and correct any misplaced carriage, which ensures good printing quality and significantly reduces the chances of errors in printing.

### Highlights at a glance

- Advanced 24-pin, flatbed printer
- Up to 450 CPS speed
- Ideal for front and back office application
- Up to 7-ply copy capability
- 9 mil characters long life ribbon
- 8.2 inches print width, supports A3 portrait
- Intelligent print position tracking sensor
- Wide range of optional interfaces
- Large 256 KB buffer size

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1330 is ideal for counter-top printing applications such as cheques, tickets, receipts, forms and multi-part documents.

Using the long life ribbon option, the 1330 requires fewer ribbon changes, less downtime and lower running costs. With print speeds of up to 450 characters per second (cps) and flexible media handling, it keeps transactions smooth and the user happy.

The 1330 is a reliable and easy to use printer, with low running costs and a small footprint.

### Available Configurations:

- 1330 Standard Product
- 1330 Standard Product + optional interface

## 1330

<b>Print Speed</b>	450 cps (Fastest Mode); 300 cps (Draft, 10 CPI), 200 cps (NLQ, 10CPI), 100 cps (LQ, 10 CPI)
<b>Print Method</b>	24-pin impact dot matrix
<b>Resolution</b>	Up to 360 x 360 dpi
<b>Character Pitch</b>	10, 12, 15, 16.6, 17.1, 20, 24 cpi, Proportional Spacing
<b>Line Spacing</b>	1/6 inch, programmable in 1/360 inch increments
<b>Printhead life</b>	400 Million Strokes per pin
<b>Memory Buffer</b>	Up to 256 KB
<b>Standard Connectivity</b>	USB 2.0; Optional: Parallel/Serial/Ethernet/WIFI/Bluetooth
<b>Standard Emulation</b>	Epson (ESC P/2), IBM PPDS
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Orator, Gothic, Script, Souvenir, OCR-A/B Barcodes: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet
<b>Character Sets</b>	58 types supported
<b>Ribbon Life</b>	9 million characters
<b>Standard Paper Handling</b>	Friction and push tractor
<b>Number of Copies</b>	Up to 1 Original + 6 copies
<b>Paper Type</b>	Cut sheet and continuous forms
<b>Paper Weight</b>	52 - 120 gsm
<b>Paper Size</b>	55 - 297 mm
<b>Physical Weigth</b>	4.2 kg
<b>Physical Size</b>	395 x 320 x 205 mm (W x D x H)
<b>Power Voltage &amp; Frequency</b>	AC 100-120 V / 200-240 V; 50-60 Hz
<b>Power Consumption</b>	Average: 34W, Sleep: 1.4W; Energy Star 2.0 compliant
<b>MTBF</b>	12,000 hours
<b>MVBF</b>	24 Mil lines
<b>Drivers</b>	Windows 2000/XP/Vista/7/8/8.1 and Server 2003/2008/2012R2
<b>Utility</b>	Tally Dascom Printer Config Tool
<b>Temperature</b>	5° C to 35° C
<b>Humidity</b>	10% to 95% (non-condensing)
<b>Acoustic</b>	< 57 dB(A) (ISO 7779)
<b>Standard Warranty</b>	One year

### DASCOM AP Pte Ltd

21 Bukit Batok Crescent  
 #29-81 WCEGA Tower  
 Singapore 658065  
 TEL: +65 6760 8833  
 FAX: +65 67601066  
 Email: sales@dascom.com.sg  
 Website: www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 