

DIGITAL CAMERA		IXUS 132
<b>IMAGE SENSOR</b>		
Type	Effective Pixels	1/2.3 type CCD Approx. 16.0M
	Colour Filter Type	Primary Colour
<b>IMAGE PROCESSOR</b>		
	Type	DIGIC 4 with iSAPS technology
<b>LENS</b>		
	Focal Length	5.0 – 40.0 mm (35 mm equivalent: 28 – 224 mm)
	Zoom	Optical 8x ZoomPlus 16x Digital Approx. 4x. (with Digital Tele-Converter Approx. 1.6x or 2.0x and Safety Zoom [1]). Combined Approx. 32x [1]
	Maximum f/number	f/3.2 – f/6.9
	Construction	8 elements in 7 groups (1 double-sided aspherical lens)
	Image Stabilisation	Yes (lens shift-type), 3-stop (Canon standard). Intelligent IS
<b>FOCUSING</b>		
	Type	TTL
	AF System/ Points	AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)
	AF Modes	Single, Continuous (Auto mode only), Servo AF/AE[10], Tracking AF[10]
	AF Point Selection	Size (Normal, Small)
	AF Lock	On/Off Selectable
	AF Assist Beam	Yes
	Closest Focusing Distance	1 cm (W) from front of lens in macro
<b>EXPOSURE CONTROL</b>		
	Metering modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre)
	AE Lock	On/Off Selectable
	Exposure Compensation	+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction
	ISO sensitivity [3]	AUTO, 100, 200, 400, 800, 1600
<b>SHUTTER</b>		
	Speed	1 – 1/2000 sec. (factory default) 15 – 1/2000 sec. (total range – varies by shooting mode)
<b>WHITE BALANCE</b>		
	Type	TTL
	Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
<b>LCD MONITOR</b>		
	Monitor	6.8 cm (2.7") TFT, Approx. 230,000 dots
	Coverage	Approx. 100%
	Brightness	Adjustable to one of five levels. Quick-bright LCD
<b>FLASH</b>		
	Modes	Auto, Manual Flash On / Off, Slow Synchro
	Slow Sync Speed	Yes. Fastest speed 1/2000 sec.
	Red-Eye Reduction	Yes
	Flash Exposure Compensation	Face Detection FE, Smart Flash Exposure
	Flash Exposure Lock	Yes
	Built-in Flash Range	50cm – 3.0 m (W) / 1.3 – 1.5 m (T)
	External Flash	Canon High Power Flash HF-DC1 Canon High Power Flash HF-DC2

SHOOTING		
Modes	Smart Auto (32 scenes detected), P, Portrait, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), Low Light (4.0 MP), Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Color Accent, Color Swap, Snow, Fireworks, Long Shutter, Stitch Assist	
Modes in Movie	Smart Auto (21 scenes detected), P, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Color Accent, Color Swap, Snow, Fireworks	
Drive modes	Single, Continuous, Self-Timer	
Continuous Shooting	Approx. 0.8 shots/sec.[6] (until memory card becomes full) [7]	
RECORDING PIXELS / COMPRESSION		
Image Size	4:3 - (L) 4608 x 3456, (M1) 3264 x 2448, (M2) 1600 x 1200, (S) 640 x 480 16:9 - (L) 4608 x 2592, (M1) 3264 x 1832, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 4608 x 3072, (M1) 3264 x 2176, (M2) 1600 x 1064, (S) 640 x 424 1:1 - (L) 3456 x 3456, (M1) 2448 x 2448, (M2) 1200 x 1200, (S) 480 x 480	
Compression Movies	Resize in playback (M2, S, XS) *XS is half the length and width of S Superfine, Fine (HD) 1280 x 720, 25 fps, (L) 640 x 480, 30 fps Miniature Effect (HD) 5fps, 2.5fps, 1.25 fps Miniature Effect (L) 6fps, 3fps, 1.5 fps	
Movie Length	(HD) Up to 4 GB or 29 min. 59 sec. [11] (L) up to 4 GB or 1 hour [7]	
FILE TYPES		
Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant	
Movies	MOV [H.264 + Linear PCM (monaural) ]	
DIRECT PRINT		
Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print supported on SELPHY CP & ES printers only)	
PictBridge	Yes	
OTHER FEATURES		
Red-Eye Correction	Yes, during shooting and playback	
Histogram	Yes	
Playback zoom	Approx. 2x – 10x	
Self Timer	Approx. 2 or 10 sec. or Custom	
Menu Languages	English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese	

INTERFACE		
	Computer	Hi-Speed USB (MTP, PTP) dedicated connector (Mini-B compatible)
	Other	A/V output, dedicated connector (PAL/NTSC)
MEMORY CARD		
	Type	SD, SDHC, SDXC
SUPPORTED OPERATING SYSTEM		
	PC & Macintosh	Windows 8 / 7 SP1 / Vista SP2 / XP SP3 Mac OS X v10.6 – 10.8
SOFTWARE		
	Browsing & Printing	ImageBrowser EX
	Other	Camera Window PhotoStitch
POWER SOURCE		
	Batteries	Rechargeable Li-ion Battery NB-11L (battery and charger supplied)
	Battery life	Approx. 200 shots [8] Eco Mode: Approx. 275 shots [8] Approx. 300 min. playback
	A/C Power Supply	Optional, AC Adapter Kit ACK-DC90
ACCESSORIES		
	Cases / Straps	Soft Case DCC-1320
	Flash	Canon High Power Flash HF-DC1 Canon High Power Flash HF-DC2
	Power Supply & Battery Chargers	AC Adapter Kit ACK-DC90
	Other	Canon AV Cable AVC-DC400
PHYSICAL SPECIFICATIONS		
	Operating Environment	0 – 40 °C, 10 – 90% humidity
	Dimensions (WxHxD)	92.9 x 52.4 x 21.6 mm
	Weight	Approx. 133 g (including battery/batteries and memory card)
	Dimensions (WxHxD)	92.9 x 52.4 x 21.6 mm
	Weight	Approx. 134 g (including battery/batteries and memory card)
<p><b>All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated. Subject to change without notice.</b></p> <p><b>[1] Depending on the image size selected.</b></p> <p><b>[3] Standard Output Sensitivity / Recommended Exposure Index. According to ISO 12232:2006 (20th April 2006) which specifies the method for assigning and reporting ISO speed ratings for digital still cameras.</b></p> <p><b>[6] Under conditions where the flash does not fire.</b></p> <p><b>[7] Depending on memory card speed / capacity / compression setting.</b></p> <p><b>[8] Using the batteries and memory card format supplied with the camera (where included), except where indicated.</b></p> <p><b>[10] Some settings limit availability.</b></p> <p><b>[11] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.</b></p>		