



3m DVI to DisplayPort Cable

No.: 41978

Connect a DVI source to a Displayport monitor

Description

- Connects a DVI equipped device to DisplayPort display
- Supports resolutions up to 1920x1200@60Hz
- Supports video mirroring and extended desktop modes
- Integrated USB Power Cable
- 2 year warranty

The Lindy DVI to DisplayPort Cable is ideal for connecting a DVI equipped source such as a PC or laptop to a DisplayPort display. It supports high definition video resolutions up to 1920x1200@60Hz.

The cable can also be used to add another display to extend available desktop workspace and increase productivity. For added convenience, a USB power cable is integrated for connection to a USB port or a power supply to power the converter cable.

Technical details

Connectors

- Connector A: DVI (18+1) Male
- Connector B: DisplayPort Male
- Housing Material:
 - DisplayPort:ABSDVI: PVCUSB:PVC
- Connector Plating: Nickel plated
- Pin Construction: Copper Pin Plating: Nickel plated
- Dimensions (approx.) WxDxH:
- DP: 40x19.6x11.89mm (1.57x0.77x0.47in)
 DVI: 46.3x40x16.5mm (1.82x1.57x0.65in)
 - USB: 35.5x15.2x8mm (1.4x0.6x0.31in)

Cable Construction

- Length: 3m (9.84ft)
- Standard: DP1.1

- Colour: Black, red USB connectorType: RoundJacket Diameter: 6mm

- Jacket Material: PVC
- Conductor Material: TC
- Conductor Gauge: 28AWGShielding: Aluminum BRAID

Specifications

- Supported Bandwidth: 4.95GbpsMaximum Resolution: 1920x1200@60Hz
- Nominal Attenuation:
 - 100MHz~450MHz -2.44--5.099dB
 - 450MHz~8100MHz -5.094~32.906dB

- Minimum Bend Radius: 60mm
 Operating Temperature: 0°C 75°C (32°F 167°F)
 Storage Temperature: -10°C 80°C (14°F 176°F)

Miscellaneous

- Packaging Type: PolybagWarranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, UL & California Proposition 65

Purchasing Information

- No.: 41978
- EAN: 4002888419789

This product is also available in other lengths

- 41975 0.5m (1.64ft)
- 41976 1m (3.28ft)
- 41977 2m (6.56ft)
- 41978 3m (9.84ft)
- 41979 5m (16.40ft)

© LINDY 2021