



Smart WiFi Video Door Phone TX-82

Video Door Phone with WiFi outdoor camera & door opener function



- | | | | |
|--|--|--|---|
| HD Kamera 720P mit CMOS Sensor /
HD Camera 720P with CMOS Sensor | Überwachung von Eingangsbereichen /
Monitoring Entrance Areas | Echtzeit-Videoaufnahme /
Real Time Video Recording | Schnappschussaufnahme /
Snapshot Function |
| Live-Bild via Mobiltelefon /
Live preview via mobile phone | Türöffnung via APP oder RFID/NFC Chip /
Unlock door by APP or RFID/NFC Chip | Sichtwinkel 105° horizontal & 72° vertikal /
Viewing Angle 105° horizontal & 72° vertical | Nachtsichtfunktion /
Night Vision Function |
| Push-Nachricht via APP bei Türklingel &
Sabotagealarm /
Push Notice via APP by door ring &
tamper alarm | Gegensprechanlage /
2-Way-Communication | Speicherung auf MicroSD Karte /
Storage on MicroSD Card | IP65 Strahlwasser- & Staubschutz /
IP65 Waterjet & Dust Protection |



- Video Door Phone with WiFi outdoor camera & door opener function via APP
- Connection via WiFi ~25m or network cable
- 1/4" CMOS image sensor HD with 1 megapixel
- Real Time Video HD 720P via APP
- Video resolution 1280x720
- 2.2mm lens: viewing angle 105° horizontal & 72° vertical
- Night Vision Function ~1-2m with IR-Cut
- Push Notice via APP by door ring & tamper alarm
- Access via free iOS & Android APP
- 2-way communication (built-in microphone & speaker)
- Supports RFID/NFC chip card to open the entrance door
- List of visitors with date & time
- Storage on MicroSD cards up to 32GB or FTP server
- IP65 camera protection class (against waterjet & dust)

Technical Specifications:

- Embedded: Micro-Controller & Linux OS
- H.264 video compression standard
- Audio compression G.711 (microphone, loudspeaker, 2-way-communication)
- Door opening via WEB interface, My Secure Pro APP (iOS & Android), PC Client (Windows), RFID Chip (distance ~1-3cm)
- 10/100Mbps self-adaptive Ethernet & supports IEEE802.11b/g/n wireless protocol
- Network protocol: TCP / IP
- Entrance: 1-ch unlock button, 1-ch door sensor feedback
- Outdoor control: 1 relay for main lock
- Current consumption: work max. 7W / standby max. 1W
- External power supply DC 12V/1A or standard PoE (802.3af)
- Recommended mounting height 1.4-1.6m / Surface mounting
- Operating conditions: -30°C~+60°C, humidity 90% or less
- Weight / Dimensions: 400g / (L) 13.5 x (W) 7.0 x (H) 3.5cm

Compatibility:

Technaxx products FullHD cameras TX-65, TX-66, TX-67, WiFi Alarm System TX-84 and surveillance monitor TX-89

Package Contents:

- Smart WiFi Video Door Phone TX-82
- 3x RFID chip key
- Ethernet (LAN) adapter
- Wiring harness (power/inputs/outputs)
- Wall mounting bracket
- 3 screws & 3 dowels
- 1 hexagon wrench T10
- Waterproof protective cap
- CD
- User Manual



Article-No. 4649

