

## Key Features

Long-lasting laser phosphor light source | 5,200 lumen brightness | Large images in small spaces | Ultra-high contrast ratio | Secure MHL/HDMI port



## Product Description

Featuring 1280x800 WXGA resolution and 5,200 lumens of brightness, the ViewSonic® LS810 Laser Projector is the ideal solution for modern business and education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, this projector delivers long-term, virtually maintenance-free usage for any boardroom or classroom. With its 0.23 ultra-short throw ratio, HV keystoning and 4 corner adjustments, the LS810 makes installation a hassle-free experience. What's more, the ultra-short throw ratio allows you to place the projector just inches away from a wall or screen to give you a huge image for less cost than a comparably sized display. The LS810 also features a hidden PortAll® compartment which accommodates additional accessories such as a wireless streaming device, or PC stick. Powered by SuperColor™ technology for true-to-life images, and SonicExpert® technology for incredibly clear sound, the LS810 delivers an immersive audiovisual performance.



Display:

Throw Distance: 1.21 - 2.62 ft. / 0.37 - 0.8 m Throw Ratio: 0.23 Laser DLP Type: Digital optical focus Lens: Vertical (± 30°) / Horizontal (± 30°) Keystone: 390 Light Source (watt): Light Source Life, Normal (hours): 15000 Light Source Life, Dynamic Eco-20000 Mode (hours): Brightness (ANSI Lumens): 5,200 Color Depth: 30 bits, 1.07B Color (10+10+10) Resolution: 1280 x 800 Dynamic Contrast Ratio: 100000:1 Aspect Ratio: 16:10 **WXGA** Resolution Type: Display Size (in.): 70 - 150 in. / 1.78 - 3.81 m (diagonal) Video Signal: Frequency Horizontal: 15-100KHz Frequency Vertical: 24-120Hz Compatibility: PC Resolution (max): Up to 1920x1080 Up to 1920x1080 (may require MAC Mac® Resolution (max): adapter) Connector: USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), HDMI 1.4(1), HDMI MHL(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Component RCA(1), S-Video In(1), Mini USB(1), Micro USB(1) Audio: Internal Speakers: 8W (x2) Power: Voltage: AC 100-240V (universal), 50-60Hz Consumption (max): 450W <0.5W Stand-by: Controls: Power, keystone/arrow keys, left/blank, Physical Controls: menu/exit, right/panel key lock, mode/enter, auto, source Display, Image, Power Management, Basic, Advanced, System, Information On Screen Display: (See user guide for full OSD functionality) Operating Conditions: 32-104° F (0-40° C) Temperature: Humidity (non-condensing): 0-90% Weight (imperial): Net (lbs): Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (01/20/2017 02:51 PM PST) Gross (lbs): Weight (metric): Net (kg): 10.0

15

Gross (kg):

Dimensions (metric) (WxHxD):

Packaging (mm): 550 x 570 x 310

Physical (mm): 508 x 392 x 165

Dimensions (imperial) (WxHxD):

Packaging (in.): 21.65 x 22.44 x 12.2

Physical (in.): 20.0 x 15.4 x 6.5

## General:

Regulations: Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE, EMC, CB, CCC, RoHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECP

PACKAGE CONTENTS: LS810 projector, power cable, VGA cable, HDMI Cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 3-year limited warranty on parts and labor, 1st year free Express Exchange® service\*\*

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws

UPC: 766907847413

## Accessories:

 ${\tt BCP100, BCP120, HB10B, PGD-350, PJ-WMK-006, VIEWSTICK2, VIEWSYNC3, WPG-300}$