

4-Port Industrial USB 3.0 Hub - Mountable

StarTech ID: ST4300USBM



The ST4300USBM Mountable 4-Port Industrial USB Hub (USB 3.0) offers a simple way to expand a systems current USB capability by providing 4 additional external USB 3.0 ports from a single USB 3.0 host connection, with speeds up to 5 Gbps.



Designed for extreme operating environments, this industrial-grade hub provides reliability under almost any condition and can be securely mounted to most surfaces.

Fully compliant with the SuperSpeed USB 3.0 specification, this industrial USB hub is backward compatible with USB 2.0 and 1.x specifications for simultaneous support of older USB peripherals or even older systems without USB capabilities.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Locations where the hub needs to be securely mounted to a surface, such as a wall or under a desk
- Environments subject to large temperature variances or where physical damage may occur, such as within a factory
- Heavily trafficked areas where there is a concern for the USB cables becoming unplugged

Features

- SuperSpeed USB 3.0 compliant, supporting transfer rates up to 5 Gbps
- Backwards compatible with USB 2.0 and 1.x specifications and devices
- Fully supports USB 3.0 and 2.0/1.x devices simultaneously
- Support for screw-locking USB cables (sold separately)
- Internal dual-regulator power circuits provide up to 900mA of stable and reliable power per port
- Bus power, coaxial power adapter and terminal block style power input options supported
- All metal construction
- Built-in surface mounting brackets
- Plug-and-Play and hot-swap compatible

Technical Specifications

| | |
|-------------------------------|--|
| Warranty | 2 Years |
| Chipset ID | VLI - VL810 |
| Fast-Charge Port(s) | No |
| Interface | USB 3.0 |
| Ports | 4 |
| USB-C Device Port(s) | No |
| USB-C Host Connection | No |
| Maximum Data Transfer Rate | 5 Gbps |
| MTBF | 245,881 Hours |
| External Ports | 1 - Terminal Block (2 Wire) |
| External Ports | 1 - USB Type-B (9 pin) USB 3.0 Female |
| External Ports | 4 - USB Type-A (9 pin) USB 3.0 Female |
| OS Compatibility | OS Independent; No additional drivers or software required |
| System and Cable Requirements | Available USB 3.0 port |
| LED Indicators | 1 - Power (Red) |
| LED Indicators | 4 - USB Device Connection (Green) |
| Center Tip Polarity | Positive |
| Output Current | 3A |
| Output Voltage | 12 DC |
| Power Source | AC Adapter Included |
| Humidity | 5~95% RH |
| Operating Temperature | 0°C to 55°C (32°F to 131°F) |
| Storage Temperature | -20°C to 85°C (-4°F to 185°F) |
| Color | Black |
| Enclosure Type | Steel |
| Form Factor | Industrial |
| Product Height | 0.9 in [23.5 mm] |
| Product Length | 6 in [152 mm] |
| Product Weight | 16.9 oz [480 g] |
| Product Width | 2.3 in [59.6 mm] |
| Shipping (Package) Weight | 47.7 oz [1350 g] |
| Included in Package | 1 - Industrial USB 3.0 Hub |
| Included in Package | 1 - USB 3.0 cable (non-locking) |

| | |
|---------------------|---|
| Included in Package | 1 - Universal Power Adapter (NA/EU/UK) or AU in Australia |
| Included in Package | 1 - Instruction Manual |

Certifications, Reports and Compatibility

