

## DATA SHEET

**B22W-5**

Issue: May 2009

Advanced Display

Business Line 55.9cm/22-inch wide TFT – efficiency for the office

The B22W-5 offers best ergonomics and usability for intensive office use with a 3-in-1 stand.


**Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office**

**Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel and tilt**

**Flexible connectivity with DVI and Analog**

**Ready for remote inventory and administration tasks due to the DisplayView Manageability tools**

**Representative design with smart details like discretely integrated speakers**



## B22W-5

### Special features

DisplayView™ IT Suite

### Ergonomic stand

Stand	3-in-1 Stand
Height adjust range	110 mm
Tilt angle	-5° / +20°
Swivel angle	90°

### Picture performance

Contrast - typical	1000:1
Response time typical	5 ms
Viewing angle (h/v)	170° / 170°
Color performance	16.7 Mio colors (Hi-FRC)
Brightness - typical	300 cd/m2

### Size and resolution

Aspect ratio	16:10
Diagonal Size	55.9 cm / 22-inch
Resolution (native)	1680 x 1050 pixel (recommended)
Resolution (interpolated)	1440 x 900 pixel, 1280 x 1024 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	474 x 296 mm
Pixel Pitch	0.282 mm

### Frequencies

Horizontal	30 - 82 kHz
Vertical	55 - 75 Hz

### Connectivity

Video input	1 x DVI, 1 x D-SUB
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack

### Ease-of-use menu

Languages	Dutch, English, French, German, Italian, Russian, Spanish, Swedish
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	sRGB, 6500K, 9300K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Position, OSD-Timeout, Factory recall

### Power consumption (typical, w/o sound)

Soft switch off	0.7 W
Power save mode	0.7 W
Operating with EPA settings	29 W
Operating maximum brightness	39 W

### Electrical values

Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1

### Compliance

Model	R22
Germany	GS
Europe	CE certification according to EC Directive 2004/108/EEC, Nordic Swan, EN 60950

---

**Compliance**

USA/Canada	FCC Class B, cUL
Australia&New Zealand	C-Tick
Russia	GOST
Saudi Arabia	SASO
Global	TCO'03, ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates/default.aspx">https://sp.ts.fujitsu.com/sites/certificates/default.aspx</a>

---

**Quality and Reliability**

MTBF (demonstrated)	70000 h
---------------------	---------

---

**Dimensions / Weight / Environmental**

Dimension without stand (W x D x H)	511 x 58 x 343
Dimension with stand (W x D x H)	511 x 212 x 402
Weight (packed)	9.8 kg
Weight (unpacked)	7.6 kg
Weight (Monitor only)	4.8 kg
Operating ambient temperature	5 - 35°C

---

**Miscellaneous**

VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared

---

**Package content**

DVI-D Data cable 1.8m, D-SUB Data cable 1.8m , Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet  
Data cables and audio cable detachable on display

---

**Order information**

Order Code	S26361-K1258-V140
EAN-Nr.	4049699076428

---

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

<http://ts.fujitsu.com/aboutus>

Take back and Recycling information:

<http://ts.fujitsu.com/recycling>

---

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions May 2009

Published by  
Fujitsu Technology Solutions  
<http://ts.fujitsu.com>