

Key **Features**

5,200 Lumen Brightness | Vertical/Horizontal Lens
Shift with Centered Lens | Stackable Design |
360-degree Installation

SuperColor: Amazing Color Accuracy



Product **Description**

Bright and versatile for any professional installation, the ViewSonic® Pro9520WL WXGA projector delivers everything you need for big screens in big venues. Delivering 5,200 lumens of advanced high brightness, this projector is ideal for auditoriums, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. Designed for installers, this top-notch performer is also easy to deploy and manage with its wide 1.7x optical zoom adjustment, a centered lens design, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the stackable design of these projectors, light output can be doubled by simply placing one projector on top of the other - perfect for large venues with high ambient light.









Contact Sales

a call: 888.881.8781

email: salesinfo@viewsonic.com

visit: viewsonic.com

RESOLUTION LUMENS THROW RATIO

1 of 2

Display:

DLP Type:

WXGA Resolution Type:

1280 x 800 Resolution:

Brightness (ANSI Lumens): 5,200

Display Size (in.): 20.7 - 351.7 in. / 0.53 - 8.9m

Throw Distance: 3.3 - 55.8 ft / 1 - 17m

Throw Ratio: 1.32 - 2.24:1

Keystone: Vertical (± 30°) / Horizontal (± 25°)

1.7x Manual optical zoom / manual Lens:

optical focus

Light Source (watt): 370

Light Source Life, Normal (hours): 1500

Light Source Life, Dynamic 3500

Eco-Mode (hours):

Color Depth: 30 bits, 1.07B Color (10+10+10)

Aspect Ratio: 16:10

Vertical (-12.7%/+23.7%) / Horizontal Lens Shift:

(+/-10.9%)

Video Signal:

Frequency Horizontal: 15-100kHz Frequency Vertical: 24-120Hz

Compatibility:

PC Resolution (max): Up to 1920x1080

Mac® Resolution (max): Up to 1920x1080

Connector:

USB 2.0 Type A(1), USB 2.0 Type B(1), Ethernet LAN (RJ45)(1), 3.5mm 12V Trigger(1), 3.5mm Audio Out(1), 3.5mm Audio In(3), Control (RS232)(1), HDMI 1.4(1), HDMI MHL(1), DVI-D(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), S-Video In(1), RCA Audio In (L/R)(1), RCA Audio Out(1), 3D VESA(1), Wired Remote In(1), Wired Remote Out(1), 5-BNC(1)

Audio:

Internal Speakers: 7W (x2)

Power:

100~240VAC (Auto Switching), Voltage: 50-60Hz (universal)

480W Consumption (max): Stand-by: <0.5W

Controls:

Physical Controls:

Power, H/V lens shift, focus, zoom, keystone/arrow keys, left/blank,

right/panel key lock, menu/exit,

mode/enter, source

Display, Image, Video, Audio, Basic, On Screen Display:

Advanced

Operating Conditions:

41-104° F (5 - 40° C) Temperature:

Humidity (non-condensing): 10-85%

Additional Hardware:

Kensington Lock Slot:

Weight (imperial):

Net (lbs): 18 26 Gross (lbs): 27.31

Weight (metric):

Net (kg): 8.29

Gross (kg): 12.4

Dimensions (imperial) (WxHxD):

Packaging (in.): 22.7 x 11.5 x 17.2 Physical (in.): 17.5 x 5.8 x 12.8

Dimensions (metric) (WxHxD):

Packaging (mm): 576 x 291 x 436

Physical (mm): 445 x 147.8 x 325.5

General:

Regulations: UL, cUL, FCC, CE, EMC, CB, ROHS, REACH, SVCH, WEEE, ErP, Mexico NOM/ENERGY, PSB, RCM, CCC

PACKAGE CONTENTS: Pro9520WL projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with

User Guide)

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express

Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal

UPC: 766907848014

Accessories:

HB10B, PJ-WMK-006, RLC-106, VIEWSTICK2, VIEWSYNC3

Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (02/21/2018 11:55 AM PST)