



Planar L055-T

Interactive Transparent OLED Display

The Planar® LookThru™ OLED display (LO55-T) is a 55-inch transparent touch-screen display that showcases interactive information on a transparent surface glass without the need for a backlight or enclosure. The Planar LO55-T offers 32 touch points and features Planar® ERO™ (Extended Ruggedness and Optics) using Corning® Gorilla Glass® for enhanced durability and optics. The Planar LO55-T can be in landscape and portrait orientation and can be table mounted, ceiling mounted, or tiled to create eye-catching video wall arrays.



SPECIFICATION	DETAIL
Planar Part Number	997-8244-00
Viewable Size	55" diagonal
Display Active Area	47.6" (W) x 27.4" (H) (1210 mm x 697 mm)
Display Inactive Area (Bottom)	3.9" (97.8 mm)
Product Name	LO55-T
Aspect Ratio	16:9
Display Resolution	1920 x 1080, full HD
Display Type	Active Matrix Organic Light-Emitting Diode (AMOLED)
Surface Treatment	ERO (Extended Ruggedness and Optics) using Corning® Gorilla Glass®
Full Screen White Brightness	150 cd/m ²
Peak White Brightness	500 cd/m ²
Brightness, Uniformity	20%
Transmissivity	45%
Orientation	Landscape, Portrait, Inverted (Ceiling Mount), Tabletop, Tiled
Viewing Angle (typ)	178° H,V
Contrast Ratio (typ)	>100k:1
Response Time (typ)	<1 ms
Palette	1.073 billion colors (10-bit)
Color Gamut	100% of NTSC
Pixels per inch (PPI)	40

Pixel Pitch	0.63 mm
Frame Rate	120Hz
Video Inputs	HDMI x4, DisplayPort x1
External Connections	LAN RJ45, RS232, IR, Keypad, AC Power In
Dimensions (W x H x D)	49.5" x 32.0" x 12.2" (1258.2 mm x 812.5 mm x 309.8 mm)
Bezel Width	1.0" / 1.0" / 1.0" / 1.0" (24.3 mm / 24.3 mm / 24.3 mm / 24.3 mm)
Weight	63.5 lbs (28.8 kg)
Power Requirements	100 to 240VAC
Power Consumption (typ)	140W (<1W standby)
Power Consumption (max)	180W
Service and Support	TBD
Product Approvals	NRTL Listed, FCC-Class A, CE Class A, WEEE, RCM, PSE, REACH, EN60950 and CISPER22/2010, RoHS
VESA Compatible/Location	No
Control and Monitoring	IR, RS-232, USB, LAN, Crestron module
Multi-Source Views	External in first product
Operating Temperature	0° to 40°C
Storage and Transport Temperature	-20° to 65°C
Storage Temperature/Humidity (degrees F/C, relative humidity)	95%
Touch Technology	32 pt IR touch
Lifetime: Typical	30k hours (dynamic image at 25°C)
Options / Features	Fanless, TAA-Compliant, Energy Star, optional tray. Tiling/Video Wall configurations possible through optional external processor. Standard mount.
Warranty	1 year
UPC	8 10689 00306 9

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 2/1/2016

© Copyright 2016 Planar Systems, Inc. All rights reserved