



Make It Yours.

MWE GOLD 750

BE BOLD, POWER WITH GOLD.



FEATURES

80 PLUS Gold Certified: The 80 PLUS Gold certification guarantees a typical efficiency of 90% or higher.

Silent and Durable LDB Fan Bearing: Silencio technology combines sealed LDB bearings with quiet fan blades, delivering a long lifetime of quiet cooling.

Proven Thermal Resistance: Engineered to operate at full performance in temperatures up to 45°C, providing reliability in even the hottest environments.

Flat & Flexible Cables: The MWE Gold series adopts black flat cables for better and more flexible cable management, beneficial for airflow even in smaller cases.

High Efficiency and Stable Output: The MWE Gold's full-bridge design coupled with LLC, Synchronous, and DC to DC topology technologies offers reliable and stable Voltage outputs.

EAN & UPC INFORMATION

Cable type	EAN	UPC
US	4719512069493	884102042003
UK	4719512069509	884102042010
EU	4719512069516	884102042027
ST	4719512069523	884102042034
AU	4719512069530	884102042041
BR	4719512069547	884102042058
KR	4719512069554	884102042065
TW	4719512069561	884102042072
JP	4719512069578	884102042089
WO	4719512069585	884102042096

The MWE Gold offers a highly efficient, affordable power solution. Enjoy reliable 90% efficiency with an 80 PLUS gold certification. Cooler Master's design techniques ensure improved efficiency while maintaining low temperatures and quiet operation. Heat resistant components maintain gold level performance even at increased temperatures up to 45°C. A near quiet Silencio fan with an exclusive LDB bearing reduces noise and lasts longer than standard bearings. Flat and flexible cables improve airflow by reducing cable bulk. Enjoy gold rated power at an affordable price. Be bold, power with gold.

SPECIFICATIONS & PACKAGE INFORMATION

Model	MPY-7501-ACAAG	
Type	ATX 12V V2.31	
PFC	Active PFC (>0.95 typical)	
Input Voltage	100-240V	
Input Current	12-6A	
Input Frequency	50/60Hz	
Dimensions (L x B x H)	140 x 150 x 86mm	
Fan size	120mm	
Fan Bearing	LDB	
Powergood Signal	100 - 500 ms	
Hold Up Time	> 14 ms @ 100% load	
Efficiency	90% Typically	
ErP 2013 Lot 6	Yes	
MTBF	>100,000Hours	
Operating Temperature	0 - 45°C	
Protections	OVP / OPP / UVP / SCP / OTP	
Regulatory	CCC,CE, TUV-SUD, RCM, EAC, cTUVus, FCC, BSMI, CB	
Connectors	MB 24 pin	1x
	CPU 12V 4+4Pin	1x
	SATA	8x
	Peripheral 4 Pin	6x
	FDD Cable 4 Pin	1x
	PCI-e 6+2 Pin	4x

AC INPUT	100-240V~ 12-6A 50/60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5sb
	15A	15A	62.5A	0.3A	2.5A
TOTAL POWER	100W		750W	3.6W	12.5W
	750W				

Net Weight	2.17 kg / 4.78 lb
Gross Weight	2.45 kg / 5.4 lb
Package Dimensions	276 x 194 x 120 mm (10.87 x 7.64 x 4.72")
Carton Dimensions	620 x 290 x 220 mm (24.41 x 11.42 x 8.66")
Unit / Carton	5 pcs
Carton / Pallet	16 cartons

FEATURES



The 80 PLUS Gold certification means the MWE Gold is independently tested with a typical efficiency of 90%.



Silencio technology combines sealed LDB bearings with quiet fan blades delivering a long lifetime of quiet cooling.



The MWE Gold uses flatter, more flexible cables for better cable management even in tight cases.