

42U Server Rack Cabinet - 37 in. Deep Enclosure

Product ID: RK4242BK24

This 42U server rack provides a sleek, secure cabinet for storing standard 19" rack-mount devices such as Dell, HP, and IBM servers, along with telecommunication and A/V equipment. The rack is compatible with EIA-310 compliant equipment and supports a total load capacity of 1500 kg (3307 lb.).

Hassle-free equipment installation

This networking cabinet offers a variety of features that make it easy to install your equipment. With adjustable mounting rails, you can easily change the rail depth from 3 to 37 in. (76.2 mm - 939.8 mm) to support full-depth equipment. The added depth also provides support for additional cable and power management behind your equipment.

The rack features grommet holes on the ceiling and floor panels, which make it easy to run cabling in and out of the cabinet for discreet cable management. The rack also features grounding lugs that enable you to ground your equipment for added protection and tool-less accessory mounting rails, so you can mount 0U vertical cable managers and PDUs.

For hassle-free cable management, the rack includes a 3-meter roll of hook-and-loop cable tie that makes it easy to keep your cables tidy. You can cut the self-gripping fabric to any size, and bind your equipment cables together or to the rack.

To provide hassle-free deployment the rack ships fully assembled.

Keep your equipment secure, cool, and accessible

To keep your rack-mounted equipment secure, this rack features front and rear locking mesh doors that also increase airflow to provide passive cooling.

The rack also has removable side panels with independent quick-release locks that enable you to access your equipment easily, while still keeping it secure. Plus, the side panels are half-height so you can easily remove, handle and install the side panels. For additional access, the rack features a quick release ceiling panel you can remove without interfering with cable runs that are running throughout your rack.





Maximum Maneuverability, with casters included

The cabinet features casters, providing ease of mobility around your office, studio or server room. Plus, the width and height of the rack fit through standard doorways, giving you the freedom to wheel your server rack into different rooms as needed.

The RK4242BK24 is backed by a StarTech.com 5-year warranty and free lifetime technical support.



Data Sheet

Certifications, Reports and Compatibility



Applications

• Deploy in server rooms and data centers to maximize space and keep your equipment secure

Features

- Easily install your equipment, with two 0U tool-less mounting panels included
- Keep your rack-mount equipment secure with lockable doors
- Hassle-free cable management with hook-and-loop cable tie included
- Keep your equipment at an optimal temperature with passive cooling
- Adjustable mounting rails
- 200 x M6 screws and cage nuts included



Data Sheet

Warranty 5 Years **Hardware** Adjustable Mounting Rails Yes Adjustable Size of Built-in Leveling 100 mm [3.94 in] Feet **Back Door Construction** Steel Mesh Back Door Key Lock Yes Back Door Reversible and/or Removable Removable Cable Management Yes Included Casters Fan(s) No **Enclosed Cabinet** Frame Type Front Door Construction Steel Mesh Front Door Key Lock Yes Front Door Reversible and/or Removable Removable **Industry Standards** EIA-310-D Ladder Offset 0 in [0 mm] Ladder Type G-Shape Mounting Holes Square Number and Type of Included Cage 200 - M6 Nuts Rack Type 4-Post Solid Steel Side Panel Construction Side Panel(s) Key Lock Yes Side Panels Reversible and/or Removable Removable Style Floor-Standing U Height 42U **U** Markings Yes Wallmountable No **Performance** Weight Capacity (Rolling) 2320.5 lb [1050 kg]

3315 lb [1500 kg]

Weight Capacity (Stationary)



Data Sheet

Physical Characteristics	Color	Black
	Enclosure Type	Steel
	External Depth	42.1 in [1070 mm]
	External Height	78.5 in [1993 mm]
	External Width	23.6 in [600 mm]
	Height with Casters	78.5 in [1993 mm]
	Internal Depth	39.4 in [1000 mm]
	Internal Height	73.6 in [1870 mm]
	Internal Width	22.4 in [570 mm]
	Maximum Mounting Depth	37 in [94 cm]
	Minimum Mounting Depth	3 in [7.6 cm]
	Product Height	78.5 in [1993 mm]
	Product Length	42.1 in [1070 mm]
	Product Weight	285.1 lb [129 kg]
	Product Width	23.6 in [600 mm]
Packaging Information	Flat Pack (Assembly Required)	No
	Shipping (Package) Weight	311.6 lb [141 kg]

Product appearance and specifications are subject to change without notice.