

# IK-FPMT-15-1500

## 15-Inch High-Bright Touchscreen Display with Rubber Bezel

The IK-FPMT-15-1500 is a high resolution, high bright, daylight-readable 15-inch flat panel display with touchscreen. The IK-FPMT-15-1500 features 1500 nits of brightness and a protective rubber bezel, offering a polished look and added durability in the harshest of environments. It is rated NEMA 4X, making the unit a rugged solution that resists corrosion, dust, water and ice. With a VESA mount pattern, the IK-FPMT-15-1500 is ideal for mobile, public safety, transportation, and utilities applications.



### Technical Specifications

Cable	MONITOR: 15 pin VGA TOUCHSCREEN: USB
Power	12VDC
Compatability	MONITOR: DOS, Windows 95, NT, 98, 2000, WinXP, Win 7 TOUCHSCREEN: DOS, Windows 95, NT, 98, 2000
Display Specifications	PIXEL RATIO: 1024(H) x 768 (V) LIGHT SOURCE: 50,000 hrs CONTRAST RATIO: 500:1
Temperature Range	OPERATING: 14Â°F to +140Â°F (-10Â°C to 65Â°C) STORAGE: -22Â°F to +158Â°F (-30Â°C to 70Â°C) HUMIDITY: 10%-90% (No )
Weight	8.6 lbs +/- 0.10 lbs (3.9 kg +/-0.05 kg)
Warranty	1 Year Limited Warranty
Dimensions	MAXIMUM OUTER DIMENSIONS (W-H-D) 15.07" x 11.33" x 9.02" 382.7mm x 287.7mm x 229.1mm DISPLAY SIZE: 15" viewable diagonal area

### Features and Benefits

- Brightness: High-Bright 1500 nits
- Optional Rubber Bezel
- 15-inch Display
- LED Backlit Display
- Resistive Touchscreen
- VESA Mounting Pattern