
# F90-W13

# 13,000 lumens, WUXGA, DLP laser phosphor projector





The excellent image quality and laser phosphor light source of Barco's F90 projectors enable you to provide stunning experiences while saving both time and money. Designed for installation in everything from high demanding visitor attractions to simulation applications that require 24/7 operation, the reliable F90-W13 is equally suited for events, retail and advertising as well as boardrooms and auditoriums. Thanks to its 3D functionality, the projector is also perfectly fit for theme park dark rides and interactive experiences.

### **Excellent image quality**

Thanks to its advanced optical design, the F90-W13 delivers excellent image quality. What's more, this reliable projector also offers images with constant light output, for long-term, worry-free operation.

#### **Unprecedented business value**

The F90-W13 projector enables you to increase uptime while driving costs down. Through its laser-phosphor light source and advanced cooling design, it provides up to 40,000 hours operating time without need for lamp changes - resulting in considerable cost-savings on maintenance and consumables.

### **Ultimate installation flexibility**

This projector can run in any orientation, giving you more flexibility in projector location and orientation. Thanks to its wide array of high-resolution FLD and FLD+ lenses – from ultra-short throw (0.28:1) to long throw (9.75:1) – each providing a wide lens shift range, the F90-W13 accommodates almost any projector configuration.



<b>Product 9</b>	pecifications	F90-W13
Product 9	pecifications	F90-W1

•		
Projector type	Single chip DLP laser phosphor projector	
Resolution	1,920 x 1,200 (WUXGA)	
Brightness	13,000 center lumens	
Contrast ratio	1800:1 sequential - 50000:1 dynamic contrast	
Brightness uniformity	90%	
Aspect ratio	16:10	
Lens type	FLD	
Optical lens shift	Up to 134% lens shift, depending on lens. Motorized zoom, focus, vertical and horizontal shift, iris* and shutter.	
Color correction	P7 RealColor™	
CLO (constant light output)	Yes*	
Light source	Laser phosphor	
Light source lifetime	20,000 / 60,000 hours, brightness mode dependent	
Sealed DLP™ core	Yes	
Orientation	360° rotation, no restrictions	
3D	Active stereoscopic 3D*	
lmage processing	Embedded warp & blend engine	
Keystone correction	Yes	
Inputs	HDSDI, 2x DP, 2x dual link DVI-D, HDBaseT*, HDMI 2.0*, RJ 45 Ethernet, DMX in/out*, RS232 in, 2x USB, 12v out	
Input resolutions	Up to 2,560 x 1,600 @ 120Hz	
Software tools	Projector Toolset	
Control	IR, RS232, RJ45	
Network connection	10/100 Ethernet, RJ45	
Power requirements	100-240V / 50-60Hz	
Power consumption	1,600 W Max.	
BTU per hour	Max 6,000 BTU/h	
Noise level (typical at 25°C/77°F)	38 dB(A)	
Operating temperature	10 - 40 °C (sea level)	
Storage temperature	-20 to 60 °C	
Operating humidity	20 - 80% RH	
Storage humidity	10 - 90% RH	
Dimensions (WxLxH)	575 x 730 x 295 mm / 22.64 x 28.74 x 11.61 in	
Weight	44.5 kg / 98 lbs	
Standard accessories	Power cord, wireless remote control	
Certifications	CE, FCC Class A and cCSAus	
Warranty	Limited 3 years parts and labor. Extendable up to 5 years	
24-7 documentation	This projector is designed and warranted for heavy duty 24/7 operation. Specific measures and design considerations have been made in order for it to comply with stringent requirements in challenging applications.	
Notes	* SW upgradable. Please contact an authorized Barco representative for details.	



