frontrow

FrontRow ToGo – Take audio anywhere The hardest part is taking it out of the box

Completely portable, FrontRow ToGo incorporates a DuO[™] precision-mounted speaker array for amazingly even coverage of classrooms, cafeteria, meeting spaces — even outdoor events.


Goes from class to playground to assembly

FrontRow ToGo goes anywhere people need to listen. Its powerful rechargeable battery, collapsible stand, and optional carrying case let you talk or play music far from power sources. And with wind-resistant boom microphones and OptiVoice[™] speech-clarifying technology, ToGo is as audible at a soccer meet or bus line as it is in a classroom.

Compatible with personal FM systems

FrontRow ToGo operates on the same radio band used by personal assistive listening systems for students with hearing impairment. Use a single transmitter on up to 16 different channels to communicate with both the ToGo and students' personal devices.





- Simple interface for lesson capture
- Universal MP4/M4A format
- Unlimited length
- Automated naming and saving of recordings

Key Features

- Installation-free and completely portable onboard rechargeable battery lasts hours
- Input jack for music and output jack for recording
- OptiVoice[™] speech clarification
- Powerful two-driver line array for more even audio coverage than flat panels provide
- Great for pass-around at conferences, outdoor events and lectures
- Boom mic for excellent sound quality, indoors and out



Learn more at gofrontrow.com

frontrow

925RS RECEIVER/SPEAKER ARRAY



925T BODY-WORN TRANSMITTER



925H HANDHELD MICROPHONE/TRANSMITTER



925C CHARGING STAND



SPECIFICATIONS

Transmission type: FM (F3E) Receiving frequency: 216.025 - 216.875 MHz Frequency response: 100Hz-9kHz (at rated output) THD: <1.5% (at rated output) @ 1kHz Signal-to-noise: >70db at rated output (system) Maximum addio output power: Maximum 36W RMS @ $4\Omega \times 2$ Power supply: AC 110-220V ~50-60Hz, 1A max Battery: NiMH rechargeable Battery life: 6.5 hours (rechargeable) Recharging time: 8 hours Input: 1 x aux-in, 3.5mm mono Output: 1 x aux-out, 3.5mm mono Size (wxdxh): 183 x 85 x 750 mm / 7.2 x 3.4 x 29.5 in Weight: 5.7kg / 12.5lbs.

USER CONTROLS

- Channel A/B on/off/volume
- Channel A/B channel selector
- aux-in volume
- aux-out volume
- OptiVoice
- main power

SPECIFICATIONS

Carrier frequency range: 216.025 - 216.875 MHz Modulation: FM (F3E) Operating range: > 34m / 110ft RF output: <15mW THD: <0.5% Dynamic range: 100dB Size (wxhxd): 65 x 90 x 25 mm / 2.5 x 3.5 x 1 in Weight: 51g / 1.8oz Controls: on/mute/off/channel selector Input/output: 2.5mm microphone input jack Battery type: 2 AA NiMH rechargeable (1600mA) or 2 AA alkaline disposable Battery life: NiMH rechargeable typically 12 hours, disposable alkaline typically 15 hours Recharging time: 6 hours

SPECIFICATIONS

Carrier frequency range: 216.025 - 216.875 MHz Modulation: FM (F3E) Operating range: > 34m / 110ft RF output: <15mW THD: <0.5% Dynamic range: 100dB Dimensions (dia x h): 54 x 237mm / 2.1 x 9.3 in Weight: 230g / 8.1 oz Controls: on/mute/off/channel selector Battery type: 2 AA NiMH rechargeable (1600mA) or 2 AA alkaline disposable Battery life: 12 hours (rechargeable), 15 hours (alkaline) Recharging time: 6 hours

SPECIFICATIONS

Power supply: AC adaptor (DC 12V / 0.5A) **Recharging time:** NiMH (1600mA), 6 hours **Size (wxhxd):** 230 × 47 × 135 mm / 9 × 1.9 × 5.3 in **Weight:** 360g/12.7oz