



## Specifications

© 2012–2013 Dell Inc.

Trademarks used in this text: Dell™, the DELL logo, and Inspiron™ are trademarks of Dell Inc. Intel®, Pentium®, and Celeron® are registered trademarks and Core™ is a trademark of Intel Corporation in the U.S. and other countries. Bluetooth® is a registered trademark owned by Bluetooth SIG, Inc. and is used by Dell under license.

2013 - 10 Rev. A02

Regulatory model: P28F | Type: P28F001/P28F003

Computer model: Inspiron 3521/3537

## Dimensions

	Non-touch	Touch
Height (Front to back):		
With 4-cell battery	24.85 mm to 27.60 mm (0.98 inch to 1.09 inches)	27.25 mm to 30.15 mm (1.07 inches to 1.19 inches)
With 6-cell battery	24.85 mm to 31.80 mm (0.98 inch to 1.25 inches)	27.25 mm to 34.80 mm (1.07 inches to 1.37 inches)
Width	376 mm (14.80 inches)	
Depth	259 mm (10.20 inches)	
Weight (Maximum):		
With 4-cell battery	2.20 kg (4.85 lb)	2.50 kg (5.51 lb)
With 6-cell battery	2.35 kg (5.18 lb)	2.65 kg (5.84 lb)
<b>NOTE:</b> The weight of your laptop varies depending on the configuration ordered and the manufacturing variability.		

## System Information

Computer model Inspiron 3521/3537

	Inspiron 3521	Inspiron 3537
Processor	<ul style="list-style-type: none"><li>• Intel Celeron Dual Core (2<sup>nd</sup> generation)</li><li>• Intel Pentium Dual Core (2<sup>nd</sup> generation)</li><li>• Intel Core i3 ULV (3<sup>rd</sup> generation)</li><li>• Intel Core i5 ULV (3<sup>rd</sup> generation)</li><li>• Intel Core i7 ULV (3<sup>rd</sup> generation)</li></ul>	<ul style="list-style-type: none"><li>• Intel Celeron Dual Core (4<sup>th</sup> generation)</li><li>• Intel Pentium Dual Core (4<sup>th</sup> generation)</li><li>• Intel Core i3 ULV (4<sup>th</sup> generation)</li><li>• Intel Core i5 ULV (4<sup>th</sup> generation)</li><li>• Intel Core i7 ULV (4<sup>th</sup> generation)</li></ul>
L1 cache	64 KB per core	
L2 cache	256 KB per core	
L3 cache	Up to 4 MB	
System chipset	Intel HM76	Integrated in processor

## Memory

---

Connectors	Two internally-accessible SODIMM connectors
Type:	
Inspiron 3521	Dual-channel DDR3
Inspiron 3537	Dual-channel DDR3L
Speed	Up to 1600 MHz
Configurations supported	2 GB, 4 GB, 6 GB, and 8 GB

## Ports and Connectors

---

### External:

Network	One RJ45 port
USB	<ul style="list-style-type: none"><li>• Two USB 3.0 ports</li><li>• One USB 2.0 port</li><li>• One USB 2.0 port with Windows debugging</li></ul>
HDMI port	One HDMI port
Audio	One headphone and microphone combo (headset) port

### Internal:

Mini-card	One full mini-card slot for Wi-Fi and Bluetooth combo card
-----------	--

## Communications

---

Network adapter	10/100 Mbps Ethernet LAN on Motherboard (LOM)
Wireless	<ul style="list-style-type: none"><li>• Wi-Fi 802.11 b/g/n</li><li>• Bluetooth 4.0</li></ul>

## Video

	Inspiron 3521	Inspiron 3537
Controller:		
Integrated	Intel HD Graphics 4000	Intel HD Graphics 5100/4200/4400 series
Discrete	<ul style="list-style-type: none"><li>• AMD Radeon HD 7670M</li><li>• AMD Radeon HD 8730M</li></ul>	<ul style="list-style-type: none"><li>• AMD Radeon HD 8670M</li><li>• AMD Radeon HD 8850M</li></ul>
Memory:		
Integrated	System shared memory	
Discrete	Up to 2 GB	

## Audio

Controller	ALC3223
Speaker	2 x 2 W
Internal microphone support	Single digital microphone in the camera assembly
Volume controls	Program menus and keyboard media-control keys

## Storage

Type	SATA
Interface	<ul style="list-style-type: none"><li>• SATA 1.0 (1.5 Gbps)</li><li>• SATA 2.0 (3.0 Gbps)</li><li>• SATA 3.0 (6.0 Gbps)</li></ul>
Hard drives	One 2.5-inch SATA drive (supports Intel Smart Response Technology)
Optical drives	One 9.5 mm SATA drive
Drives supported	DVD+/-RW

## Media-card reader

---

Type	One 8-in-1 slot
Cards supported	<ul style="list-style-type: none"><li>• SD card</li><li>• SD High-Capacity (SDHC) card</li><li>• SD Extended Capacity (SDXC) card with Ultra High Speed (UHS)</li><li>• Memory Stick</li><li>• Memory Stick PRO</li><li>• Memory Stick XC (MSXC)</li><li>• MultiMedia Card (MMC)</li><li>• MultiMedia Card plus (MMC+)</li></ul>

## Display

---

Type	<ul style="list-style-type: none"><li>• 15.6-inch HD</li><li>• 15.6-inch HD touchscreen</li></ul>
Maximum resolution	1366 x 768
Dimensions:	
Height	224.30 mm (8.83 inches)
Width	360 mm (14.17 inches)
Diagonal	396.24 mm (15.60 inches)
Refresh rate	60 Hz
Operating angle	0 degree (closed) to 140 degrees
Pixel pitch	0.252 mm
Controls	Brightness can be controlled through keyboard shortcuts

## Keyboard

---

Type	Chiclet keyboard
------	------------------

## Camera

---

Resolution:	
Still image	0.92 megapixels
Video	1280 x 720 (HD) at 30 fps (maximum)
Diagonal viewing angle	74 degrees

## Touchpad

---

### Resolution:

Horizontal	1560 dpi
Vertical	2553 dpi

### Dimensions:

Height	54 mm (2.13 inches)
Width	98 mm (3.86 inches)

## Battery

---

Type	<ul style="list-style-type: none"><li>• 4-cell "smart" lithium ion (40 WHr) – non-touch only</li><li>• 6-cell "smart" lithium ion (65 WHr)</li></ul>
------	--

Dimensions:	4-cell	6-cell
Height	20 mm (0.79 inch)	27.40 mm (1.08 inches)
Width	272.40 mm (10.72 inches)	
Depth	49.30 mm (1.94 inches)	
Weight	0.26 kg (0.57 lb)	0.36 kg (0.79 lb)
Voltage	14.8 V	11.1 V
Operating time	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions	
Life span (approximate)	300 discharge/charge cycles	
Temperature range:		
Operating	0 °C to 35 °C (32 °F to 95 °F)	
Storage	−40 °C to 65 °C (−40 °F to 149 °F)	
Coin-cell battery	CR-2032	

## Power Adapter

---

Type	<ul style="list-style-type: none"><li>• 65 W</li><li>• 90 W</li></ul>
Input voltage	100 VAC–240 VAC
Input current (maximum)	1.50 A/1.60 A/1.70 A/2.50 A
Input frequency	50 Hz–60 Hz
Output current	3.34 A/4.62 A
Rated output voltage	19.50 VDC
Temperature range:	
Operating	0 °C to 40 °C (32 °F to 104 °F)
Storage	–40 °C to 70 °C (–40 °F to 158 °F)

## Computer Environment

---

Temperature range:

Operating	0 °C to 40 °C (32 °F to 104 °F)
Storage	–40 °C to 70 °C (–40 °F to 158 °F)

Relative humidity (Maximum):

Operating	10 % to 90 % (non-condensing)
Storage	10 % to 95 % (non-condensing)

Maximum vibration (Measured using a random vibration spectrum that simulates user environment):

Operating	0.66 GRMS
Storage	1.30 GRMS

Maximum shock (Measured with hard drive in operating status and a 2-ms half-sine pulse for operating. Also measured with hard drive in head-parked position and a 2-ms half-sine pulse for storage):

Operating	110 G
Storage	160 G

Altitude (Maximum):

Operating	–15.20 m to 3048 m (–50 ft to 10,000 ft)
Storage	–15.20 m to 10,668 m (–50 ft to 35,000 ft)

Airborne contaminant level G1 as defined by ISA-S71.04-1985