



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PS-410-HGOEMCC

4-Outlet, 3ft. Coiled Cord Medical Power Strip



Highlights

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- Tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 hospital-grade receptacles and hospital-grade plug
- 3-ft coiled cord, extends to 10 ft.
- Two 15-amp resettable circuit breakers

Description

Tripp Lite's PS-410-HG-OEMCC Power Strip is designed to be installed on any mobile cart, diagnostic equipment, instrument, IV pole, etc. It is TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack, table or pedestal-mounted. Features 4 output receptacles, 10-ft. AC coiled cord and two built-in resettable circuit breakers that control power to all outlets and protect against overloads. Switchless design prevents accidental shutoff. Optional -use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal coil corded multi-outlet strip

Applications

- Mobile carts, IV poles and other UL 1363A certified usages.
- Can be used in Patient Care Areas, when properly mounted.

Package Includes

- PS-410-HGOEMCC Power Strip
- Owner's manual and warranty information

Features

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 x NEMA 5-15R-HG hospital-grade output receptacles
- 10-ft. AC coiled cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Rugged all-metal housing withstands years of use without breakage
- 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff

Specifications

OVERVIEW

| | |
|--|--|
| Model Type | For Patient-Care Areas |
| OUTPUT | |
| Frequency compatibility | 50 / 60 Hz |
| Output volt amp capacity (amps) | 15 |
| Overload protection | 2 x 15amp breakers (1 line, 1 neutral) |
| Outlet quantity / type | 4 NEMA 5-15R-HG |
| Outlet orientation | Single row of 4 |
| INPUT | |
| Recommended Electrical Service | 15A, 120V |
| Input connection type | NEMA 5-15P-HG |
| Input cord length (ft.) | 15 |
| Input cord length (m) | 4.572 |
| Input cord gauge, type | 14 gauge, SJT |
| Voltage compatibility (VAC) | 120 |
| LEDS ALARMS & SWITCHES | |
| Switches | No power switch |
| PHYSICAL | |
| Shipping weight (lbs) | 3.55 |
| Unit Dimensions (HWD/in) | 13.75 x 2.5 x 1.5 |
| Shipping Dimensions (HWD/in) | 15 x 6 x 3.55 |
| Unit weight (lbs) | 2.25 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Keyhole mounting tabs and flanges enable mounting to a variety of surfaces |
| Receptacle Color | White |
| AC line cord color | White |
| CERTIFICATIONS | |
| Approvals | TUV tested to UL 1363A |
| WARRANTY | |
| Product Warranty Period (U.S., Canada & Puerto Rico) | Lifetime limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4844.

improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.