

Dual-Monitor USB-C Dock for Windows® - 4x USB 3.0 Ports

Product ID: MST30C2DPPD



Enhance your productivity by turning your Windows® based USB-C™ laptop into a full-scale workstation. This dual-monitor USB-C dock lets you easily connect two monitors (1x HDMI and 1x DisplayPort) using one USB-C cable, with no setup of display drivers required, right out of the box. The USB-C dock provides 60W charging power, and four USB 3.0 ports to connect devices. With easy dual-monitor setup, the dock is ideal for wide-scale use in office workstations.

Create a Dual Monitor Workstation

This USB-C dock lets you connect dual monitors with flexible options, and with no display driver setup.

Connect your USB-C laptop to:

- Dual displays: 1x DisplayPort and 1x HDMI (cable included) at 1920 x 1200 resolution @ 60Hz

You can also connect to a single 4K HDMI or DisplayPort display. The included 3.3 ft. (1 m) long USB-C cable makes it easy to position your laptop and improves the video signal quality.



Connect Your Devices

Unlike some USB-C docks that may drop to USB 2.0 and limit Ethernet performance, this USB Type-C™ dock offers full USB 3.0 and network bandwidth. This provides faster data transfer speeds when using your USB 3.0 peripherals and supports true Gigabit Ethernet network throughput.

USB Type-C™ dock gives you plenty of ports with four USB 3.0 ports, a reliable Gigabit Ethernet port and easy connection to the microphone and headset ports. Connect flash drives, keyboard, mouse or external hard drives using the three Type-A ports (including one Fast-Charge port). Connect a USB-C device with the USB-C port.



60W Charging Power

The USB C docking station with Power Delivery will power and charge (up to 60W) your laptop, while powering your devices.

The MST30C2DPPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Notes:

- *Ensure your laptop's drivers, firmware, and operating system are current prior to using the docking station.*
- *Video output capabilities depend on the video*



card and hardware specifications of the connected laptop.

- *Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your laptop USB-C port supports DP Alt Mode and USB Power Delivery.*
- *Not all Thunderbolt 3 USB-C ports support the full functionality of the Thunderbolt 3 standard. Ensure that your laptop Thunderbolt 3 port supports USB Power Delivery.*

Certifications, Reports and Compatibility



Applications

- Add essential ports required for mass deployment and standard workstation use in an office environment
- Ideal for USB-C equipped Windows laptops such as Dell XPS™, Lenovo® ThinkPad™, HP® Spectre, HP EliteBook and HP ProBook

Features

- Easily connect dual monitors (DisplayPort and HDMI) right out of the box, with no display driver setup
- Connect your USB devices with 4 x USB 3.0 ports - 1x USB-C and 3x USB-A (including 1x Fast-Charge)
- Power and charge your laptop with Power Delivery 2.0 (up to 60W)
- Add wired network connectivity with the Gigabit Ethernet RJ45 port
- Includes long 3.3 ft. (1 m) USB-C cable and HDMI cable

Hardware	Warranty	3 Years
	4K Support	Yes
	Bus Type	USB-C
	Chipset ID	Cypress - CYPD1122-40 MegaChips - STDP4320 MegaChips - MCDP2850 Cypress - CYUSB3328-88LTXC Cypress - CYUSB3610-68LTXC Texas Instruments - PCM2912APJT
	Displays Supported	2
	Fast-Charge Port(s)	Yes
	Industry Standards	USB Power Delivery Specification Rev. 2.0 USB Battery Charging Specification Rev. 1.2 DisplayPort 1.2 with MST IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1
	Performance	
Auto MDIX	Yes	
Compatible Networks	10/100/1000 Mbps	
Full Duplex Support	Yes	
Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)	
Maximum Digital Resolutions	Single display - DisplayPort - 3840 x 2160 @ 30Hz Single Display - HDMI - 4096 x 2160 @ 24Hz / 3840 x 2160 @ 30Hz Dual displays - 1x DisplayPort + 1x HDMI - 1920 x 1200 @ 60Hz Lower resolutions are also supported.	
Type and Rate	USB 3.0 - 5 Gbit/s	
UASP Support	Yes	
Connector(s)		
Connector Type(s)	2 - USB Type-C (24 pin) USB 3.0 (5Gbps) Female 1 - DisplayPort (20 pin) Female 1 - HDMI (19 pin) Female 1 - USB 3.0 A (Fast-Charge, 9 pin) Female 2 - USB Type-A (9 pin) USB 3.0 Female 1 - RJ-45 Female 2 - 3.5 mm Mini-Jack (3 Position) Female	
Software		
OS Compatibility	Windows® 7, 8, 8.1, 10	

Special Notes / Requirements	Note	
	System and Cable Requirements	<p>Ensure your laptop's drivers, firmware, and operating system are up to date prior to using the docking station.</p> <p>For a dual-monitor configuration, the Windows laptop must support MST.</p> <p>A 4K-capable HDMI display is required to achieve 4K resolution</p> <p>Video output capabilities are dependent on the video card and hardware specification of your connected laptop.</p> <p>Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your laptop USB-C port supports DP Alt Mode, as well as USB Power Delivery.</p> <p>USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps</p> <p>Not all Thunderbolt 3 USB-C ports support the full functionality of the Thunderbolt 3 standard. Ensure that your laptop Thunderbolt 3 port supports USB Power Delivery.</p> <p>This docking station provides up to 60W of Power Delivery to charge your laptop. Some laptops may have specific charging requirements such as the full 60W for charging. In the event that your laptop is not charging, simply unplug any peripheral accessories attached to the dock's USB-C port (on back of dock) and the USB 3.0 (Type-A) charging port (on front of dock) during charging. This will ensure the full 60 W of power is available for charging your laptop.</p> <p>A Windows-based laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode)</p>
Indicators	LED Indicators	<p>1 - Power (Green)</p> <p>1 - RJ45 Link (Green/Amber)</p> <p>1 - RJ45 Activity (Yellow)</p>
Power	<p>Center Tip Polarity</p> <p>Input Current</p> <p>Input Voltage</p> <p>Output Current</p> <p>Output Voltage</p> <p>Plug Type</p> <p>Power Consumption (In Watts)</p> <p>Power Delivery</p>	<p>Positive</p> <p>1.5 A</p> <p>100 - 240 AC</p> <p>4.5 A</p> <p>20V DC</p> <p>N</p> <p>90</p> <p>60W</p>

	Power Source	AC Adapter Included
Environmental	Humidity	5%~95% RH (Non-condensing)
	Operating Temperature	5°C to 35°C (41°F to 95°F)
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Physical Characteristics	Color	Black
	Material	Plastic
	Product Height	1.1 in [2.8 cm]
	Product Length	8.3 in [21 cm]
	Product Width	3.5 in [90 mm]
	Weight of Product	9.2 oz [261 g]
Packaging Information	Package Height	4.5 in [11.5 cm]
	Package Length	9.8 in [25 cm]
	Package Width	5.1 in [13 cm]
	Shipping (Package) Weight	2.9 lb [1.3 kg]
What's in the Box	Included in Package	<ul style="list-style-type: none"> 1 - USB-C docking station for laptops 1 - USB-C cable [1 m/3.3 ft] 1 - HDMI cable 1 - universal power adapter 3 - power cords (NA/JP, UK, EU) 1 - quick-start guide

Product appearance and specifications are subject to change without notice.