



Fast, affordable, compact POS printers with a 2-Year Overnight Exchange warranty¹

PT340/PT341 printers from OKI: ideal where productivity, economy and space are critical.

Responsive, versatile, efficient and fast—with an extremely short time to first print of 1.95 seconds². PT340/PT341 Series printers are ideal for busy, time-critical and customer-focused environments, such as retail and hospitality.

They're also highly adaptable where space is at a premium: not only do they have a small footprint, they can be positioned either horizontally or vertically, even wall-mounted.


Both models have a recess under the case to neatly conceal interface connectors, and the PT341 has its own built-in power supply.

Flexible and versatile POS printing. PT340/PT341 Series printers can handle a variety of media types and sizes, including the industry standard 83mm-OD roll. They're perfect for receipts, coupons and tickets.

Both models deliver up to 300mm/sec print speed³ with up to 203 dpi resolution. They give you a choice of fonts and a variety of barcodes, including 2-dimensional QR codes. In addition, their internal memory can store up to 576 KB, so you can add graphics and logos to your printouts.

Save paper. And money, too. With PT340/PT341 Series printers, you can reduce the amount of paper you use for receipts—and reduce your costs, as well as your carbon footprint. This can be done in two ways:

- By back-feeding the paper after each receipt prints—the top section usually left blank—you can save up to 5.7% of the paper you use.³



- By using the Windows[®] driver that allows you to shrink the vertical print size, you can slash receipt lengths by up to 50% without losing printed data.⁴

With their long list of features and capabilities, PT340/PT341 Series receipt printers are perfect for your business. And they're backed by a 2-Year Advanced Overnight Exchange warranty and 24/7/365 live technical support.⁴

Highlights:

- **Fast print speed: up to 300mm/sec.²**
- **Robust and reliable – withstand extreme environments**
- **PT341 model has a built-in power supply**
- **Auto cutter (partial cut) – enables clean and easy removal of printed receipts**
- **Models available with Serial + USB + LAN or Serial + USB connectivity**
- **Buzzer alert function – signals completion of print job; ideal in noisy environments**
- **Optional splash-proof cover – adds protection**
- **Optional wall-mount bracket – adds flexibility**



¹ Available in the U.S. and Canada only.

² Published performance results based on laboratory testing. Individual results may vary.

³ On receipts 150mm in length; 3.5% on receipts 250mm in length.

⁴ Available in 203 dpi mode only.

PT340/PT341 Series

Specifications		
Technology	Print Method	Direct Thermal
	Print Speed	Up to 300mm/second ¹
	Print Resolution	Up to 203 dpi (8 dot/mm)
Interface	Standard	Choice of RS232C Serial + Full-speed USB 2.0 + 10 Base-T/100 Base-TX (RJ-45) Ethernet or RS232C Serial + Full-speed USB 2.0
Compatibility	Operating Systems	Windows® 8, Windows 7, Windows Vista®, Windows XP, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003, Windows Embedded POSReady 2009, Windows Embedded for Point of Service, OPOS (v1.13), JavaPOS™ (v1.10) for Windows
	Emulation	Epson® ESC/POS®
Font and Graphics	Character Types	Alphanumeric, International Character, Extended Graphics, Downloaded Registration, User-defined Kanji
	Barcodes	1D: UPC-A, UPC-E, JAN13 (EAN), JAN8 (EAN), CODE 39, ITF, CODABAR (NW-7), CODE 93, CODE 128; 2D: QR code, PDF417, DataMatrix
	Graphic/Logo Storage	384KB/192KB
Paper Handling	Media Width/Print Area	58mm: 48mm (384 dots) or 52.5mm (420 dots); 80mm: 64mm (512 dots) or 72mm (576 dots)
	Media Roll Diameter	Up to 83mm diameter max.
	Media Thickness	0.065mm (65µm) to 0.085mm (85µm)
	Cutter	Partial cut
	Paper Loading	Drop-in
	Sensors	Paper near end; Paper end
Environmental	Size (WxDxH)	PT340: 5.67" x 7.24" x 4.72" (144mm x 184mm x 120mm) PT341: 5.67" x 7.24" x 6.50" (144mm x 184mm x 165mm)
	Weight	PT340: 2.64 lb. (1.2kg); PT341: 3.74 lb. (1.7kg)
	Electrical	PT340: 24VDC, +/- 10%; PT341: 100-240VAC, 50/60Hz
	Operating Temperature/Humidity	32°F to 104°F (0°C to 40°C); 10% to 95% RH, without condensation
	Storage Temperature/Humidity	-4°F to 140°F (-20°C to 60°C); 5% to 95% RH, without condensation
Reliability	Printer	60 million lines (MCFB)
	Printhead	100km
	Cutter	1.5 million cuts (Partial cut)
Warranty	Printer	2-Year Advanced Overnight Exchange ³
Options	Accessories	Splash-proof cover; Wall-mount bracket (PT340 only)

Ordering Information	
Description	Part Number
PT340 Black – Serial/USB/LAN (120V)	62308503
PT340 Black – Serial/USB (120V)	62308504
PT341 Black – Serial/USB/LAN (120V)	62308603
PT341 Black – Serial/USB (120V)	62308604
Options	
Splash-proof cover	44950502
Wall-mount bracket (PT340 only)	44950402

For more information on Label/POS Printers from OKI, contact your OKI representative. Or visit our Web site: www.okidata.com

For a complete list of OKI print media, please go to our Web site: www.okidata.com

¹ Published performance results based on laboratory testing. Individual results may vary.

² javaPOS driver supports RS232C and USB interface.

³ Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2013 Oki Data Americas, Inc. OKI Reg. T.M., Oki Electric Industry Co., Ltd. Windows, Vista Reg. T.M., Microsoft Corp. JavaPOS T.M., Sun Microsystems, Inc. Epson, ESC/POS Reg. T.M., Seiko Epson Corp. USB I/F logo T.M., Universal Serial Bus Implementers Forum, Inc.

OKI DATA AMERICAS, INC.

USA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 800.OKI.DATA (800.654.3282)
FAX: 856.222.5320

CANADA
4140B SLADEVIEW CRESCENT
UNITS 7 & 8
MISSISSAUGA, ONTARIO L5L 6A1
TEL: 905.608.5000
FAX: 905.608.5040

LATIN AMÉRICA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 55.5263.8780 (MEXICO)
FAX: 55.5250.3501 (MEXICO)

OKI DATA DE MÉXICO, S.A. DE C.V.
MARIANO ESCOBEDO, 748 8º PISO
COL. NUEVA ANZURES C.P. 11590
MÉXICO, D.F.
TEL: 55.5263.8780
FAX: 55.5250.3501

OKI DATA DO BRASIL INFORMÁTICA LTDA.
AV. ALFREDO EGÍDIO DE SOUZA ARANHA, 100
BLOCO C – 4º ANDAR
04726-170 – SÃO PAULO – SP – BRASIL
TEL: 11.3444.3500
FAX: 11.3444.3502

WWW.OKIDATA.COM

