

2 Port Wall Mountable USB to Serial Adapter Hub with COM Retention

Product ID: ICUSB2322X



The ICUSB2322X 2 Port Professional Grade USB Serial Adapter converts a single USB port to two RS232 serial ports allowing you to connect to, monitor and control your serial devices. Rugged metal construction and sturdy wall-mount brackets provide a robust solution for both harsh industrial environments and simple desktop installations.

Powered by USB, the device does not require a power outlet for most standard applications. For installations requiring more power through the RS232 ports, the hub supports connection of an external power adapter (not included) to the integrated DC jack or terminal block. Once connected, the adapter retains assigned serial COM port values, allowing the same values to automatically be re-assigned to the ports provided by the adapter in the event it is disconnected, then re-connected to the host computer.

This innovative Serial adapter offers a professional grade solution for connecting legacy or industrial RS232 serial devices to more modern computers, or computers with unused USB ports – perfect for connecting serial modems, barcode scanners or any device with serial sync through USB, eliminating the expense of upgrading serial peripherals for USB compatibility.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Perfect for IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port
- Connect, monitor and control industrial/automotive sensors and equipment
- Connect bar code scanners, receipt printers and other point of sale devices
- Connect a satellite receiver, serial modem, or PDA with serial sync
- Connect and program LED and Digital signage boards with serial communication ports

Features

- USB to 2 Port Straight-Through RS232 Serial Adapter
- Rugged metal construction
- Wall-mountable
- COM Port assignments maintained across reboot
- Baud Rate up to 230 Kbps
- Optional DC jack or terminal block power connections
- Powered by an available USB port - no external power adapter required
- Designed to make serial port expansion quick and simple
- Provides dual buffers for upstream and downstream data transfer
- Supports automatic handshake mode
- Enables and disables enumerations

Hardware	Warranty	2 Years
	Bus Type	USB 2.0
	Chipset ID	Texas Instruments - TIUSB3410
	Interface	Serial
	Port Style	External Hub
	Ports	2
Performance	FIFO	32 Bytes
	Max Baud Rate	230.4 Kbps
	Serial Protocol	RS-232
Connector(s)	Connector Type(s)	1 - USB Type-A (4 pin) USB 2.0 Male
	External Ports	2 - DB-9 (9 pin, D-Sub) Male
Software	OS Compatibility	Windows® XP, Vista, 7, 8 Windows Server® 2003, 2008 R2, 2012, 2016
Power	Input Voltage	9 ~ 36 DC
	Plug Type	N
	Power Source	Not Included (not required for standard applications)
Environmental	Humidity	5~85% RH
	Operating Temperature	-10°C to 80°C (14°F to 176°F)
	Storage Temperature	-20°C to 100°C (-4°F to 212°F)
Physical Characteristics	Color	Black
	Enclosure Type	Steel
	Product Height	0.9 in [23 mm]
	Product Length	4.4 in [113 mm]
	Product Weight	10.6 oz [300 g]
	Product Width	3.1 in [80 mm]
Packaging Information	Shipping (Package) Weight	1 lb [0.5 kg]
What's in the Box	Included in Package	1 - USB to RS-232 Serial Adapter 1 - 3ft USB A to B cable 1 - Driver CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.