

Heavy-Duty Power Extension Cord, 15A, 14 AWG (IEC-320-C14 to IEC-320-C13), White, 6 ft.

MODEL NUMBER: P005-006-AWH











Highlights

- Easy-to-identify white SJT jacket and fully molded white ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Also recommended for replacing lost or old power cord

Package Includes

P005-006-AWH Heavy-Duty
 Power Extension Cord, White, 6
 ft.

Description

The P005-006-AWH Heavy-Duty Power Extension Cord is recommended for replacing a lost or worn-out power cord or extending your current power connection by six feet. It features a white SJT jacket and fully molded white ends, allowing you to easily identify your connections in a crowded workstation. A C14 male connector on one end and a C13 female connector on the other let you attach computers, printers, scanners, power supplies, monitors and other compatible hardware. This six-foot 15A cord supports voltages up to 250V. It's UL-listed and features a flexible SJT jacket and 14 AWG wire for easy routing through tight areas.

Features

Safe, Reliable Power Solution

- Connects hardware with C13/C14 power connectors
- · Ideal for replacing an old or lost cord
- Extends current power connection by 6 ft.

Color-Coded Cable and Connectors

• Colored white for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- · Flexible SJT jacket
- 250V/15A rating
- UL-listed

Specifications

INPUT





Cable Length (m) 1.8 Cable Length (in.) 72 PHYSICAL Color White ENVIRONMENTAL Operating Temperature Range -4 F TO 140 F (-20 C TO 60 C) Storage Temperature Range -4 F TO 140 F (-20 C TO 60 C) Operating Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13		
Cable Length (in.) PHYSICAL Color White ENVIRONMENTAL Operating Temperature Range -4 F TO 140 F (-20 C TO 60 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13	Cable Length (ft.)	6
PHYSICAL Color White ENVIRONMENTAL Operating Temperature Range -4 F TO 140 F (-20 C TO 60 C) Storage Temperature Range 4 F TO 140 F (-20 C TO 60 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13	Cable Length (m)	1.8
ENVIRONMENTAL Operating Temperature Range	Cable Length (in.)	72
ENVIRONMENTAL Operating Temperature Range	PHYSICAL	
Operating Temperature Range -4 F TO 140 F (-20 C TO 60 C) Storage Temperature Range -4 F TO 140 F (-20 C TO 60 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13	Color	White
Storage Temperature Range -4 F TO 140 F (-20 C TO 60 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13	ENVIRONMENTAL	
Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13 WARRANTY	Operating Temperature Range	-4 F TO 140 F (-20 C TO 60 C)
Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13 WARRANTY	Storage Temperature Range	-4 F TO 140 F (-20 C TO 60 C)
CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13 WARRANTY	Operating Humidity Range	10-85% RH
Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C13 WARRANTY	Storage Humidity Range	10-85% RH
Side B - Connector 1 IEC-320-C13 WARRANTY	CONNECTIONS	
WARRANTY	Side A - Connector 1	IEC-320-C14
	Side B - Connector 1	IEC-320-C13
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY	
	Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies