Hyper T4

RR-T4-18PK-R1

The Cooler Master Hyper T4 is an affordable mainstream Heatsink delivering great cooling performance on all modern platforms thanks to its 4 specially shaped direct touch Heatpipes. The T4's 120mm PWM fan features a wide fan speed range and can be fine tuned for maximum airflow and cooling performance or silent operation. Thanks to this flexibility, a quick and easy snap-on fan bracket and a universal mounting system the Hyper T4 is a great match for any system.

Features

- 4 Direct Contact heatpipes for seamless contact between cooler and CPU.

- 120mm wide range PWM fan, RPM can be fine tuned for maximum airflow or whisper quiet operation.

- Snap-On fan brackets to quickly and easily install, remove, clean or replace the fan or heatsink.

- Versatile all-in-one mounting solution supporting the Intel® LGA 2011/1366/1156/1155/775 and AMD FM2+/FM2/FM1/AM3+/AM3 /AM2

Specifications

CPU Socket	Intel® LGA 2011/1366/1156/1155/1150/775 AMD FM2+/FM2/FM1/AM3+/AM3 /AM2
Dimensions	131.6 x 72.5 x 152.3 mm (5.2 x 2.9 x 6 in)
Heat Sink Dimensions	128 x 44 x 152.3 mm (5 x 1.7 x 6 in)
Heat Sink Material	4 Direct Contact Heatpipes / Aluminum Fins
Heat Sink Weight	448 g / 1 lb
Heat Pipe Dimensions	Ø6mm
Fan Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1 in)
Fan Speed	600~1800 RPM (PWM) ± 10%
Fan Air Flow	24~70 CFM ± 10%
Fan Air Pressure	0.3~2.14 mm H_2O ± 10%
Fan Life Expectancy	40,000 hours
Noise Level	15.1~31.6 dBA
Bearing Type	Rifle bearing
Connector	4-Pin
Rated Voltage	12 VDC
Rated Current	0.2A**
Power Consumption	2.64 W
Fan Weight	100 g / 0.22 lb
Net Weight	650 g / 1.43 lb
Gross Weight	804 g / 1.77 lb

Package Information

EAN Code	4719512038826
UPC Code	884102018206
Package Dimensions	163 x 115 x 185 mm (6.4 x 4.5 x 7.3 in)
Carton Dimensions	506 x 246 x 392 mm (19.9 x 9.7 x 15.4 in)
Unit / Carton	12
Carton / Pallet	40

Warranty

2 years

*Note: Photos may slightly differ from the final product

Convenient Snap-On fan bracket	Compatible with all common mainboards
4 Direct Contact Heatpipes	Universal CPU mounting system