
Epson WorkForce AL-M200DN

DATASHEET



The Epson WorkForce AL-M200DN LED printer features double-sided printing, fast print speeds and a large duty cycle for high-performance printing. With one of the best Total Cost of Ownerships (TCOs) in its class, this model offers an affordable solution for small office and home office users.

The WorkForce AL-M200DN is network-ready for sharing across small workgroups, but can also be used on individual user desktops thanks to its compact size. It also features a retractable paper tray which, when the printer is not in use, can be folded away.

The Epson WorkForce AL-M200DN's toner cartridge is easy to replace. Users simply insert the cartridge into the toner slot and twist to connect. No mess, no hassle, no problem.

In addition, users can print and share from anywhere in the office, thanks to Epson's mobile printing app, Epson iPrint. This easy-to-use application allows workers to print wirelessly from smartphones and tablet PCs*1.

With the WorkForce AL-M200DN, businesses can concentrate on their work, without any downtime, as its high-performance, user-friendly features offer great peace of mind and productivity.

KEY FEATURES

- One of the best TCOs in its class
- 30ppm*2 and 30,000-page duty cycle
- Standard double-sided printing
- Easy-to-replace toner cartridge
- Print from smartphones and tablet PCs

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Resolution	1,200 dpi
Toner System	AcuBrite
Category	Small Workgroup

PRINT

Printing Speed	Monochrome 30 Pages/min
First Page Out	Monochrome 7 Seconds
Warm Up time	26 s
Max Duty cycle	30,000 Pages per month

CONNECTIVITY

Interfaces	USB 2.0 Type B, Ethernet interface (100 Base-TX / 10 Base-T)
Network Printing Protocols	Port 9100, WSD, NDS Printserver
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, mDNS, WSD, SMTP, POP3

PAPER / MEDIA HANDLING

Paper Formats	A4, A5, B5, C5 (Envelope), DL (Envelope), LT, LGL, MON, Executive
Duplex	Yes
Compatible Paper Weight	60 g/m ² - 163 g/m ²
MP Tray Capacity	10 Sheets Standard
Output Tray Capacity	125 Sheets
Paper Tray Capacity	250 Sheets Standard
Number of Paper Trays	1 Trays

GENERAL

Power consumption	1,000 W (Max.), 450 W (Printing), 50 W (Ready), 8 W (sleep)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Product dimensions	385 x 355.6 x 225 mm (Width x Depth x Height)
Product weight	6.8 kg
Temperature	Operation 10° C - 32° C
Humidity	Operation 10% - 85%, Storage 15% - 80%
Compatible Operating Systems	Mac OS 10.5.8 or later, Mac OS 10.6+, Windows 7, Windows 7 x64, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Vista, Windows Vista x64, Windows XP, Windows XP x64
Drivers	Printer driver (PCL6, PS3)
Safety Standards	IEC60950-1, EN60950-1, IEC60825-1, EN60825-1
Electrical Standards	Energy Star Compliant
EMI Standard	EN55022, EN61000-3-2, EN61000-3-3
Included Software	Epson Status Monitor
Sound Power	Operation: 7.4 B (A) - standby: 4.3 B (A)
Sound Pressure	Operation: 54.4 dB (A)-standby: 24.8 dB (A)

OTHER FEATURES

Processor Speed	295 MHz
Memory	128 MB Included, 128 MB maximum
Emulations	PCL6, PostScript 3

OTHER

Warranty	12 months Carry in
LCD screen	Type: Monochrome, 2-line text x 2 Lines

WHAT'S IN THE BOX

- Main unit
- Power cable
- Setup guide
- Software (CD)
- Warranty Documents

LOGISTICS INFORMATION

- SKU
C11CC70011BY
- Barcode
8715946527536
- Dimensions Single Carton
444 x 484 x 330 mm
- Carton Weight
8.4 Kg



For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)

Web: www.epson.co.uk
www.epson.ie

E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1. Epson iPrint-enabled printers must be on the same network subnet as the smartphone and tablet PC being used. For more information, supported languages and devices, please visit www.epsonconnect.eu
2. Determined in accordance with ISO/IEC 24734 showing the average of ESAT / FSOT from the Office Category Test for default simplex / duplex. For more information visit www.epson.eu/testing

EPSON[®]