

Yield Reporting Form

HP LaserJet Pro M118-M119 and HP LaserJet Pro MFP M148-M149 cartridge model CF294X

Declared ISO yield

Toner cartridge yieldAverage cartridge yield **2,800** standard pages¹

Declared yield value in accordance with ISO/IEC 19752 based on continuous printing

Average ¹	3,092
Standard Dev.	138
90% lower confidence limit ¹	3,043

Test date: beginning	11/5/2018
Test dates: ending	11/27/2018
Number of cartridges used in testing	24
Number of cartridges used in calculations	24
Type of cartridge	HP CF294X
Shake procedure used?	No
Print mode	Continuous
Job size	100 pages per job
Number of engines used in testing	8
Media	Double A 80g
Paper size	A4
Paper feed orientation	Short edge
Computer model	HP LP2065
Operating system	Microsoft Windows 10
Application software	Adobe Reader 9
Print driver version	44.3.2667
Connection type	network
Test page version*	Version 4.0 pdf
Power on/off every day	No

Engine serial numbers:

Engine Firmware Version:

VNF3K03916	20180726
VNF3K03298	20180726
VNF3K03914	20180726
VNF3K05393	20180726
VNC4701630	20180726
VNC4701680	20180726
VNC4701641	20180726
VNC4701640	20180726

*filename: Download_Free___19752_Test_Chart___pdf from ISO SC28 website

Cartridge testing data

Test environmental limits:	Temperature	Humidity
	°C	%RH
Max running average	24.4	56
Min running average	21.4	44
Average	23.1	52

CF294X		HP LJ Pro M118dw and M148fdw	
Cartridge	Lot Code	Engine SerNo	Cartridge Yield
CF294X_AM_1	8J12H1Aa	VNF3K03916	3275
CF294X_AM_2	8J12H1Aa	VNF3K03298	3166
CF294X_AM_3	8J12H1Aa	VNF3K03914	3225
CF294X_AM_4	8J12H1Aa	VNF3K05393	3208
CF294X_AM_5	8J12H1Aa	VNC4701630	3325
CF294X_AM_6	8J12H1Aa	VNC4701680	3220
CF294X_AM_7	8J12H1Aa	VNC4701641	3330
CF294X_AM_8	8J12H1Aa	VNC4701640	3325
CF294X_AM_9	8J22H2Aa	VNF3K03916	2973
CF294X_AM_10	8J22H2Aa	VNF3K03298	2941
CF294X_AM_11	8J22H2Aa	VNF3K03914	2978
CF294X_AM_12	8J22H2Aa	VNF3K05393	3059
CF294X_AM_13	8J22H2Aa	VNC4701630	3075
CF294X_AM_14	8J22H2Aa	VNC4701680	3067
CF294X_AM_15	8J22H2Aa	VNC4701641	3015
CF294X_AM_16	8J22H2Aa	VNC4701640	3175
CF294X_AM_17	8J29H1Aa	VNF3K03916	3042
CF294X_AM_18	8J29H1Aa	VNF3K03298	2963
CF294X_AM_19	8J29H1Aa	VNF3K03914	2944
CF294X_AM_20	8J29H1Aa	VNF3K05393	2879
CF294X_AM_21	8J29H1Aa	VNC4701630	2994
CF294X_AM_22	8J29H1Aa	VNC4701680	2975
CF294X_AM_23	8J29H1Aa	VNC4701641	3017
CF294X_AM_24	8J29H1Aa	VNC4701640	3025

¹ In an ISO report two values are commonly listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information visit www.hp.com/go/learnaboutsupplies.