Christie Access Series LCD panels

The perfect balance between performance and price

24/7 operation

Technical sp	ecifications	Christie UHD751-P	Christie UHD861-P	
Display technology	screen size (diagonal)	• 75" (190.5cm)	• 86" (217.4cm)	
	native resolution	• UHD 3840 x 2160 (16:9)		
	backlight	Direct-lit LED		
	LED lifespan	• 50,000 hours to 50% brightness		
	display orientation	Portrait or landscape		
	pixel pitch	• 0.429 x 0.429mm	• 0.493 x 0.493mm	
	nominal bezel size (bottom/side/top)	• 38mm/16mm/16mm	• 103mm/30mm/30mm	
	brightness	• 400 nits (cd/m²) typical	• 500 nits (cd/m²) typical	
	contrast ratio (full field)	• 1200:1 typical		
	viewing angle (CR 10:1)	• 178° h/v		
	refresh rate	• 60Hz	• 120Hz	
	response time	• 8 ms typical		
	color space (CIE 1931)	• 75% typical	• 60% minimum	
	display colors	• 10 bit, 1.07 billion colors		
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • 2 x USB 2.0 • USB 3.0		
	outputs	• DisplayPort 1.2a; HDMI 2.0		
Audio	inputs	• RCA (L/R) line in		
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax		
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender		
Power	input rating	• 100-240 VAC @ 50-60Hz		
	power consumption	218W typical (without OPS)250W typical (without OPS)<= 0.5W in standby (without OPS)	251W typical (without OPS)310W typical (without OPS)<= 0.5W in standby (without OPS)	
Environment	operating temperature	• 32-104°F (0-40°C)		
	storage temperature	• -4-140°F (-20-60°C)		
	operating humidity	• 20-90% RH non-condensing		
Physical	size (panel only)	• (WxHxD) 66.3 x 38.1 x 2.9" (1684 x 967 x 73mm)	• (WxHxD) 77.8 x 45.1 x 4.1" (1975 x 1146 x 103mm)	
	weight	• 80.5lbs (36.5kg)	• 144.4lbs (65.5kg)	
	mounting	• VESA 600 x 400mm, M6		
Runtime		Designed for 24/7 operation featuring a reliable power supply ¹		
Features		Commercial-grade LCD with LED backlight OPS slot Anti-glare treatment 2 x 8W speakers On/off scheduler USB playback of Photo/Video/MP3 HDMI-CEC Source switching for failover Kensington lock Wi-Fi® Bluetooth Miracast device connectivity Pixel shifting		
Accessories		• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA751 up to 10 point IR touch overlay (for 75" panel only)		
Warranty		Three year parts and labor limited warranty Contact an authorized Christie representative for full details		

 $^{^{1}\,\}text{Avoid static images for extended periods.}\,\text{Refer to the product documentation for additional guidance}.$

Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com

Corporate offices	Worldwide offices	
Christie Digital Systems USA, Inc. Cypress	Australia ph: +61 (0) 7 3624 4888	
ph: 714 236 8610	Brazil	

Christie Digital Systems Canada Inc. ph: +55 (11) 2548 4753 ph: 519 744 8005

China (Beijing) ph: +86 10 6561 0240 China (Shanghai) ph: +86 21 6278 7708 Columbia ph: +57 (318) 447 3179

Eastern Europe ph: +36 (0)1 47 48 138

France ph: +33 (0) 1 41 21 44 04 Germany (Cologne) ph: +49 221 99 512-0 Germany (Moechengladbach) ph: +49 2161 566200 ph: +91 (080) 6708 9999

> ph: +81 3 3599 7481 Mexico ph: +52 55 4744 1790

Republic of South Africa ph: +27 11 251 0000

ph: +65 6877 8737 South Korea ph: +82 2 702 1601

ph: +34 91 633 9990 United Arab Emirates ph: +971 (0) 4 503 6800 United Kingdom ph: +44 (0) 118 977 8000 United States (Arizona) ph: 602 943 5700 United States (New York) ph: 646 779 2014

Independent sales consultant offices

Italy ph: +39 (0) 2 9902 1161 Russia ph: +7 (495) 930 8961









