



PN 901381
UPC 7 84090 04014 5

USB-C 4K Docking Station

Key Features:

- USB-C Compatibility (Including Thunderbolt™ 3)
- Triple Display MST Docking Station
- Power Delivery up to 85W with included USB-C Power adapter and cable
- Supports up to 3 external displays - Windows™
- Supports up to 2 external displays - Mac™
- 2x USB 3.0 Ports
- 2x USB 2.0 Ports
- Kensington™ Security Lock Slot
- Enterprise Features
 - Wake on LAN
 - MAC Address Pass-Through
 - PXE Boot

Increase productivity with our plug and play power passthrough docking station, the VisionTek VT2500 USB-C Docking Station for Windows™ and Mac™ laptop systems. With a single USB-C connection, you can connect up to three external displays, transfer files and data at up to 5Gbps speeds, play audio and charge your laptop and mobile devices.

- Universally Compatible USB-C – Windows™ or Mac™, the VT2500 is compatible through the single, included USB-C 1 meter cable, making this the ideal docking station for mixed system environments. Also compatible with Thunderbolt™ 3 systems.
- USB-C Power Delivery – Charge your laptop, up to 85W with included USB-C Power adapter and cable. The VT2500 can also be used without the power adapter to charge your mobile devices from the laptop's battery. USB-C power adapter can be used to charge your laptop without the dock too.
- Connect Up to Three External Displays – The VT2500 has three video ports to provide video connection options that suit your needs using MST technology. Use two DisplayPort and one HDMI together for a three-display experience. (Windows™ systems support up to three external displays. Mac™ systems support one extended and one cloned/mirrored external display.)
- Expanded Selection of Ports – Flexibility is the goal with the VT2500, by offering some of the most commonly needed ports in one dock using the included 1 meter USB-C cable.
 - 1x HDMI and 2x DP ports let you connect external displays to increase your system workspace.
 - 2x USB 3.0 ports let you connect external storage or mobile devices for sync & charge.
 - 2x USB 2.0 ports increase the number of compatible devices you can connect when you don't need USB 3.0 speed support, including full sized mouse & keyboard.
 - 1x SD and 1x MicroSD Reader port let you retrieve data without having to use any of the USB ports.
 - 1x Combination 3.5mm Audio Input/Output port gives you a single connection option for music listening or video conference participation.
 - 1x RJ45 port supports speeds up to 1000Mbps (10/100/1000Mbps supported) to keep you wired to the internet, avoiding Wi-Fi connection or security concerns.



Part Number: 901381 | UPC Code: 7 84090 04014 5

Front



Sides




USB-C to System Port
(Use Included Cable)



Kensington™ Lock Slot

Back



Part Number: 901381 | UPC Code: 7 84090 04014 5

Dock Specifications

System Requirements

Operating Systems Supported	Windows™ 7, 8, 8.1, 10 - MacOS™ 10.X and later
System Resource Requirement	System must support Power Delivery mode through USB-C DP Alt Mode. System must support MST compatibility for multi-display setup.
USB-C Power Delivery	Supports USB-C PD 3.0 5V/9V/12V/15V/20V up to 4.25A 85W Maximum

Dock to System Connection

Dock Connector	USB-C
----------------	-------

Video Connections

Single Display	DisplayPort 1.4 Port: Up to 3840 x 2160 @60Hz HDMI 2.0 Port: Up to 3840 x 2160 @60Hz
Dual Display	DisplayPort 1.4 Port: Up to 2560 x 1440 @60Hz Or: HDMI 2.0 Port: Up to 3840 x 2160 @60Hz
Triple Display	2x DP + 1x HDMI Ports: Up to 1920 x 1080 @60Hz

* Windows™ systems support up to three external displays.
** Mac™ systems support one extended and one cloned/mirrored external display.

USB Connections

Front	1x USB-A 3.0 Port
Back	1x USB-A 3.0 Port 2x USB-A 2.0 Port 1x USB-C Power Delivery Input Port

Additional Ports

Front	1x SD Reader 1x MicroSD Reader
-------	-----------------------------------

Network Connections

Ethernet Port	RJ45
Compatible Ethernet Speed	10/100/1000 Mbps

Audio Connections

Audio Connectors	3.5mm Combo Audio Input/Output Port - Front
Audio Channels Supported	Stereo LR

Part Number: 901381 | UPC Code: 7 84090 04014 5

Dock Specifications

Power and Environmental

Power	Power delivery compatible with supplied USB-C Power Adapter up to 85W. Must connect dock to system with included USB-C Cable.
Operating Temperature	0 to 40° C (32 to 104° F)
Storage Temperature	-10 to 70° C (-14 to 158° F)
Relative Humidity	5% to 90% non-condensing

Product Dimensions

Product Dimensions	Length: 8.15" (207mm) Depth: 2.25" (58mm) Height: 0.75" (20mm)
Product Weight	0.50 lbs (230g)
Power Adapter Dimensions	Length: 8.15" (207mm) Depth: 2.25" (58mm) Height: 0.75" (20mm) Power Cable Length: 4.6' (1402mm)
Power Adapter & Cable Weight	1.1 lbs (499g)
Included USB-C Cable Length	3 feet (1M)
Product Color and Material	Black Polycarbonate ABS

Packaging Dimensions

Packaging Style	Retail Box
Packaging Specifications	Length: 10.4" (265mm) Depth: 2.4" (61mm) Height: 4.4" (112mm) Weight: 2.2 lb (998g)
Master Carton	40 pcs
Individual Package Contents	1x VT2500 Dock 1x 100W Power Adapter & Cable (85W to system if using dock) 1x USB-C to USB-C Cable 3ft (1M) 1x Quick Start Manual

Country of Origin and Warranty Information

Country of Origin	China
Certifications and Compliance	CE, FCC, RCM, REACH, RoHS, WEEE, HDMI 2.0 Certified
Warranty	2-Years Limited

Additional Features

Security	Kensington™ Security Lock Slot
----------	--------------------------------

All specifications are subject to change without notice. Products may not be available in all markets. The VisionTek name and design are registered trademarks of VisionTek Products, LLC. All other registered and unregistered trademarks are the property of their respective owners.

FOR MORE INFORMATION CONTACT: 1-866-883-5411 | sales@visiontek.com

