





FCS-5202 Version: 1

1 Power supply unit is to be ordered separately.

# GEMINI Fixed IP Network Camera, 4-Megapixel, IR LEDs, 802.3af PoE, Indoor/Outdoor

The LevelOne FCS-5202 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 4-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5202 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

# **Key Features**

- 4-Megapixel high-definition resolution
- Video compression: H.264, H.265, MJPEG
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Built-in infrared LEDs for night viewing up to 30m
- Weatherproof IP67-rated housing

# **Specifications**

# **System Specifications**

# Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

# Image Sensor:

1/3" Progressive Scan CMOS

#### Lens:

4 mm fixed lens

## Port:

RJ45 10M/100M Ethernet port

Power connect

#### Button/Knob:

Reset Button

# IR Cut Filter:

Support

#### IR LED:

IR LEDs for illumination up to 30m

www.level1.com Page 1 of 3

#### Shutter Time:

1/3 s to 1/100,000 s

## Angle of View:

4 mm @ F1.6: horizontal FOV: 83°, vertical FOV: 45°, diagonal FOV: 99°

## Video Format:

H.265 /H.264 / MJPEG/

#### Resolution:

50Hz:25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)

## Output Video Format:

MPEG-4

## Power Input:

12 VDC ± 25%, ? 5.5 mm coaxial power plug

PoE (802.3af, class 3)

## Power Consumption:

DC12V ± 10%, PoE (802.3af), Max. 6W

#### Data Rate:

256 Kbps to 16 Mbps

## Storage Capacity:

Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

# Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

# Operating Humidity (Non-condensing):

95% or less

# **Features**

## General:

One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter

## PoE:

PoE (802.3af)

## Security:

Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error

## Management:

Line crossing detection, intrusion detection

Region of Interest: 1 fixed region for main stream and sub-stream

Face Detection: Yes

# Video:

- Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR)120dB
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Portrait Mode
- Privacy Mask
- Time Stamp and Text Caption Overlay

Image Layout:

Streaming: Up to 3 video streams Motion Detection: 3 Detection Zones

www.level1.com Page 2 of 3

## **Performance**

## Number of Clients:

Simultaneous Live View up to 6 channels

# Frame Rate (fps):

Main Stream:

50Hz:25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)

Sub-Stream:

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream:

50Hz: 25fps (1280  $\times$  720, 640  $\times$  360, 352  $\times$  288) 60Hz: 30fps (1280  $\times$  720, 640  $\times$  360, 352  $\times$  240)

## Minimum illumination:

Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR

# **Physical Specifications**

## Dimensions (W x D x H mm):

 $70 \times 70 \times 155.03 \text{ mm } 2.8" \times 2.8" \times 6.1"$ 

# Weight (g):

420 g (0.9 lb.)

## Color:

White

# **Approval and Compliance**

## EMI/EMS:

CE,FCC

# Safety:

IP67

TVS 2000V Lightning Protection

Surge Protection and Voltage Transient Protection

## Others:

**ONVIF** 

# Others

## Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

## **Order Information**

FCS-5202

# **Package Contents**

FCS-5202

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content. Specifications are subject to change without notice. All mentioned brand names are registered trademarks and property of their owners. Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.

www.level1.com Page 3 of 3