

## 5948q Series Zero Clients

Power Class

Model Numbers: 5948qv, 5948qc, 5948qr, 5948qp

### Industry Leading VDI Performance

The 5948q NOS™ Series Zero Client is the newest model to the 10ZiG product lineup and is of the first in the industry to fully support a triple-monitor 4K UHD setup at the absolute highest performance levels never seen before in a zero client. The new 10ZiG 5948q Series is based on the Intel Braswell Refresh CPU platform. The impressive 3840 x 2160 @ 30Hz/ 2560 x 1600 @ 60Hz support allows for a maximum of three simultaneous displays, including an in-demand 2 x DisplayPort and 1 x HDMI combination.

The CPU features the Quad-Core Intel Pentium Processor N Series N3710, has new Touch Technology with a rotating "ports-on-foot" stand, TPM 2.0 optional, and comes with a rare find of optional PoE. The 5948q NOS™ Series Zero Client comes in models built to excel for VMware, Citrix, RDP or Parallels RAS.



- ▶ Quad-Core Intel Pentium Processor N Series N3710
- ▶ Operates at a Base Frequency of 1.6 GHz (2.56 GHz Burst)
- ▶ 2 x DisplayPort and 1 x HDMI Combination
- ▶ 7 x USB (2 x USB 3.0)
- ▶ Optional PoE (Power over Ethernet)
- ▶ Optional Wireless
- ▶ Optional VESA & ARM Mount
- ▶ TPM 2.0 Optional
- ▶ 4K UHD with Triple Monitor Support\*
- ▶ 802.1x Network Authentication
- ▶ FREE Centralized Management via 10ZiG Manager



# 5948q Series Thin Clients



System	
Management	10ZiG Manager
Form Factor	Mini
Processor	Intel Pentium N3710 Quad-Core 1.6 GHz (2.56 GHz Burst Frequency)
Processor Graphics	Intel HD Graphics 400
Dimensions	
Device	1.9"(W) x 7.5"(H) x 5.8"(D)   4.9 x 19.3 x 14.9cm
Weight	1.98 lbs (900g)
Connections	
Ports	2 x DisplayPort, 1 x HDMI, 2 x USB 3.0, 5 x USB 2.0, 1 x Mic In, 1 x Line Out, 1 x LAN (RJ-45), DC Jack
Video/Resolution	3840 x 2160 @ 30Hz / 2560 x 1600 @ 60Hz (3 monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Ethernet	1 x RJ-45 (10/100/1000 Base-T)
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity
Power	3.4 Average Watt Consumption, DC-12V/3A External Power Adapter



### SPECIFICATIONS

- |                    |                                      |
|--------------------|--------------------------------------|
| 1. Power Button    | 8. Reserve hole for extended antenna |
| 2. USB 3.0 (2)     | 9. USB 2.0                           |
| 3. USB 2.0         | 10. HDMI Port                        |
| 4. Mic In          | 11. DisplayPort (2)                  |
| 5. Line Out        | 12. RJ45 LAN Port                    |
| 6. Kensington Lock | 13. DC Jack                          |
| 7. USB 2.0         |                                      |

**VMware**  
**5948qv**

**Citrix**  
**5948qc**

**RDP**  
**5948qr**

**Parallels RAS**  
**5948qp**

Operating System	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)	NOS™ (Zero)
Memory (RAM)	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB	Std: 4GB Max: 8GB
VDI Broker Support	VMware Horizon (Blast Extreme, PCoIP, RDP)	Citrix XenApp & XenDesktop (HDX, HDX Premium, HDX 3D Pro)	RDP	Parallels RAS

\*4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.



Americas P: +1 (866) 865-5250  
 EMEA P: +44 (0) 116 214 8650  
 APAC P: +61 2 80027421  
 DE P: +49(0) 6724 934-45

E: info@10ZiG.com  
 E: info@10ZiG.eu  
 E: info@10ZiG.com.au  
 E: vertrieb@10zig.de

W: www.10ZiG.com

