

Thunderbolt 3 Dual-4K Docking Station for Laptops - Mac and Windows - 5K Support - Thunderbolt 3 Dock for MacBook Pro

Product ID: TB3DKDPMAWUE



This cost-effective Thunderbolt[™] 3 dock (without Power Delivery) supports your Thunderbolt 3 port equipped MacBook Pro or Windows® based laptop. Plus, the dock supports dual monitors, so you can easily connect two 4K Ultra HD (up to 60Hz) displays (one DisplayPort and one Thunderbolt 3 USB-C[™] port), or a single Thunderbolt 3 display (60Hz).




Merging performance with simplicity, this highquality dock is a single-cable solution that caters to creative professionals such as video producers, graphic and web designers, engineers, architects, and many more.



Finish your work faster with Thunderbolt 3

You can quickly integrate the dock into your workspace and boost your productivity. With up to 40Gbps of throughput, you can add extra displays to your laptop, access files faster, and reduce waiting, so you can accomplish more in the same amount of time.

Thunderbolt 3 is the fastest connection available, and it supports multiple video channels and data, without impacting system performance. It's easy to access and edit large uncompressed files such as videos and images on the fly.



Multitask at the highest resolution

If you need a larger, higher-resolution viewing area, this dock can help. You can connect two 4K Ultra HD displays, so it's perfect for anyone working with high-bandwidth or graphics-intensive content.

The Thunderbolt 3 dock supports two 4K (3840 x 2160p) monitors at up to 60Hz through the DisplayPort and Thunderbolt 3 USB-C port (USB-C video adapter might be required). For dual monitors, simply connect your DP monitor, and a second monitor through the dock's extra Thunderbolt 3 port using an adapter such as the <u>USB-C to DisplayPort Adapter Cable</u> (CDP2DPMM1MB - sold separately) or using a USB-C based monitor. The Thunderbolt dock will also work with legacy displays such as VGA monitors when coupled with a USB-C to VGA adapter.

With support for two 4K monitors, the Thunderbolt dock makes it easier to multitask when you're working with high-definition video or other complex work.



For advanced 5K resolutions requirements, this dock supports a single 5K display when you connect your monitor to one of the Thunderbolt 3 ports, delivering $5120 \times 2880p$ resolutions at up to 60Hz.

Connect your peripherals using only a single cable

Using the single Thunderbolt 3 cable (included) and a single port on your laptop, you can transform your macOS Sierra (or later) or Windows® 7 (or later) laptop into a full-size workstation with access to new and legacy technologies through a number of different port types. The dock is ideal for virtually all Thunderbolt 3 equipped laptops such as the Dell[™] XPS 13, and the Apple MacBook Pro (2016).

The Thunderbolt 3 docking station features two Thunderbolt 3 USB-C ports for connecting to Thunderbolt devices and other peripherals that use the USB-C connector, as well as DisplayPort video output.



Convenient connections prepare you for the future

You can keep your mobile device charged and ready to go using the dock's convenient, always-on USB fast-charge and sync port which supports USB Battery Charging Specification 1.2. The Thunderbolt 3 dock offers a variety of other connections that are often missing from port-limited laptops, such as an extra USB-C port (5Gbps - data only), and a Gigabit Ethernet port.

With three USB 3.0 ports in total, you have plenty of ports to connect modern and legacy devices. (USB 3.0 is also known as USB 3.1 Gen 1.) Now, you can rest assured knowing you're ready for the current and next generation of universal connectivity.

The rear-panel DP and USB-C ports can be used with dual monitors that support lower resolutions, such as 4K at 30Hz or 1080p. StarTech.com offers a variety of USB-C video adapters, such as <u>USB-C to HDMI</u> and <u>USB-C to VGA</u>, which lets you connect a mixture of modern and legacy displays to the docking station.

Maximum Supported Resolutions*



| Video Output Configuration | Max DisplayPort Resolution | Max Thunderbolt 3 USB-C Resolution |
|---|-----------------------------------|--|
| DisplayPort and Thunderbolt 3 USB-C (Two Displays - Dual-4K) | 3840 x 2160p (Up to 4K - 60Hz) | 3840x 2160p (4K - 60Hz) |
| DisplayPort (Single Display - 4K) | 3840 x 2160p (Up to 4K - 60Hz) | N/A |
| Thunderbolt 3 USB-C (Single Display - 5K) | N/A | 5120 x 2880p (5K - 60Hz) |
| Thunderbolt 3 USB-C (Single Display through DP ALT mode - 4K) | N/A | 3840x 2160p (4K - 60Hz) |
| Thunderbolt 3 USB-C Daisy Chain | N/A | Dependent on the number of Thunderbolt 3 displays |

*Lower resolutions are also supported.

*When connecting a display to one of the Thunderbolt 3 USB-C ports, a USB-C video adapter may be required depending on the input of your display.

Please note: 5K support can only be achieved using a Thunderbolt 3 5K monitor. DisplayPort 5K monitors will not work with this docking station.

Certain monitors may be limited to 4K at 30Hz when connecting through DisplayPort. These monitors include the following models: Dell P2715Q, Viewsonic VX2475Smhl-4K, Philips 288P6LJEB, LG 31MU97C-B, Asus PB287Q (these models will need to be set to 4K at 30Hz).

The TB3DKDPMAWUE features a rugged aluminum casing, and is backed by a StarTech.com 3-year warranty and free lifetime technical support.



Your computer's Thunderbolt 3 ports might not function properly until you update one or more of the following on your computer:

• BIOS

- Thunderbolt firmware
- Thunderbolt 3 controller drivers



• Thunderbolt 3 software

The required updates will vary depending on your computer.

For an up-to-date list of affected computers and instructions, visit <u>http://thunderbolttechnology.net/updates.</u> If your manufacturer isn't listed on the Thunderbolt website, contact your manufacturer.



Certifications, Reports and Compatibility











Applications

- The perfect docking station for the MacBook Pro, with support for macOS Sierra (or later)
- A vital accessory for your Thunderbolt 3 equipped laptop
- Ideal for creative professionals and those who work with highresolution, high-bandwidth, and graphically intensive images, video, CAD drawings, and medical imagery
- Recommended for video producers, graphic and web designers, engineers, architects, and more
- Access and edit large, uncompressed files such as videos and images on the fly, for dynamic on-site production
- Transfer a 4K movie in under 30 seconds, or 3 hours of 4K GoPro® video in less than a minute
- Edit 4K video on one display, with a full-size video preview on the second 4K display
- Dock and undock quickly, with a single cable for data and external displays

Features

- Improve your workflow with single-cable docking and up to 40Gbps bandwidth — twice the speed of Thunderbolt 2 (20Gbps) and eight times faster than USB 3.0 (5Gbps)
- Supports dual-4K monitors, with 3840 x 2160p at up to 60Hz resolution on each display, or a single 5K 5120 x 2880p display
- Connects to your laptop's Thunderbolt 3 USB-C port, so you can access multiple displays and peripherals
- Thunderbolt Certified and includes a Thunderbolt 3 host cable (0.5 m)
- Includes three USB 3.0 ports (USB-C, 2x USB-A), two Thunderbolt 3 USB-C ports, 3.5mm audio out, 3.5mm microphone in, and Gigabit Ethernet
- Fast charge your phone or tablet with the always-on USB 3.0 fastcharge and sync port
- Works with macOS Sierra (or later), as well as Windows 7 (or later)



Hard-to-find made easy*

Data Sheet

| | Warranty | 3 Years |
|------------------|-----------------------------|--|
| Hardware | 4K Support | Yes |
| | Bus Type | Thunderbolt 3 |
| | Chipset ID | Intel - Alpine Ridge DSL6540 Fresco Logic - FL1100EX Texas Instruments - PCM2912A Intel - WGI210AT |
| | Displays Supported | 2 |
| | Fast-Charge Port(s) | Yes |
| | Industry Standards | Thunderbolt 3 USB Battery Charging Specification Rev. 1.2 IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1 |
| Compa Full Du | Auto MDIX | Yes |
| | Compatible Networks | 10/100/1000 Mbps |
| | Full Duplex Support | Yes |
| | Maximum Data Transfer Rate | 40 Gbps (Thunderbolt 3) 10 Gbps (USB 3.1 Gen 2) 5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex) |
| | Maximum Digital Resolutions | Single display - DisplayPort or USB-C (DP alt mode) - 4096 x 2160p (up to 60Hz) or 4096 x 2160p (60Hz) Single display - Thunderbolt 3 Display - 5120p x 2880p (60Hz) Dual displays - DisplayPort and USB-C (DP alt mode) - 4090 x 2160p (up to 60Hz) / 3840 x 2160p (60Hz) and 4096 x 2160p (up to 60Hz) / 3840 x 2160p (60Hz) |
| | Type and Rate | Thunderbolt 3 - 40 Gbit/s |
| | UASP Support | Yes |
| Connector(s) | Connector Type(s) | 2 - Thunderbolt™ 3 USB-C (24-pin) Female |
| | | 1 - DisplayPort (20 pin) Female |
| | | 1 - USB Type-C (24 pin) USB 3.0 Female |
| | | 1 - USB 3.0 A (Fast-Charge, 9 pin, SuperSpeed) Female |
| | | 1 - USB Type-A (9 pin) USB 3.0 Female |
| | | 2 - 3.5 mm Mini-Jack (3 Position) Female |
| | | 1 - RJ-45 Female |
| | | |



Hard-to-find made easy*

Data Sheet

| Software | OS Compatibility | Windows® 10 (32-bit or 64-bit), 8 / 8.1 (32-bit or 64-bit), 7 (32-bit or 64-bit) macOS 10.12 (Sierra) |
|---------------------------------|--|--|
| Special Notes / Requirements | Note | This docking station will not charge your host laptop. |
| | | 5K support can only be achieved using a Thunderbolt 3 5K monitor. DisplayPort 5K monitors will not work with this docking station. |
| | | A 4K-capable display is required to achieve 4K x 2K resolution (4K is also known as 4K x 2K). |
| | | Certain monitors may be limited to 4K at 30Hz when connecting through DisplayPort. These monitors include the following models: Dell P2715Q, Viewsonic VX2475Smhl-4K, Philips 288P6LJEB, LG 31MU97C-B, Asus PB287Q (these models will need to be set to 4K at 30Hz). |
| | | When connecting a display to one of the Thunderbolt 3 USB- C ports, a USB-C video adapter might be required depending on the input of your display. |
| | | USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. USB 3.1 Gen 2 offers speeds up to 10Gbps. |
| | | |
| | System and Cable Requirements | Thunderbolt 3 equipped computer with a Thunderbolt 3 port. |
| Power | System and Cable Requirements Center Tip Polarity | Thunderbolt 3 equipped computer with a Thunderbolt 3 port. Positive |
| Power | | |
| Power | Center Tip Polarity | Positive |
| Power | Center Tip Polarity Input Current | Positive 1.5 A |
| Power | Center Tip Polarity Input Current Input Voltage | Positive 1.5 A 100 ~ 240 AC |
| Power | Center Tip Polarity Input Current Input Voltage Output Current | Positive 1.5 A 100 ~ 240 AC 6 A |
| Power | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC |
| Power | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N |
| Power | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type Power Consumption (In Watts) | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N 72 |
| | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type Power Consumption (In Watts) Power Source | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N 72 AC Adapter Included |
| | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type Power Consumption (In Watts) Power Source Humidity | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N 72 AC Adapter Included 5~95% RH (Non-condensing) |
| | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type Power Consumption (In Watts) Power Source Humidity Operating Temperature | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N 72 AC Adapter Included 5~95% RH (Non-condensing) 5°C to 40°C (41°F to 104°F) |
| Environmental Physical | Center Tip Polarity Input Current Input Voltage Output Current Output Voltage Plug Type Power Consumption (In Watts) Power Source Humidity Operating Temperature Storage Temperature | Positive 1.5 A 100 ~ 240 AC 6 A 12 DC N 72 AC Adapter Included 5~95% RH (Non-condensing) 5°C to 40°C (41°F to 104°F) -40°C to 70°C (-40°F to 158°F) |



| Hard-to-find made easy® | | Data Sheet |
|--------------------------|---------------------------|-----------------------------------|
| | Product Height | 27 mm [1.1 in] |
| | Product Length | 220 mm [8.7 in] |
| | Product Weight | 442 g [15.6 oz] |
| | Product Width | 80 mm [3.1 in] |
| Packaging Information | Shipping (Package) Weight | 1.2 kg [2.6 lb] |
| What's in the Box | Included in Package | 1 - Thunderbolt 3 docking station |
| | | 1 - Thunderbolt 3 cable |
| | | 1 - universal power adapter |
| | | 2 - power cords (EU, UK) |
| | | 1 - instruction manual |

Product appearance and specifications are subject to change without notice.