

# Thor VX8

## Vehicle-Mount Computer

In the dynamic environment faced by the modern enterprise, accurate, real-time data is critical. With this in mind, many enterprise resource planning (ERP) deployments are looking to integrate every possible datapoint, including the warehouse floor, and the forklifts rolling on that floor during a shift. Vehicle-mounted computers operating in this environment require the enterprise-level computing power needed to handle robust applications and ERP systems without slowing the operator down.

The Thor VX8 is designed for enterprises that need full Microsoft® Windows® computing power in a mobile environment to optimize application and network management compatibility, and is flexible enough to run multiple advanced applications, with a Microsoft® Windows® 7 Professional MUI, Windows® XP Professional MUI or Windows® Embedded Standard 2009 operating system. Radio communications are delivered on the move with optional Bluetooth® wireless connectivity, WLAN or WWAN radio configurations. And it's all packaged in an IP65-rated magnesium enclosure that's built to thrive in the toughest environments. In fact, when combined with its Microsoft® Windows® 7 performance, the VX8's rugged construction makes it ideal for a wide array of manufacturing applications including process control, quality assurance, intermodal operations, and more.



## Features

- **Field Proven Reliability:** Minimizes downtime and maintenance cost with a magnesium case and ruggedness test specifications; dominates the Microsoft® Windows® 7/XP rugged vehicle market with proven reliability in countless rugged vehicle applications
- **Powerful:** Maximizes productivity with Intel Core 2 Duo and Atom processors; minimizes the wait when GUI screens refresh
- **802.11n WLAN and 3.5G WWAN Radios:** Enhances productivity with an extensive range of communications capabilities

# Thor VX8 Technical Specifications

## Mechanical/Environmental

<b>Dimensions</b>	11" x 9" x 3" (279mm x 229mm x 77mm)
<b>Weight</b>	7.7 lbs. (2.9 kg)
<b>Operating Temperature</b>	-22 to +122°F (-30 to +50°C)
<b>Start-up Temperature</b>	-4 to +122°F (-20 to +50°C)
<b>Storage Temperature</b>	-4 to +122°F (-20 to +50°C)
<b>Environmental Sealing</b>	Independently certified to meet IP65 standards for moisture and particle resistance
<b>Material</b>	High strength magnesium housing
<b>Vibration</b>	According to IEC 60068-2-64, Test Fh
<b>Shock</b>	Bump: according to IEC 60068-2-29, Test Eb

## System Architecture

<b>Processor</b>	Intel® Core 2 Duo 1.5GHz, Intel® Atom 1.6GHz
<b>Operating System</b>	Microsoft® Windows® 7 Pro with MUI, Microsoft® Windows® XP Professional MUI, Microsoft® Windows® Embedded Standard 2009 (WES 2009)
<b>Memory</b>	1GB, 2GB
<b>System Software</b>	VMT Manager (Config. Utility), Citrix® Client, Windows® Terminal Services, Barcode Wedge
<b>Optional Software</b>	RFTerm® (Windows Terminal Emulations VT220, TN5250, TN3270), FreeFloat® Access*One Terminal Emulator (VT220, TN5250, TN3270), On-screen soft keyboard
<b>Mass Storage</b>	80 GB 2.5" Hard Drive Automotive, 16 GB CF Solid State Drive, 8 GB CF Solid State Drive, 2 GB CF Solid State Drive (WES Only)
<b>Graphics Processor</b>	Intel® Graphics Media Accelerator (GMA 950), up to 224MB DVMT 3.0
<b>Power Supply &amp; UPS</b>	External power supplies for DC from 10 to 150V and AC, integrated Li-Polymer maintenance UPS
<b>Display</b>	Indoor 10.4" (264mm) TFT flat panel, SVGA (800x600), 400 NIT, 700:1 contrast ratio; Outdoor 10.4" (264mm), SVGA (800x600), 800 NIT, 900:1 contrast ratio
<b>Touch Panel</b>	Industrial 5-wire touch panel with resistive touch and support for finger touch and stylus, Optional touchscreen defroster
<b>Audio</b>	1 Audio out (head set), 1 Mic in (microphone), Onboard speakers (front)
<b>I/O Ports</b>	2 PS/2 ports (1 keyboard, 1 mouse) w/strain relief, 2 Serial ports (COM1) & (COM2) support 5V or 12V to external devices, 2 USB 2.0 ports (with strain relief), 1 USB port under service lid, 1 Multi-purpose connector (Serial + USB), 1 RJ-45 ethernet 10/100, 1 VGA for external monitors
<b>Storage Expansion</b>	2 Mini-PCI, 1 PC card slot
<b>Warranty</b>	1 year factory warranty
<b>Service Plans</b>	Optional one-, three- and five-year service programs offer worry-free mobile computing

## Wireless Connectivity

<b>WWAN</b>	GSM/GPRS Edge, HSDPA/UMTS/WCDMA, Multiband 850/900/1800/1900/2100 MHz, Remote GSM/GPRS antenna included
<b>WLAN</b>	802.11 a/b/g, 802.11 a/b/g/n
<b>WLAN Security</b>	Authentication: Support for a full range of 802.1X (EAP) types, including EAP-TLS, PEAP-MSCHAPv2, PEAP-GTC, LEAP, and EAP-FAST; Encryption: Support for Static, pre-shared, and dynamic encryption keys, 40-bit and 128-bit keys, 8 to 63 ASCII and 64 hexadecimal character passphrases, WEP, WPA (TKIP), and WPA2 (AES) encryption methods. The 802.11 a/b/g/n radio also supports CCKM encryption.
<b>WLAN Antennas</b>	Dual diversity integral external antennas, Remote mount antenna kits available
<b>WPAN</b>	Bluetooth® 2.0+EDR

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance)  
For a complete listing of all supported bar code symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies)



### For more information:

[www.honeywellaidc.com](http://www.honeywellaidc.com)

### Honeywell Scanning & Mobility

9680 Old Bailes Road  
Fort Mill, SC 29707  
800.582.4263  
[www.honeywell.com](http://www.honeywell.com)

