




Planar UltraRes UR9851 Touch

Interactive 4K LCD Display

The Planar® UltraRes™ UR9851 Touch combines a multi-touch experience with stunning 4K image clarity. With 32 simultaneous touch points, the Planar UltraRes UR9851 Touch makes it easy for multiple users to collaborate and interact at the same time. The Planar UltraRes Touch is a fully integrated solution, delivering an elegant design and more accurate multi-touch experience. Offering the flexibility to mount in landscape or portrait, the Planar UltraRes UR9851 delivers a versatile interactive solution. Planar UltraRes UR9851 Touch features Planar® ERO™ (Extended Ruggedness and Optics™) optically-bonded, low-friction protective glass for increased ruggedness and optical performance.



SPECIFICATION	DETAIL
Product Name	UR9851-ERO-T
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	98 in. (diagonal)
Aspect Ratio	16:9
Display Active Area	85.0" (2159mm) x 47.8" (1214mm)
Cabinet Dimensions (W x H x D)	87.6" x 50.4" x 4.1" (2225mm x 1280mm x 104mm)
Dimensions, including wall mount	87.6" x 50.4" x 4.1" (2225mm x 1280mm x 104mm)
Bezel Width	1.3" (33mm)
Protective Glass	ERO optically-bonded glass technology, 3mm AR
Brightness (typ)	500 nits
Response Time (typ)	8 ms
Frame Rate	120Hz
Contrast Ratio (typ)	1300:1
Viewing Angle (typ)	178°
Color Gamut	72% NTSC
Display Color	>1 billion colors. Full 10 bit data path
Modes	1x 3840x2160 @ 24/25/30/60Hz, 4x 1920x1080 @ 24/25/30/50/60Hz; 4x 960x2160 @ 60Hz; 2x 1920x2160 @ 60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz

Pixel Pitch	0.562mm
Weight	330 lbs (150 kg)
Weight (Shipping)	TBD
Backlight	LED
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	410W
Operating Temperature	0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at up to 3000m
Humidity	20 - 85% RH (non-condensing)
Approvals	FCC Class A, CE, cTUVus
External Connections	DisplayPort 1.2 x 1, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS x 1, OPS USB 2.0 x 2, OPS USB 3.0 X 1
Audio Output	PC Line Out, S/PDIF
Multi-Source Views	PiP, Dual, Triple, Quad
Display Control	IR, RS-232, LAN, Keypad, Mobile app
Speakers	10W x 2 built-in
Orientation	Landscape/Portrait
Mounting	Planar Profile Mounting System or VESA: 600 x 400 mm
Fanless	Yes
HD format	4K UHD 2160p
Display Technology	Direct-lit LED LCD
Touch Technology	IR 32 point touch
OS Compatibility	Windows 7, 8, 10, Vista, XP, Mac OSX and Linux
Options / Features	MediaPlex Plus Processing, Scheduling, Presets, Redundant power supply, TAA compliant
Warranty	3 years Advance Exchange
Planar Part Number	997-8092-00
UPC	8 10689 00263 5

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 11/11/2015

© Copyright 2015 Planar Systems, Inc. All rights reserved