



Black Hawk – get in the game

Capable of displaying Full HD images at 75Hz, the 24.5" Black Hawk G-MASTER GB2530HSU is the perfect companion in your gaming adventures. Armed with Black Tuner function and FreeSync Technology with a stunning 1 ms response time, the Black Hawk guarantees you will see every tiny detail even in the shadowed screen areas and will be able to respond to the changing situation in an instant. The height adjustable stand with pivot, swivel and tilt functions allows you to perfectly adjust the position of the screen to your preferences. So get comfortable and get in the game! If 24.5" is not enough for you, check out the 27" Black Hawk GB2730HSU-B1.



FreeSync™ Technology

AMD FreeSync™ technology puts an end to choppy gameplay and broken frames with fluid, artifact-free performance at virtually any framerate.



1ms

Fast response time is key to ultra-smooth game. It reduces ghosting and blurring providing the user with a rich experience to improve performance.

01 DISPLAY CHARACTERISTICS

Diagonal	24.5", 62.2cm
Panel	TN LED, matte finish
Native resolution	1920 x 1080 @75Hz (2.1 megapixel Full HD, HDMI&DisplayPort)
Aspect ratio	16:9
Brightness	250 cd/m ² typical
Static contrast	1000:1 typical
Advanced contrast	12M:1
Response time	1ms
Viewing zone	horizontal/vertical: 170°/160°, right/left: 85°/85°, up/down: 80°/80°
Colour support	16.7mIn 8bit (6bit + Hi-FRC)
Horizontal Sync	30 - 84KHz
Vertical Sync	40 - 75Hz
Viewable area W x H	543.74 x 302.61mm, 21.4 x 11.9"
Pixel pitch	0.283mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	VGA x1 (max. 1920 x 1080 @60Hz) HDMI x1 (max. 1920 x 1080 @75Hz) DisplayPort x1 (max. 1920 x 1080 @75Hz)
USB HUB	x2 (v.2.0)
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
FreeSync support	HDMI&DisplayPort @40-75Hz
OSD languages	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Menu/ Select, Scroll down/ Volume, Scroll up/ ECO Mode, Exit, Input
User controls	picture adjust (contrast, brightness, OverDrive, ACR, ECO, Blue Light Reducer, Black Tuner, colour saturation, gamma), input select, audio adjust (volume, mute, digital audio), store user settings, colour adjust, manual image adjust (i-Style colour, sharpness, HDMI RGB range, video mode adjust, geometry (auto adjust, H. position, V. position, clock, phase), language, setup menu (OSD position, OSD time out, opening logo, FreeSync), display information, reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt, height, pivot (rotation), swivel
Height adjustment	130mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	18W typical, 0.5W stand by

07 SUSTAINABILITY

Regulations	TCO, CE, TÜV-GS, VCCI-B, PSE, CU, Energy Star
Energy efficiency class	A+

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	557.5 x 380 (510) x 230mm
Weight (without box)	5.2kg



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.