

HITACHI Projector Specifications

Model Name		<i>CP-WU8461</i>	<i>CP-WU8451</i>
Display system		3LCD	
Display device	Panel size	0.76" x 3	
	Aspect ratio	16:10	
	Number of pixels	2,304,000 pixels H1920 x V1200 (WUXGA)	
Lens	Zoom	Powered (x 2.0)	
	Focus	Powered	
	Lens shift	Vertical: 0%(up) ~ 55%(down) at the ceiling mounting position Horizontal: 10%(left) ~ 10%(right)	
	F No.	FL-701: 1.8, SL-702: 1.6~2.0, ML-703: 1.6~2.9, LL-704: 1.7~2.0, UL-705: 1.7~2.0	
Light source		365W	330W
Screen Size		30-600 inch	
Number of colors		16.7 million colors	
Light Output (Brightness)		6,000lm	5,000lm
Contrast ratio		5,000 : 1 (Presentation mode)	
Speaker		8Wx2 (stereo)	
Terminals	Computer Input	Digital	HDMI x 2 (HDCP compliant)
		Analog	D-sub 15pin mini jack x 1
	Video Input	Component (Y,Pb/Cb,Pr/Cr)	3RCA jack x 1
		S-Video	Mini DIN 4 pin jack x 1
		Video	RCA jack x 1
	Audio	Input	3.5mm (stereo) mini jack x 2, 2RCA jack (L/R) x 1
		Output	2RCA(L/R) x 1
	Monitor out	Analog	D-sub 15pin mini jack x 1
	HDBaseT Input		RJ45 x 1
	Control		D-sub 9 pin plug x 1 for RS232C
	Network		Wired LAN:RJ45(100BASE-TX/10BASE-T) x 1 Wireless LAN: Optional USB wireless adapter is necessary
	Remote Control Input		3.5mm (stereo) mini jack x 1
	Remote Control Output		3.5mm (stereo) mini jack x 1
	USB		USB-A x 2, USB-B x 1
Operating temperature		0 ~ 45°C at altitude 0 ~ 3,048m	
Operating humidity		10 ~ 85%RH (No condensation)	
Power supply		AC100-120V/AC220-240V (50/60Hz)	
Power consumption		AC100-120V: 550W AC220-240V: 520W	AC100-120V: 500W AC220-240V: 480W
Dimensions (WxHxD)		498mm x 135mm x 396mm (19.6"x5.3"x15.6") [excluding protruding part]	
Weight		Approx. 9.2kg (20.3 lbs)	
Standard accessories		Remote Control (Part # HL02801) with AA batteries, Power cord, Computer cable, Lens cover, User's manuals, Security label, Application CD, Adapter cover	
Optional accessories	Lamp	DT01471	DT01291
	Filter set	UX38242	
	Option Lens	Fixed short throw lens: FL-701 Short throw zoom lens: SL-702 Middle throw zoom lens: ML-703 (Standard lens) Long throw zoom lens: LL-704 Ultra long throw zoom lens: UL-705	
	Mounting accessories	HAS-8150 (Bracket for fixing mount) HAS-104S (Short adapter for fixing mount) HAS-204L (Standard adapter for fixing mount) HAS-304H (Long adapter for fixing mount)	
	USB wireless adapter	USB-WL-11N	
Projecting Method (Setting)		Desk top use / Mount Ceiling / Vertical 360° rotation	
Picture By Picture		Yes	
Status Monitor		Yes	
Cabinet		Material: Plastic Molding, Color: White	

Specifications are subject to change without notice.