



Self-Service  
Customer Engagement

## Stellar TK-2100 Series

21.5" Modular Kiosk



# HIGHLIGHTS

- 21.5" true-flat PCAP touch screen
- Flexible configurations: floor-standing, countertop
- Expandable pedestal for extra functionalities:  
bill acceptance, card dispensing, ticketing and  
pager dispensing
- Modular design for easy serviceability
- Reversible printing direction
- Ideally for self-service applications in retail, food-service,  
hospitality, healthcare, ticketing



Windows/Android



NFC/RFID reader



2D scanner



Fingerprint sensor



Status Indicator



EMV Supportive\*



# Versatile Functionality

PT-200BC



Floor-standing  
with Card Dispenser & Bill Acceptor

PT-300



Floor-standing  
with Ticket Printer



Countertop

PT-200



Floor-standing

PT-500



Floor-standing  
with Pager Dispenser

# PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-200



- Thermal Printer
- Reserved space for Customized bracket for EMV payment devices
- 2D Scanner



- Status Indicator
- Camera
- Proximity Sensor
- NFC/RFID Reader
- MSR / Fingerprint Sensor

# PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-200BC



# PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-300



# PRODUCT SHOWCASE / Stellar TK-2100 Series with Pedestal PT-500



Specifications		TK-2110*	TK-2130	TK-2150	
<b>Computer</b>	Processor	ARM Cortex-A53 Quad Core CPU, 1.20GHz	Intel Bay Trail J1900 Quad Core, up to 2.42 GHz, 2M Cache	Intel 7th Generation Kaby Lake U Core i3/i5/i7	
	System Memory	LPDDR3 2 GB	DDR3L SO-DIMM slot x 1, max 8 GB	DDR4 SO-DIMM slot x 2, max 32 GB	
	Storage Device	16 GB eMMC+ microSD slot x 1		SATA SSD x 1	
	Intel vPro Support	N/A	N/A	Core i3: N/A Core i5/Core i7: Yes (for option)	
	TPM Support	N/A		Yes (for option)	
	Power Supply	12V/60W x 2		12V/60W x1 + 24V/60W x1	
	OS Support	Android 7.1	Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT	Win 10 IoT 64 bit	
	Serial Port	6, DB9 x 1 + RJ45 x 5, 5V/12V support on all COM ports		6, DB9 x 1 + RJ45 x 5, 5V/12V support on all COM ports	
	Standard USB Port	6, USB 3.0 x 1 + USB 2.0 x 5	6, USB 3.0 x 1 + USB 2.0 x 5	6, USB 3.0 x 2 + USB 2.0 x 4	
	OTG USB	Micro-USB x 1		N/A	
	Display Port	HDMI x 2		MiniDP x 1	
	LAN Port	10/100 Mb x 1		10/100/1000 Mb x 1	
	Audio	Internal 3W speaker x 2		Internal 3W speaker x 2	
	Internal Expansion Slot	N/A		M.2 x 1	
<b>Display &amp; Touch</b>	LCD	21.5"			
	Resolution	1920 x 1080			
	Touch	True-flat PCAP touch with multi-touch support			
<b>Physical Dimension</b>	Dimension (W x D x H in mm)	Countertop version: 400 x 460 x 832 Floorstanding version: 625 x 610 x 1620			
	Weight (N. W. in kg)	Countertop version: 27.5 Floorstanding version: 60			
<b>Environmental</b>	Operating Condition	0°C - 50°C, 20%RH - 90%RH	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)		
	Storage Condition	-20°C - 70°C, 10%RH - 90%RH			
<b>Standard Components</b>	Status Indicator	RGB Color LED Indicator			
	Proximity Sensor	Range from 60 cm to 100 cm			
	Camera	1MP wide angle camera			
	Printer	3" thermal printer w/auto cutter, 200 mm/sec			
	WiFi	USB dongle	M.2 WiFi/BT module		
<b>Optional Components</b>	Scanner	2D barcode scanner			
	EMV Payment Device Bracket Support*	Custom bracket support for various EMV payment devices			
	MSR	3 tracks ISO or JISII (HID/VCOM selection)			
	Fingerprint Sensor	Optical type			
	NFC/RFID Reader	Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18092)			
	<b>Optional Items for Pedestal PT-200BC</b>				
	Bill Acceptor	Storing up to 900 notes			
	Card Dispenser	Integrated RFID Reader/Writer, supporting ISO 14443 Type A/B contactless cards; Storing up to 262 cards			
	<b>Optional Item for Pedestal PT-300</b>				
	Ticket Printer	Fanfolded ticket printer for ticket thickness: .004" to .011", ticket width: 2.0" to 3.25"			
	<b>Default Items for Pedestal PT-500 (UPCOMING)</b>				
Pager Dispenser	Capacity	Storing up to 40 pager units			
	Speed	2.5 sec per pager			
	Frequency	430-460MHz			
Pager/Receiver	Dimension (Diameter x H in mm)	100 x 100 x 16.5			
	Weight (N. W. in g.)	96			
	Frequency	430-460MHz			
Transmitter	Power Supply	5V/2A adapter			
	Dimension (W x D x H in mm)	180 x 120 x 30			
	Weight (N. W. in g.)	475			

Note: Bill Acceptor & Card Dispenser can be set in the same pedestal PT-200BC, but only the pedestal PT-300 can accommodate Ticket Printer while pedestal PT-500 can only accommodate Pager Dispenser. \*Google Play services is not supported by this device.

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc. \*Posiflex does not sell the EMV payment devices, but can provide bracket support with an additional charge. \*The product information and specifications are subject to change without prior notice.