# **CyberPower**

## **CSB606 ESSENTIAL SURGE PROTECTOR**

## Offering vital surge protection for common home & office electronic devices

The Essential Surge Protector CSB606 from CyberPower offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The CSB606 provides 900 joules of protection with 6 outlets and a power cord (6 ft.).

Features of the CSB606 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

#### TYPICAL APPLICATIONS

- Routers & Modems
- · Personal Electronics

#### **FEATURES**

- Surge suppression: 900 J
- · Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Straight
- Outlet type: (6) NEMA 5-15R (surge-protected)
- · Power cord: 6 ft
- · Warranty: Limited lifetime

## • Desktop Computers

- Volts: 125 V

- EMI/RFI Filtration: Yes
- Connected Equipment Guarantee: \$50,000

### **SPECIFICATIONS**

| INPUT                        |                        |  |
|------------------------------|------------------------|--|
| Cord Length (ft)             | 6'                     |  |
| Plug Type                    | NEMA 5-15P             |  |
| Plug Style                   | Straight               |  |
| Circuit Breaker              | 15 Amp                 |  |
| Switch                       | Lighted on/off - reset |  |
| OUTPUT                       |                        |  |
| Outlet Type                  | NEMA 5-15R             |  |
| Outlets - Total              | 6                      |  |
| SURGE PROTECTION & FILTERING |                        |  |
| Maximum Surge Current H-G    | 15,000 Amps            |  |
| Clamping Voltage             | 400V (L-N, N-G, L-G)   |  |
| Attenuation                  | 32 dB                  |  |
| EMI/RFI Filtration           | 150KHz to 100MHz       |  |

| SURGE PROTECTION & FILTERING - CON'T |                         |  |
|--------------------------------------|-------------------------|--|
| Maximum Surge Current H-N            | 15,000 Amps             |  |
| Maximum Surge Current N-G            | 15,000 Amps             |  |
| Response Time                        | < 1 nanosecond          |  |
| Maximum Surge Voltage                | 6,000V                  |  |
| Surge Suppression                    | 900 Joules              |  |
| Maximum Surge Current                | 45,000 Amps             |  |
| CERTIFICATIONS                       |                         |  |
| Environmental                        | ROHS Compliant          |  |
| Safety                               | UL1449 3rd Edition, cUL |  |
| WARRANTY                             |                         |  |
| CEG Amount                           | \$50,000                |  |
| Product Warranty                     | Limited-Lifetime        |  |
| Connected Equipment Guarantee        | Lifetime                |  |