



BP48V75ART2UTAA EBM

The Extended Battery Module offers extended run-times during power outages.

The CyberPower Federal Trade Agreements Act (TAA) compliant BP48V75ART2UTAA (48V) Extended Battery Module (EBM) significantly extends run-time during power outages.

It is designed to be similarly mounted in 2U rack or tower configurations. The battery data link transmits the unit's diagnostic vitals to the UPS display for real-time monitoring and a heavy gauge power cord, adapted with plug-n-play DC connectors, permits the battery pack to be easily hot-swapped, ensuring continuous operation of critical systems, during normal UPS maintenance.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship.

Compatible Applications

- PR1500LCDRTXL2UTAA
- PR2200LCDRTXL2UTAA
- PR3000LCDRT2UTAA

Features

- 48V Output
- Plug-n-Play DC Connectors
- 2U Rack/Tower Form Factor
- 3-Year Warranty

BP48V75ART2UTAA EBM

The Extended Battery Module offers extended run-times during power outages.

GEVER 4.1	
GENERAL	
Voltage	48V
Amperage	75A
BATTERY	
Battery Type	Sealed Lead-Acid
Battery Size	12V/9AH
Hot-Swappable	Yes
Replacement Battery	BB Battery - HR9-12
Battery Quantity	8
User Replaceable	Yes
Typical Recharge Time	8 Hours
PHYSICAL	
Rack Size	2U
Dimensions (WxHxD) (in.)	17.25 x 3.5 x 19.5
Weight (lbs.)	67.0
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 90% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	·
Safety	UL1778, cUL 107.1, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	<u></u>
Product Warranty	3 Years Limited