

Mini DisplayPort to HDMI Adapter with USB Audio

Product ID: MDP2HDMIUSBA



The MDP2HDMIUSBA Mini DisplayPort® with USB Audio to HDMI® Adapter offers a cost-effective HDMI with audio to Mini DisplayPort link, letting you connect an HDMI-capable HDTV to a device with a Mini DisplayPort output, while saving the expense of upgrading the TV for compatibility. The Mini DisplayPort adapter is the perfect accessory for any of your Microsoft® Surface™ Pro devices with mDP.

Simply plug in the USB and Mini DisplayPort connectors to a PC or Mac® and the HDMI connector to an HDMI television/monitor. 2-Channel analog audio will pass through to the HDMI connection, delivering sound to the display side, with the convenience of one HDMI cable.

MDP2HDMIUSBA is a passive adapter that requires a DP++ port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbolt™ I/O port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- The Mini DisplayPort® to HDMI® adapter allows for an easy and hassle free connection to any HDMI HDTV or display from a PC or Mac.
- Use your DisplayPort and USB port for video and audio pass-through to one HDMI cable.
- Deliver audio/video content from your PC or Mac to your A/V devices (HDTV or receiver) for a larger and louder viewing.

Features

- USB Audio pass-through to HDMI® cable
- Supports HDTV resolutions up to 1080p
- Easy to use cable, no software required
- Compatible with Intel® Thunderbolt™

Hardware	Warranty	2 Years
	Active or Passive Adapter	Passive
	Adapter Style	Adapters
	Audio	Yes
	AV Input	DisplayPort USB
	AV Output	HDMI
	Industry Standards	DisplayPort 1.1a HDMI 1.3b
Performance	Audio Specifications	Analog / Two channel stereo audio
	Maximum Digital Resolutions	1920x1200 / 1080p
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - Mini-DisplayPort (20 pin) Male
	Connector B	1 - HDMI (19 pin) Female 1 - USB Type-A (4 pin) USB 2.0 Male
Special Notes / Requirements	System and Cable Requirements	DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported)
Indicators	LED Indicators	1 - Red - Power
Environmental	Humidity	0~80% RH
	Operating Temperature	5°C to 35°C (41°F to 95°F)
	Storage Temperature	0°C to 70°C (32°F to 158°F)
Physical Characteristics	Cable Length	26.9 in [68.2 cm]
	Color	Black
	Enclosure Type	Plastic
	Product Height	0.4 in [10 mm]
	Product Length	30 in [762 mm]
	Product Weight	3.2 oz [90 g]
	Product Width	2.2 in [56 mm]
Packaging Information	Shipping (Package) Weight	3.2 oz [90 g]
What's in the Box	Included in Package	1 - Mini DisplayPort and USB Audio to HDMI Adapter

Product appearance and specifications are subject to change without notice.