EB-1980WU

10,000:1	2x HƏMI	16 W	WUXGA

Projecting in WUXGA resolution and with a high brightness of 4,400 lumens, the EB-1980WU is a well-connected business projector. Epson's 3LCD technology provides high White and Colour Light Output for bright images and more vivid colours.

High quality
Professional environments are treated to presentations in more detail than ever before thanks to the EB-1980WU's WUXGA resolution, which fits the resolution and aspect ratio of most laptops. That detail shines through, even in daylight, thanks to 4,400 lumens brightness.

More vivid colours
Epson's own 3LCD technology ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than leading competitive projectors[1].

Easy to set up
Focus help, keystone correction and screen fit modes are included to ensure that set-up is simple, while flexible connectivity options include two HDMI ports and wired LAN.

Share content
Content, such as a multi-source video conference and presentations, can be displayed in split-screen, while Multi-PC Projection software supports up to 50 PCs for collaboration in large meetings.

Built-in speakers
Epson recognises that video is being used more often within presentations, so as well as a high-resolution image, this business projector also includes built-in 16W speakers.

KEY FEATURES

- **Ultra-bright images**
  4,400 lumens White and Colour Light Output
- **Picture quality**
  3LCD technology for vivid colours
- **High connectivity**
  Benefit from HDMI inputs and wired LAN
- **Focus help**
  Easy-to-use focus pattern
- **Split-screen**
  See content, like presentations and video conferences, simultaneously

No.1 SINCE 2001 **EPSON WORLD LEADER IN PROJECTORS**
Source: Futuresource Consulting Ltd.

EPSON®
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.76 inch

IMAGE

Color Light Output	4,400 lumen-3,400 lumen (economy) In accordance with ISO 21118:2012
White Light Output	4,400 lumen - 3,400 lumen (economy) In accordance with ISO 21118:2012
Resolution	WUXGA, 1920 x 1200, 16:10
Contrast Ratio	10,000 : 1
Lamp	280 W, 200 W (economy mode), 3,000 h durability, 4,000 h durability (economy mode)
Keystone Correction	Auto vertical: ± 30 °, Auto horizontal ± 30 °
Aspect Ratio	16:10

OPTICAL

Projection Ratio	1.38 - 2.28:1
Zoom	Manual, Factor: 1 - 1.6
Projection Size	50 inches - 300 inches
Projection Distance Wide	1.5 m - 9 m
Projection Distance Tele	2.4 m - 14.8 m
Projection Lens F Number	1.5 - 2
Focal Distance	23 mm - 38.4 mm
Focus	Manual
Offset	10 : 1

CONNECTIVITY

Interfaces	USB 1.1 Type A, RS-232C, VGA in (2x), VGA out, HDMI in (2x), Composite in, Component in, MHL, Stereo mini jack audio out, Stereo mini jack audio in (2x)

ADVANCED FEATURES

Security	Kensington lock, Security cable hole
Features	Automatic keystone correction, Built-in speaker, Screen Fit, PC Free, Quick Corner, Split-Screen-Function
Video Color Modes	Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM

GENERAL

Product dimensions	377 x 292 x 125 mm (Width x Depth x Height)
Product weight	4.5 kg
Noise Level	Normal: 39 dB (A) - Economy: 32 dB (A)
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
Loudspeaker	16 W

OTHER

Warranty	36 months Carry in or 8,000 h, Lamp: 12 months or 1,000 h

LOGISTICS INFORMATION

SKU	V11H620041
Barcode	8715946538679
Dimensions Single Carton	360 x 539 x 207 mm
Carton Weight	6.33 Kg
Country of Origin	Multiple country of origin

WHAT'S IN THE BOX

- CD Manual
- Computer cable
- Power cable
- Remote control incl. batteries
- User manual

OPTIONAL ACCESSORIES

- Lamp - ELPLP77 - EB-4xxx/197x/198x
  V13H010L77
- Quick Wireless Connect USB key - ELPAP09
  V12H005M09
- Air Filter - ELPAF41 - New EB-19 Series
  V13H134A41
- Soft Carry Case - ELPKS68 - EB-197*W/EB-198*WU
  V12H001K68
- Ceiling Mount - ELPMB23 - White
  V12H003B23
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB02 [240v]
  V12H614040DA

1. - Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO

For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
        www.epson.ie

EPSON®