



# Delock USB Microphone with base and Touch-Mute Button

## Description

This USB microphone by Delock can be used for voice and vocal transmissions. The rubberized base provides a non-slip stand and the gooseneck allows the microphone to bend in the ideal direction. The LED ring indicates that the microphone is ready for operation by means of a blue or red light and the touch mute button can be used to mute the microphone.



## **Specification**

• Connector: 1 x USB 2.0 Type-A reversible male

• Sensitivity: -37 dB +/- 3 dB

• Frequency range: 70 Hz - 15 kHz

• Impedance: 2.2 kOhm +/- 30% at 1 kHz

Sample rate: 16 Bit / 48 kHz

• Touch Mute-Button

Gooseneck

Status LED

Rubber BaseColour: black

Cable length: ca. 1.7 m

• Dimensions (LxWxH): ca. 140 x 60 x 60 mm

· USB bus powered

Plug & Play

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 3.3 / Kernel 4.9.x, Mac ex OS 10.9
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- User manual

## **Images**









## Item no. 65868

EAN: 4043619658688

Country of origin: China

Package: Retail Box







General	
function:	Plug & Play
Supported operating system:	Linux ex Kernel 4.9
	Linux ex Kernel 3.3
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Mac ex OS 10.9
Interface	
connector:	1 x USB 2.0 Type-A reversible male
Technical characteristics	
Frequency range:	70 Hz - 15 kHz
Impedance:	2.2 kOhm +/- 30% at 1 kHz
Voltage:	USB Bus powered (no additional power supply required)
Sensibility:	-37 dB +/- 3 dB
Sample rate:	16 Bit / 48 kHz
Physical characteristics	
Cable length:	1.7 m
Length:	140 mm
Width:	60 mm
Height:	60 mm
Colour:	black