

PowerLite® 99WH WXGA 3LCD Projector



Projectors

Networked Classroom

The widescreen classroom projector with advanced connectivity and premium audio.

3x Brighter Colors¹, and reliable performance — 3LCD, 3-chip technology

One measurement of brightness is not enough — look for both high color brightness and high white brightness. The PowerLite 99WH has:

Color Brightness — 3000 lumens²

White Brightness — 3000 lumens²

Incredible image quality — native WXGA (1280 x 800) resolution and 16:10 format

Long-lasting, low-cost lamps — up to 10,000 hours in ECO Mode³

Advanced network control — RJ-45 and optional wireless connectivity⁴ for remote projector management, presentations over the network and more

Convenient collaboration for BYOD classrooms — wirelessly share⁴ and compare students' work from multiple devices, simultaneously, with Moderator device management software⁵

Wireless projection from an array of devices — project from iPhone®, iPad®, Android™ tablets and smartphones with the free Epson iProjection™ App⁴ (wireless module sold separately)

2x HDMI® digital connectivity — supports multiple high-definition A/V devices; includes one MHL-enabled port

Powerful sound to engage every student — includes a built-in 16 W speaker and microphone input; or, use external speakers, even in Standby Mode



Specifications

Projection System 3LCD, 3-chip technology

Projection Method Front/rear/ceiling mount

Driving Method Poly-silicon TFT Active Matrix

Pixel Number

1,024,000 dots (1280 x 800) x 3

Color Brightness² Color Light Output

3000 lumens

White Brightness² White Light Output

3000 lumens

Aspect Ratio 16:10

Native Resolution

1280 x 800 (WXGA)

Resize

640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA),
1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1366 x 768
(WXGA60-3), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+),
1680 x 900 (WXGA++), 1600 x 1200 (UXGA60)

Lamp Type 200 W UHE

Lamp Life³

Up to 10,000 hours (ECO Mode)

Up to 5000 hours (Normal Mode)

Throw Ratio Range

1.30 (Zoom:Wide), 1.56 (Zoom:Tele)

Size (projected distance)

33" to 320" (0.91 to 9.07 m) (Zoom:Wide)

Keystone Correction

Vertical: ± 30 degrees (Automatic)

Horizontal: ± 30 degrees (Slider)

USB Plug 'n Play

Projector is compatible with PC and Mac® computers

Contrast Ratio Up to 10,000:1

Color Reproduction Up to 1 billion colors

Projection Lens

Type Manual Focus

F-number 1.58 – 1.72

Focal Length 16.9 – 20.28 mm

Zoom Ratio (optical zoom) 1.0 – 1.2

Interfaces

USB-A x 1

USB-B x 1

LAN x 1

HDMI x 1

HDMI/MHL® x 1

Computer/Component x 2

Video x 1

S-video x 1

RS-232C x 1

Mic: Stereo Mini-jack 1

Monitor Out x 1

Audio 1 & 2

Audio L & R

Audio Out x 1

Wireless LAN port: 802.11 b/g/n (optional – module sold separately)

Other

Display Performance NTSC: 480 lines PAL: 576 lines
(Depends on observation of the multi-burst pattern)

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/
SECAM

Speaker 16 W (mono)

Operating Temperature 41 ° to 95 °F (5 ° to 35 °C)

Power Supply Voltage 100 – 240 V AC ±10%, 50/60 Hz

Power Consumption

299 W (Normal Mode)

221 W (ECO Mode)

2.3 W Standby (Communication On)

0.21 W Standby (Communication Off)

Fan Noise

37 dB (Normal Mode)

29 dB (ECO Mode)

Security Kensington®- style lock provision, padlock
and security anchor bar

Dimensions (W x D x H)

Including feet 11.6" x 9.7" x 3.5"

Excluding feet 11.6" x 9.6" x 3.4"

Weight 6 lb (2.7 kg)

Remote Control

Features

Brightness, Contrast, Tint, Saturation, Sharpness, Input signal,
Sync, Tracking, Position, Color temperature, Volume

Operating Angle

Right/left: ± 30 degrees

Upper/lower: ± 15 degrees

Operating Distance 19.7' (6 m)



Eco Features

RoHS compliant

Recyclable product⁶

Epson America, Inc. is a SmartWaySM Transport Partner⁷

Support

The Epson ConnectionSM

Pre-sales support

(U.S. and Canada): 800-463-7766

Internet website: www.epson.com

Service Programs

Two-year projector limited warranty, Epson Road Service
program, PrivateLine[®] dedicated toll-free support and 90-day
lamp limited warranty

What's in the Box

PowerLite 99WH projector, power cord, computer cable (VGA),
projector remote control, batteries, user manual CD, Software
CD, Quick Setup Sheet, warranty card, password protect
sticker

Ordering Information

PowerLite 99WH projector	V11H686020
Genuine Epson lamp (ELPLP88)	V13H010L88
Replacement air filter (ELPAF32)	V13H134A32
Wireless LAN module (ELPAP07)	V12H418P12
Quick Connect USB key (ELPAP09)	V12H005M09
Soft Carrying Case (ELPKS67)	V12H001K67

¹ Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading 1-chip DLP projectors, based on NPD data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. | ² Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | ³ Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | ⁴ Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable wireless connection on your Epson projector. Epson projectors can be networked either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Not all Epson projectors are able to be networked. Availability varies depending on model. | ⁵ Moderator feature is part of EasyMP[®] Multi-PC Projection software. | ⁶ For convenient and reasonable recycling options, visit www.epson.com/recycle | ⁷ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.