

HP LaserJet M3035 MFP series



Accomplish multiple office tasks: printing, copying, scanning, and faxing with this reliable, easy-to-use HP LaserJet MFP. Enhance productivity with embedded send-to-e-mail/network folder functionality, and expandable options.



HP LaserJet M3035 MFP



HP LaserJet M3035xs
MFP

Ideal for small workteams of up to 8 users in enterprise environments, this very reliable, black-and-white HP LaserJet MFP enables them to do handle multiple office workflows from a single, easy-to-use device.

Enable small workteam productivity with this fast, flexible HP LaserJet multifunction device.

Get more done with consolidated print, copy, send-to-e-mail, and analogue fax ¹ functionality. Enjoy fast print and copy speeds of up to 33 ppm, and no wait as HP's Instant-on Technology ensures a fast first page out. Integrate documents into workflows with embedded send-to-e-mail, folder, and fax functionality ¹. Copy and scan double-sided originals with a 50-sheet reversing automatic document feeder. Conserve paper with convenient double-sided printing.

Achieve your goals with a device that is easy to use and manage with a new, intuitive control panel.

Easily use, manage and maintain your device with a new, improved control panel that intuitively takes you through any process. Experience fewer interruptions as interactive HP Smart printing technology ² in the print cartridge and device optimises print quality and reliability. Enjoy best-in-class networking with the HP Jetdirect internal print server which enables data transfer quickly and reliably. HP Web Jetadmin provides remote installation, configuration and proactive management.

Enhance efficiency and expand your LaserJet MFP's capabilities to meet your workteam's needs.

Expand connectivity options with an additional FIH connector, open EIO slot, and Hi-Speed USB 2.0 for access to business process and security solutions. Experience reliable operation with a 400 MHz processor capable of handling complex print, fax ¹ and send-to jobs easily, and expandable memory up to 512MB. Support workgroup efficiency with an input capacity of up to 1,100 sheets ³. An off-line stapler ⁴ enables convenient document finishing. Proven LaserJet quality and reliability.

¹ Fax functionality comes standard on the HP LaserJet M3035xs MFP only and cannot be added to the HP LaserJet M3035 MFP.

² Using genuine HP supplies ensures availability of all HP printing features.

³ The second 500-sheet input tray comes standard on the HP LaserJet M3035xs MFP. It is an optional (sold separately) accessory that can be added to the HP LaserJet M3035 MFP.

⁴ The stapler unit comes standard on the HP LaserJet M3035xs MFP only. It cannot be added to the HP LaserJet M3035 MFP.

HP LaserJet M3035 MFP series

Series at a glance



HP LaserJet M3035 MFP

- HP LaserJet M3035 MFP: print speed of up to 33 ppm
- HP ProRes 1200 and FastRes 1200
- 256 MB memory expandable to 512 MB
- 400 MHz processor
- 40GB Hard Disk
- HP Jet Direct Embedded Print Server
- Embedded Web Server
- open EIO slot
- Hi-Speed USB 2.0
- standard input capacity of 600-sheets with 500-sheet input tray and 100-sheet multipurpose tray
- 50-sheet automatic document feeder
- automatic two-sided printing

HP LaserJet M3035xs MFP

- HP LaserJet M3035xs MFP: as base model with analogue fax
- additional 500-sheet input tray
- 20 sheet integrated convenience stapler

Recommended accessories



J7989G
HP High Performance
Serial ATA EIO Hard
Disk



Q7719A
HP 256 MB 100-pin
DDR DIMM



J7972G
HP 1284B Parallel EIO
Card



Q7817A
HP 500-sheet Paper Tray



T1936AA
HP Digital Sending
Software 4



J7960G
HP Jetdirect 625n
Internal Print Server (EIO,
10/100/1000TX)



J7961G
HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 17.5 to 25° C. Operating humidity: 20 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: -20 to 60° C. Storage humidity: 10 to 90% RH. Noise level per ISO 9296: sound power: LwAd 6.5 B(A) (printing at 35 ppm). Sound pressure: LpAm 56 dB(A) (printing), 54 dB(A) (copy or scan)
Certifications	CISPR 22:1993/EN 55022:1994 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly. Regulatory standards: Argentina (TUV S Mark-Rs.92/98/Ds.1009/98), Australia (AS/NZ 3260), Canada (cUL-CAN/CSA C22.2 No. 60950-1-03), China (GB4943), Czech Republic (CSN-IEC 60950-1; IEC 60825-1), Estonia (EEI-EN60950-1; IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV- EN60950-1; IEC 60825-1), Hungary (MEEI- IEC 60950-1; IEC 60825-1), Lithuania (LS- IEC 60950-1; IEC 60825-1), Russia (GOST- R50377), Slovakia (IEC 60950-1; IEC60825-1), Slovenia (SQI- IEC 60950-1; EN60825-1), South Africa (IEC 60950-1; IEC60825-1), US (UL-UL 60950-1; FDA-21 CFR Chapter 1 Subchapter J for lasers), Class 1 Laser/LED Product. ENERGY STAR: Yes
Warranty	One-year, on-site limited warranty

Ordering information



HP LaserJet M3035 MFP (CB414A)

HP LaserJet M3035 MFP (with duplexer and hard drive), toner cartridge, support flyer, power cord, control panel overlays, software/documentation CD, Getting Started Guide, wall poster



HP LaserJet M3035xs MFP (CB415A)

as CB414A plus convenience stapler, HP Analog Fax, 500-sheet input tray, phone cord

Accessories, Supplies and Support

Accessories

J7989G	HP High Performance Serial ATA EIO Hard Disk
Q7718A	HP 128 MB 100-pin DDR DIMM
Q7719A	HP 256 MB 100-pin DDR DIMM
J7972G	HP 1284B Parallel EIO Card
Q7817A	HP 500-sheet Paper Tray
T1936AA	HP Digital Sending Software 4
Q7432A	HP Staple Cartridge Pack (2 cartridges at 1,500 staples each)

Supplies

Q7551A	HP LaserJet Q7551A Black Print Cartridge with Smart Printing Technology 6,500 pages according to ISO/IEC 19752
Q7551X	HP LaserJet Q7551X Black Print Cartridge with Smart Printing Technology 13,000 pages according to ISO/IEC 19752

Connectivity

C6518A	HP USB Cable, 2m
J7951G	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server
J7960G	HP Jetdirect 625n Internal Print Server (EIO, 10/100/1000TX)
J7961G	HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)

Service & support

UE685A/E	HP Care Pack, Next Business Day On-Site, 3 years
UE691A/E	HP Care Pack, Same Day (4 hours) 13x5, 3 years
UE696PE	HP Care Pack, Post Warranty Next-Business-Day On-Site, 1 year
UE695PE	HP Care Pack, Post Warranty Same Day (4 hours) 13x5, 1 year
UE686E	HP Care Pack, Next Business Day On-Site, 4 years
UE687E	HP Care Pack, Next Business Day On-Site, 5 years
U2010A/E	HP Care Pack, Installation & Network Configuration

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

Technical specifications

Print technology	Monochrome Laser		
Print speed	A4: Up to 33 ppm. First page out black: Less than 10 sec Speed specifications have been updated to reflect current industry testing methods.		
Processor	400 MHz. MIPS embedded in custom HP ASIC		
Memory	256 MB. Expandable to 512 MB through one 100-pin DDR DIMM slot. Hard Disk Capacity: Standard, 40 GB		
Print	Quality	HP ProRes 1200, HP FastRes 1200, 600 dpi, 170 lpi	
	Resolution	Up to 1200 x 1200 dpi	
	Printer languages	HP Postscript Level 3 emulation, PCL 6, PCL 5, PDF 1.4	
	Economical printing	Economode (saves up to 50% toner from 600 dpi), immediate return to Powersafe mode after each print job due to Instant-on fuser technology (saves electricity), optional automatic two-sided printing and N-up printing (saves paper)	
	Typefaces/fonts	80 scalable TrueType fonts	
	Duty cycle	Up to 75000 pages per month	
	Print margins (mm)	Top: 1 mm. Left: 1 mm. Right: 1 mm. Bottom: 2 mm	
Fax	Telecom compliance	Telecom: TBR-21:1998; EG 201 121:1998, FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002:2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong), YD514, YD/T589, YD703, GB3382 (China)	
	Fax memory	Dependent on the amount of available disk space	
	Fax resolution	Standard: 200 x 200 dpi. Superfine: 300 x 300 dpi. Photo: 200 x 200 dpi	
Digital sending	File formats	PDF, JPG, TIFF, MTIFF	
	Installation	Via HP Jetdirect embedded networking, HP Jetdirect internal print servers, HP Jetdirect external print servers, HP wireless print servers, and HP connectivity cards	
Scan	Type	Flatbed, ADF. Colour scanning: Yes	
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up to 1200 dpi	
	Grey scale levels	256	
	Scannable area	Maximum media size: 21.6 x 29.7 cm	
	Margins for scanned items	Left: 4.2 mm. Top: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm	
Copy	Copy speed	Up to 33 cpm	
	Copy resolution	600 dpi	
	Multiple copies	Up to 1000	
	Reduce/enlarge	25 to 400%	
Media handling	Input:	Capacity	Weight
	Tray 1	Sheets: 100, transparencies: 50, envelopes: 10, labels 50	60 to 199 g/m ²
	Tray 2	Sheets: 500	60 to 120 g/m ²
	Tray 3	Sheets: 500	60 to 120 g/m ²
	ADF	Sheets: 50	60 to 105 g/m ²
	Output:	Sheets: Up to 250. Envelopes: Up to 10. Transparencies: Up to 50	
	Duplex printing:	Automatic (standard)	
Media types	Paper (plain, photo, banner), envelopes, labels, cards (index, greeting), overhead transparencies		
Interface and connectivity	Optional: HP Jetdirect 635n IPv6/IPsec Print Server J7961A, HP Jetdirect 625n Gigabit Ethernet Print Server J7960A, HP Jetdirect 620n Fast Ethernet Print Server J7934A, HP Jetdirect ew2400 802.11g Wireless Print Server (USB 2.0) J7951A, HP Jetdirect en3700 Fast Ethernet Print Server (USB 2.0) J7942A, HP Jetdirect 175x Fast Ethernet Print Server (USB 1.1) J6035D, HP High Performance Serial ATA Hard Disk J7989G, HP 1284B Parallel Card J7972G, HP Jetdirect Connectivity Card J4135A, HP bt450 Bluetooth Wireless Printer and PC Adapter Q6398A, HP bt400 Bluetooth Wireless Printer Adapter Q6399A		
Operating systems compatibility	Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. Latest print drivers available from HP Support Web site at http://www.hp.com/support/ljm3035mp		
Network operating systems compatibility	Windows® NT 4.0, 98, 2000, Me, XP Home, XP Professional, XP Professional x64 Edition (Itanium only), Windows® Server 2003 (IPv6 is only supported on Windows® 2003, XP Home, XP Professional), Novell® NetWare 3.2, 4.2, 5.x, 6.x (NDPS), Mac OS 8.6 and later, RED HAT Linux 6.x, 7.x, 8.x, 9.x, SUSE Linux 6.x, 7.x, 9.x, HP UX 10.20, 11.x, 11i, Solaris® 2.5x, 2.6, 2.7, 2.8 (SPARC systems only), IBM® AIX 3.2.5 and higher, MPE-iX, Unix, Citrix® MetaFrame, Windows® Terminal Servers		
Minimum system requirements	133 MHz processor or higher; 64 MB of RAM; 40 MB available hard disk space; USB or network port connection. Mac OS 10.2 and higher; 128 MB RAM, 25 MB available hard disk space; network or USB port		
Control panel	CCFL backlit STN LCD (640 x 240) with analog touch screen; contrast adjust thumbwheel; device status LEDs: Ready, Data, Attention, Start, Sleep; hard keys: 13-key numeric keypad; Sleep key; Reset key; Stop key; Start key		
Power	Requirements: Input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp. Consumption: 0.1 watts maximum (off), 24 watts maximum (sleep), 280 watts maximum (ready), 600 watts maximum (printing), 1265 watts maximum (copying)		
Dimensions (w x d x h)	Out of package: M3035 MFP: 426 x 485 x 530 mm; M3035xs MFP: 426 x 485 x 670 mm. Packaged: M3035 MFP: 600 x 630 x 670 mm; M3035xs MFP: 600 x 630 x 950 mm		
Weight	Out of package: M3035 MFP: 27.56 kg; M3035xs MFP: 33.44 kg. Packaged: M3035 MFP: 31.88 kg; M3035xs MFP: 40.65 kg		

<http://www.hp.com/uk>



© 2006 Copyright Hewlett-Packard Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 10/06 4AA0-5303EEE

