


HDMI Audio/Video with RS-232 Serial and IR Control over IP Receiver, 1920 x 1080 (1080p) @ 60 Hz, 328 ft. (100 m)

MODEL NUMBER: **B160-100-HDSI**



Highlights

- Designed for managed network switches with IGMP
- Compatible with all analog or digital sources
- Supports video resolutions up to 1920 x 1080 (1080p)
- Plug and play—no software or drivers required
- Mounts on wall, rack or pole with included hardware

Package Includes

- Receiver unit
- External power supply w/NEMA 1-15P plug (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V, 2A)
- Plug adapters for U.S., U.K., Europe and Australia
- IR-In cable
- HDMI to DVI adapter cable
- Mounting hardware
- Owner's manual

Description

The B160-100-HDSI HDMI Audio/Video with RS-232 Serial and IR Control over IP Receiver extends and distributes HDMI/DVI video (adapter cable included for connecting DVI display), RS-232 serial and IR (infrared) remote signals through a dedicated Ethernet network switch* located up to 328 feet (100 m) away. With an additional 328 feet between the switch and the transmitter (sold separately), the total maximum distance from source to display is 656 feet (200 m).

The B160-100-HDSI is designed for managed network switches with IGMP, which allow login and remote management via switch interface. You can connect up to 64 transmitters and 255 receivers in a single managed switch installation.**

The B160-100-HDSI supports video resolutions up to 1920 x 1080 (1080p) at 60 Hz. It works with any analog or digital source, including DisplayPort and VGA. It extends IR control signals that control a source, such as a Blu-ray™ player, from a remote display, as well as RS-232 signals at serial baud rates up to 57600 Bps.

Compatible with Tripp Lite's B160-001-DPSI, B160-001-HDSI and B160-001-VSI transmitters.

**B160-Series designed for use with dedicated network switch. Connecting to a switch used with other networking equipment will result in degraded or non-functional performance.*

***Unmanaged switch installations are limited to two transmitter units. Number of receivers is limited to number of ports remaining on unmanaged switch.*

Features

Extends and Distributes HDMI/DVI A/V, Serial and IR Control Signals over Cat5/6 Cabling

- Converts source video to IP-based signal transmitted to and distributed through network switch
- Adapter cable included for connecting a DVI display
- Extends signal up to 328 ft. (100 m) from switch



- Can also connect directly to transmitter up to 328 ft. away

Designed for Managed Network Switches with IGMP

- Allows login and remote management via switch interface
- Works with any analog or digital source, including DisplayPort and VGA
- Connect up to 64 transmitters and 255 receivers in single managed switch installation

Enhanced Technical Features

- Supports video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Uses H.264 video compression standard
- Transmits on 20–60 kHz IR frequency
- Extends IR control signals that control a source from a remote display
- Supports RS-232 serial baud rates up to 57600 Bps
- HDCP and 3D compatible when used with a DisplayPort or HDMI transmitter (not compatible with VGA transmitter)

Plug and Play Functionality

- No software or drivers required
- Hardware included for mounting on wall, rack or pole
- Compatible with B160-001-DPSI, B160-001-HDSI and B160-001-VSI transmitters

TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

COMMUNICATIONS	
Max 1024 x 768 Range (ft)	328
Max 480P Range (ft)	328
Max 1440 x 900 Range (ft)	328
Max 1080i Range (ft)	328
Max 1080P Range (ft)	328
Max 1920 x 1440 Range (ft)	328
Max 480i Range (ft)	328
Max 640 x 480 Range (ft)	328
Max 800 x 600 Range (ft)	328
Max 1600 x 1200 Range (ft)	328
Max 1920 x 1200 Range (ft)	328
Max 720P Range (ft)	328
CONNECTIONS	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Ports	1
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>